

RPPM

Flexible, Dual Wall, Moisture-Proof, Heat-Shrinkable Tubing

Product Facts

- Environmental sealing
- Excellent mechanical strength
- Abrasion resistance
- 4:1 shrink ratio
- RoHS compliant



Applications

RPPM is a flexible, heatshrinkable, dual wall tubing with an integrally bonded meltable adhesive liner. Available in clear and black, the tough outer jacket offers excellent mechanical strength. RPPM is used for moisture-proof encapsulation of a wide variety of components. In particular, it adheres well to PVC. The high-shrink-ratio allows RPPM to be used with a range of dimensions. Clear RPPM offers excellent clarity for protection of substrates that may need to be inspected during service. Black RPPM has a high gloss finish suitable for cosmetic applications.

Installation

Minimum shrink temperature: 60°C [140°F] Minimum full recovery temperature: 80°C [176°F]

Operating Temperature Range

-40°C to 85°C [-40°F to 185°F]

Specifications/Approvals

Series	Raychem
RPPM	RK-6214

		Available in:	Americas		Europe	Asia Pacific	
							1-97
9-1773447-9 CIS WR 08/2011	Dimensions are millimeters unles specified. Values	ss otherwise	Dimensions are shown fo reference purposes only. Specifications subject	Canada	800-522-6752 1-905-475-6222 52-55-1106-0800	Germany: 49-6251-133-1999 China: 86-400-820-6015 Japan: 81-44-844-8013	9
te.com	are metric equiva		Downloaded From		54 44 4700 0000		



RPPM (Continued)

Product Dimensions

	Inside Diameter		Recovered Wall Thickness*		
Size	Minimum Expanded as Supplied	Maximum Recovered After Heating	Nominal Total Wall After Heating	Nominal Adhesive Wall After Heating	
4/1	4.0 [0.158]	1.0 [0.039]	0.8 [0.032]	0.3 [0.012]	
8/2	8.0 [0.315]	2.0 [0.079]	0.9 [0.035]	0.3 [0.012]	
12/3	12.0 [0.472]	3.0 [0.118]	1.2 [0.047]	0.4 [0.016]	
16/4	16.0 [0.630]	4.0 [0.158]	1.5 [0.059]	0.5 [0.020]	

*Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Clear (-X)
	Nonstandard	Black (-0)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.	
Standard packaging	On spools, in 1.2 meter [4-foot] lengths or cut pieces.	
Ordering description	Specify product name, size and color (for example, RPPM 4/1-X).	

9-1773447-9 CIS WR 08/2011

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject

USA: 1-800-522-6752 Canada: 1-905-475-6222 Mexico: 52-55-1106-0800 erica: 54-11-4733-2200 Downloaded From Oneyac.com

Germany: 49-6251-133-1999 China: 86-400-820-6015 Japan: 81-44-844-8013 UK: 44-800-267-666



单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)