




## GaAs MMIC I/Q DOWNCONVERTER 21 - 24 GHz

### Typical Applications

The HMC967LP4E is ideal for:

- Point-to-Point and Point-to-Multi-Point Radio
- Military Radar, EW & ELINT
- Satellite Communications

### Functional Diagram



### Features

- Conversion Gain: 15 dB
- Image Rejection: 25 dBc
- 2 LO to RF Isolation: 40 dB
- Noise Figure: 2.5 dB
- Input IP3: 1 dBm
- 24 Lead 4 x 4 mm SMT Package: 16 mm<sup>2</sup>

### General Description

The HMC967LP4E is a compact GaAs MMIC I/Q downconverter in a leadless RoHS compliant SMT package. This device provides a small signal conversion gain of 15 dB with a noise figure of 2.5 dB and 25 dBc of image rejection across the frequency band. The HMC967LP4E utilizes an LNA followed by an image reject mixer which is driven by an active x2 multiplier. The image reject mixer eliminates the need for a filter following the LNA, and removes thermal noise at the image frequency. I and Q mixer outputs are provided and an external 90° hybrid is needed to select the required sideband. The HMC967LP4E is a much smaller alternative to hybrid style image reject mixer downconverter assemblies, and is compatible with surface mount manufacturing techniques.

### Electrical Specifications, $T_A = +25^\circ\text{C}$ , IF = 1000 MHz, LO = +6 dBm, Vdd = 3.5 Vdc USB <sup>[1]</sup>

Parameter	Min.	Typ.	Max.	Units
Frequency Range, RF		21 - 24		GHz
Frequency Range, LO		8.8 - 13.5		GHz
Frequency Range, IF		DC - 3.5		GHz
Conversion Gain (As IRM)	11	15		dB
Noise Figure		2.5	3.5	dB
Image Rejection	15	25		dBc
1 dB Compression (Input)		-8.5		dBm
2 LO to RF Isolation	32	40		dB
2 LO to IF Isolation	14	20		dB
IP3 (Input)	-2	1		dBm
Amplitude Balance <sup>[2]</sup>		0.5		dB
Phase Balance <sup>[2]</sup>		-12		deg
Total Supply Current		170	210	mA

[1] Data taken as IRM with external IF 90° Hybrid

[2] Data taken without external 90° hybrid, IF = 500 MHz

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.


For price, delivery, and to place orders: Analog Devices, Inc., One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106 Phone: 781-329-4700 • Order online at [www.analog.com](http://www.analog.com) Support: Phone: 1-800-ANALOG-D




**GAAS MMIC I/Q DOWNCONVERTER**  
**21 - 24 GHz**

*Data Taken As IRM With External IF 90° Hybrid, IF = 1000 MHz*


**Conversion Gain USB vs. Temperature**




**Conversion Gain USB vs. LO Drive**




**Image Rejection vs. Temperature**




**RF Return Loss vs. Temperature**



**LO Return Loss vs. Temperature**









**IF Return Loss <sup>[1]</sup>**



[1] Data taken without external 90° hybrid.


**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**

Data Taken as IRM With External IF 90° Hybrid, IF = 1000 MHz


**Isolations**

**Input P1dB USB vs. Temperature**

**Input IP3, USB vs. Temperature**

**Input IP3, USB vs. LO Drive**

**Noise Figure vs. LO Drive,  
LO Frequency = 8.25 GHz**

**Noise Figure vs. Temperature,  
IF Frequency = 1000 MHz**





**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**

**Quadrature Channel Data Taken Without IF 90° Hybrid, IF = 1000 MHz**


**IF Bandwidth <sup>[1]</sup>**



**Amplitude Balance vs. LO Drive <sup>[2]</sup>**



**Phase Balance vs. LO Drive <sup>[1]</sup>**









[1] Data taken with LO frequency fixed at 8.5 GHz and RF varied.

[2] Data taken with IF = 500 MHz







**GAAS MMIC I/Q DOWNCONVERTER**  
**21 - 24 GHz**

Data Taken as IRM With External IF 90° Hybrid, IF = 1000 MHz

**Conversion Gain, LSB vs. Temperature**

**Conversion Gain, LSB vs. LO Drive**

**Image Rejection vs. Temperature**

**Input P1dB, LSB vs. Temperature**

**Input IP3, LSB vs. Temperature**

**Input IP3, LSB vs. LO Drive**








**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**

Data Taken as IRM With External IF 90° Hybrid, IF = 2000 MHz

**Conversion Gain, USB vs. Temperature**

**Conversion Gain, USB vs. LO Drive**

**Image Rejection vs. Temperature**

**Input IP3, USB vs. Temperature**

**Input IP3, USB vs. LO Drive**



**GAAS MMIC I/Q DOWNCONVERTER**  
**21 - 24 GHz**

Data Taken as IRM With External IF 90° Hybrid, IF = 2000 MHz


**Conversion Gain, LSB vs. Temperature**

**Conversion Gain, LSB vs. LO Drive**

**Image Rejection vs. Temperature**

**Input IP3, LSB vs. Temperature**

**Input IP3, LSB vs. LO Drive**





**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**

**Data Taken as IRM With External IF 90° Hybrid, IF = 3300 MHz**


**Conversion Gain, USB vs. Temperature**




**Conversion Gain, USB vs. LO Drive**




**Image Rejection vs. Temperature**



**Input IP3, USB vs. Temperature**



**Input IP3, USB vs. LO Drive**









**GAAS MMIC I/Q DOWNCONVERTER**  
**21 - 24 GHz**

*Data Taken as IRM With External IF 90° Hybrid, IF = 3300 MHz*


**Conversion Gain, LSB vs. Temperature**




**Conversion Gain, LSB vs. LO Drive**




**Image Rejection vs. Temperature**



**Input IP3, LSB vs. Temperature**



**Input IP3, LSB vs. LO Drive**





## GAAS MMIC I/Q DOWNCONVERTER 21 - 24 GHz

### MxN Spurious Outputs

	nLO				
mRF	0	1	2	3	4
0	x	-24.2	-4.3	-29.3	-34.4
1	-25.6	-40.6	0	-43.8	-34.6
2	-67.4	-86.9	-57.4	-66.2	-45.3
3	x	x	-96.6	-102.8	-71.3
4	x	x	x	x	-108.8

RF = 22 GHz @ -20 dBm  
LO = 10.5 GHz @ +4 dBm  
Data taken without IF hybrid  
All values in dBc below IF power level (1RF -2LO = 1 GHz)


### Absolute Maximum Ratings

RF	+2 dBm
LO Drive	+10 dBm
Vdd	4V
Channel Temperature	175 °C
Continuous P <sub>diss</sub> (T=85°C) (derate 12.5 mW/°C above 85°C)	1.13 W
Thermal Resistance (R <sub>TH</sub> ) (channel to package bottom)	79.6 °C/W
Storage Temperature	-65 to +150 °C
Operating Temperature	-55 to +85 °C
ESD Sensitivity (HBM)	Class 1A



ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS

### Outline Drawing









### Package Information


Part Number	Package Body Material	Lead Finish	MSL Rating	Package Marking <sup>[1]</sup>
HMC967LP4E	RoHS-compliant Low Stress Injection Molded Plastic	100% matte Sn	MSL1 <sup>[2]</sup>	H967 XXXX

[1] 4-Digit lot number XXXX

[2] Max peak reflow temperature of 260 °C


**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**
**Pin Descriptions**


Pin Number	Function	Description	Interface Schematic
1, 2, 6, 7, 10 - 12, 15, 18 - 22	N/C	The pins are not connected internally; however, all data shown herein was measured with these pins connected to RF/DC ground externally.	
3	VDRF	Power supply for RF LNA.	
4	VDLO2	Power supply for second stage of LO amplifier.	VDLO2 
5	VDLO1	Power supply for first stage of LO amplifier.	VDLO1 
8	LO	This pin is AC coupled and matched to 50 Ohms.	LO 
9, 13, 17, 24	GND	These pins and the exposed ground paddle must be connected to RF/DC ground.	GND 
16	IF2	This pin is DC coupled. For applications not requiring operation to DC this port should be DC blocked externally using a series capacitor whose value has been chosen to pass the necessary frequency range. For operation to DC, this pin must not sink / source more than 3 mA of current or part non-function and possible failure will result.	IF1, IF2 
14	IF1		
23	RF	This pin is AC coupled and matched to 50 Ohms	RF 

**Typical Application Circuit**




**GAAS MMIC I/Q DOWNCONVERTER  
21 - 24 GHz**

**Evaluation PCB**



**List of Materials for Evaluation PCB 131656 [1]**

Item	Description
J1	PCB Mount SMA RF Connector, SRI
J2, J3	PCB Mount K Connector, SRI
J5 - J8	DC Pin
C1, C4, C7	100 pF Capacitor, 0402 Pkg.
C2, C5, C8	10 nF Capacitor, 0402 Pkg.
C3, C6, C9	4.7 $\mu$ F Capacitor, Case A Pkg.
U1	HMC967LP4E
PCB [2]	161653 Evaluation Board

[1] Reference this number when ordering complete evaluation PCB

[2] Circuit Board Material: Rogers 4350

The circuit board used in the application should use RF circuit design techniques. Signal lines should have 50 Ohm impedance while the package ground leads and exposed paddle should be connected directly to the ground plane similar to that shown. A sufficient number of via holes should be used to connect the top and bottom ground planes. The evaluation circuit board shown is available from Hittite upon request.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Analog Devices Inc. \(亚德诺\)](#)