



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	1/11

1. Scope

This specification applied to the products of Lead-Free current sensing resistor of metal foil for Lead-Free RLS series manufactured by TA-I TECHNOLOGY CO.,LTD.

2. Type Designation

RLS12	F	T	C	R005																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Series No.</th> </tr> </thead> <tbody> <tr><td>04 : 0402</td></tr> <tr><td>06 : 0603</td></tr> <tr><td>10 : 0805</td></tr> <tr><td>12 : 1206</td></tr> <tr><td>25 : 2512</td></tr> </tbody> </table>	Series No.	04 : 0402	06 : 0603	10 : 0805	12 : 1206	25 : 2512	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Tolerance</th> </tr> </thead> <tbody> <tr><td>F= ±1%</td></tr> <tr><td>G= ±2%</td></tr> <tr><td>J= ±5%</td></tr> </tbody> </table>	Tolerance	F= ±1%	G= ±2%	J= ±5%	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Packaging</th> </tr> </thead> <tbody> <tr><td>T= Paper</td></tr> <tr><td>E= Embossed</td></tr> </tbody> </table>	Packaging	T= Paper	E= Embossed	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Power</th> </tr> </thead> <tbody> <tr><td>P= 0.0625W</td></tr> <tr><td>K= 0.2W</td></tr> <tr><td>A= 0.25W</td></tr> <tr><td>S= 0.5W</td></tr> <tr><td>I= 0.75W</td></tr> <tr><td>C= 1.0W</td></tr> <tr><td>E= 2.0W</td></tr> </tbody> </table>	Power	P= 0.0625W	K= 0.2W	A= 0.25W	S= 0.5W	I= 0.75W	C= 1.0W	E= 2.0W	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Resistance</th> </tr> </thead> <tbody> <tr><td>R005=5mΩ</td></tr> <tr><td>R0065=6.5mΩ</td></tr> <tr><td>R010= 10mΩ</td></tr> <tr><td>*For 0402</td></tr> <tr><td>R0Z10=Jumper</td></tr> <tr><td>Max resistance</td></tr> <tr><td>10mΩ</td></tr> </tbody> </table>	Resistance	R005=5mΩ	R0065=6.5mΩ	R010= 10mΩ	*For 0402	R0Z10=Jumper	Max resistance	10mΩ
Series No.																																	
04 : 0402																																	
06 : 0603																																	
10 : 0805																																	
12 : 1206																																	
25 : 2512																																	
Tolerance																																	
F= ±1%																																	
G= ±2%																																	
J= ±5%																																	
Packaging																																	
T= Paper																																	
E= Embossed																																	
Power																																	
P= 0.0625W																																	
K= 0.2W																																	
A= 0.25W																																	
S= 0.5W																																	
I= 0.75W																																	
C= 1.0W																																	
E= 2.0W																																	
Resistance																																	
R005=5mΩ																																	
R0065=6.5mΩ																																	
R010= 10mΩ																																	
*For 0402																																	
R0Z10=Jumper																																	
Max resistance																																	
10mΩ																																	

3. Features

Series	Size	Power (W)	Resistance Value	Operation Temperature Range	TCR	Tolerance
RLS04	0402	0.0625	Max. resistance 10mΩ Max. Current 3A	-55°C~+125°C	±100ppm/°C	5%
		0.25	5 ~ 20mΩ			±1% ±2% ±5%
RLS06	0603	0.50	3 ~ 20mΩ	-55°C~+155°C	±50ppm/°C	±1% ±2% ±5%
RLS10	0805	0.75	5 ~ 100mΩ			
RLS12	1206	1.0	3 ~ 200mΩ			
RLS25	2512	2.0	5 ~ 10mΩ			




Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	2/11


4. Construction and Dimension

4.1 RLS04 & RLS06

Marking: For 0402 & 0603 No Marking



RLS04 \geq 10 m ohm and RLS06



RLS04 < 10 m ohm

Series	L	W	C	T
RLS04	1.10±0.10	0.55±0.10	0.30±0.10	0.45±0.10
RLS06	1.60±0.20	0.80±0.20	0.40±0.20	0.60±0.20


UNIT: mm



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	3/11

3.2 RLS10 to RLS25



Marking

For 0805 to 2512:

Resistance value is expressed by 3-4 digits.

E.G.:

005 = 0.005Ω = 5 mΩ

010 = 0.010Ω = 10mΩ

6.5 = 0.0065Ω = 6.5mΩ

R100=0.1Ω=100mΩ

R150=0.15Ω=150mΩ

Series	L	W	C	T
RLS10	2.00±0.20	1.25±0.20	0.40±0.30	0.70±0.20
RLS12	3.20±0.20	1.60±0.20	0.50±0.30	0.70±0.20
RLS25	6.40±0.20	3.20±0.20	0.90±0.20	0.70±0.20

Unit: mm

5. Reliability Tests

Test Items	Reference standard	Condition of Test	Test Limits
Temperature Coefficient of Resistance	IEC60115-1 4.8	+25 ~ 125°C	Refer item 4
Short Time Overload	IEC60115-1 4.13	5 X rated power for 5s	< ±1%
High Temperature Exposure (Storage)	AEC-Q200-REV D-Test 3 MIL-STD-202 Method 108	1000 hrs. @ T=125°C. Unpowered. Measurement at 24±2 hours after test conclusion.	< ±1%
Temperature Cycling	AEC-Q200-REV D-Test 4 JESD22 Method JA-104	1000 Cycles (-55°C to +125°C) Measurement at 24±4 hours after test conclusion. 30min maximum dwell time at each temperature extreme. 1 min. maximum transition time.	< ±1%
Moisture Resistance	AEC-Q200-REV D-Test 6 MIL-STD-202 Method 106	T=24 hours / Cycle ,10 Cycles. Notes: Steps 7a& 7b not required. Unpowered	< ±1%
Biased Humidity	AEC-Q200-REV D-Test 7 MIL-STD-202 Method 103	1000 hours 85°C/85%RH. Note: Specified conditions: 10% of operating power (not exceeding max working voltage). Measurement at 24±2 hours after test conclusion.	< ±1%



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	4/11

Operational Life	AEC-Q200-REV D-Test 8 MIL-STD-202 Method 108	1000 hours TA=125°C at 35% rated power. Measurement at 24±4 hours after test conclusion.	< ±2%
External Visual	AEC-Q200-REV D-Test 9 MIL-STD-883 Method 2009	Electrical test not required. Inspect device construction, marking and workmanship.	
Physical Dimension	AEC-Q200-REV D-Test 10 JESD22 Method JB-100	Verify physical dimensions to the applicable device detail specification. Note: User(s) and Suppliers spec. Electrical test not required.	
Resistance to Solvents	AEC-Q200-REV D-Test 12 MIL-STD-202 Method 215	a: Isopropyl Alcohol : Mineral Spirits= 1 : 3 b: Terpene Defluxer (Bioact EC-7R) c: Deionized water : Propylene Glycol Monomethyl Ether : monoethanolamine =42 : 1 : 1	Marking and protective layer cannot be detached
Mechanical Shock	AEC-Q200-REV D-Test 13 MIL-STD-202 Method 213	Wave Form: Tolerance for half sine shock pluse. Peak value is 100g's. Normal duration(D) is 6(ms)	< ±1.0%
Vibration	AEC-Q200-REV D-Test 14 MIL-STD-202 Method 204	5 g's for 20 min., 12 cycles each of 3 orientations. Note: Test from 10-2000 Hz.	< ±1.0%
Resistance to Soldering Heat	AEC-Q200-REV D-Test 15 MIL-STD-202 Method 210	Condition B: Immerse the specimens in and eutectic solder at 260±5°C for 10±1S.	< ±0.5%
Thermal Shock	AEC-Q200-REV D-Test 16 MIL-STD-202 Method 107	-55°C/+155°C. Note: Number of cycles required-300, Maximum transfer time-20 seconds, Dwell time-15 minutes. Air-Air.	< ±1.0%
ESD	AEC-Q200-REV D-Test 17 AEC-Q200-002 or ISO/DIS 10605	verify the voltage setting at 500V	< ±1.0%
Solderability	AEC-Q200-REV D-Test 18 J-STD-002	Method B, aging 4 hours at 155 °C dry heat Lead-free solder bath at 235±3 °C Dipping time: 3±0.5 seconds	> 95% area covered with tin
Flammability	AEC-Q200-REV D-Test 20 UL-94	V-0 are acceptable. Electrical test not required.	V-0
Board Flex (Bending)	AEC-Q200-REV D-Test 21 AEC-Q200-005	The duration of the applied forces shall be 60 (+ 5) Sec 3mm deflection (RLS04~ RLS 12) 2mm deflection (RLS 25)	< ±1.0%
Terminal Strength (SMD)	AEC-Q200-REV D-Test 22 AEC-Q200-006	RLS04: Force of 1.0 kg for 60 seconds Remarks: 0201-NA	< ±1.0%
		RLS06~ RLS 12: Force of 1.8kg for 60 seconds Remarks: 0201-NA	




Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified


Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	5/11

5.1 Derating Curve

5.1.1 RLS04



5.1.2 RLS06 to RLS25





Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	6/11

5.2 Rated Current

The rated current is calculated by the following formula:

$$I = \sqrt{P \div R}$$

$$V = \sqrt{P \times R}$$


I: Rated Current (A)

V: Rated Voltage (V)

P: Rated Power (W)

R: Resistance Value (Ω)

6. Recommended Solder Pad Dimension



Series	Resistance (m Ω)	A	L	B
RLS04	$5 \leq R \leq 20$	0.7	0.45	0.375
RLS06	$3 \leq R \leq 20$	1.0	0.6	1.1
RLS10	$5 \leq R \leq 100$	1.4	1.2	1.0
RLS12	$5 \leq R \leq 35$	1.8	1.6	1.55
	$36 \leq R \leq 200$	1.8	2.2	1.35
RLS25	$5 \leq R \leq 10$	4.0	4.1	2.1

Unit: mm

*1 The copper foil minimum thickness of PCB needs 3 oz

*2. PCB Dimension Tolerance is +/-0.1mm.

*3 The Resistance will change slightly after soldered, it is depended on PCB PAD size deign and its necessary to consider the effect of the resistance increase or decrease.




Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	7/11


7. Number of Package

Series	RLS04	RLS06	RLS10	RLS12	RLS25
Pieces/Package	10000	5000	4000	4000	4000

8. Label



9. Packaging



Tape packaging dimension


Packing	Type	A	B	W	F	E	P1	P2	P0	$\phi D0$	T
Paper	RLS04	0.75 ± 0.05	1.30 ± 0.05	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10	2.00 ± 0.10	2.00 ± 0.10	4.00 ± 0.10	1.55 ± 0.10	0.65 ± 0.10
	RLS06	1.10 ± 0.15	1.90 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	4.00 ± 0.10	1.55 ± 0.10	0.85 ± 0.10
	RLS10	1.60 ± 0.15	2.40 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	4.00 ± 0.10	1.55 ± 0.10	1.05 ± 0.10
	RLS12	2.00 ± 0.15	3.60 ± 0.20	8.00 ± 0.20	3.50 ± 0.05	1.75 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	4.00 ± 0.10	1.55 ± 0.10	1.05 ± 0.10

Unit: mm



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	8/11




Tape packaging dimension

Packing	Type	A	B	W	F	E	P1	P2	P0	$\phi D0$	t
Embossed	RLS25	3.60 ± 0.15	6.90 ± 0.20	12.0 ± 0.20	5.50 ± 0.05	1.75 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	4.00 ± 0.10	1.55 ± 0.10	0.85 ± 0.10

Unit: mm

10. Reel Specification



Series	ϕA	ϕB	ϕC	W	T
RLS04	178 ± 2.0	60 ± 1.0	13.0 ± 1.0	9.0 ± 1.0	11.4 ± 1.0
RLS06 RLS10 RLS12	180 ± 2.0	60 ± 1.0	13.0 ± 1.0	9.0 ± 1.0	11.4 ± 1.0
RLS25	180 ± 2.0	60 ± 1.0	13.0 ± 1.0	13.0 ± 1.0	15.4 ± 1.0

Unit: mm




Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	9/11

11. Peeling Strength of Top Cover Tape

Test Condition: 0.1 to 0.7 N at a peel-off speed of 300 mm / min.



12. Storage Conditions

Temperature: 5°C~35°C, Humidity:40%~75%

Moisture Sensitivity Level: Level 1

13. Shelf Life


2 years from manufacturing date.



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	10/11

14. Recommend IR – Reflow profile (solder: Sn96.5 / Ag3 / Cu0.5)



Allowed Re-flow times: 3 times

Remark: To avoid discoloration phenomena of chip on terminal electrodes, please use N2 Re-flow furnace.

Iron Solder: 350±10°C, 3+1/-0 sec, 1 time


Profile Feature	Lead (Pb)-Free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C / second max.
Preheat - Temperature Min (T _{Amin}) - Temperature Max (T _{smax}) - Time (T _{Amin} to T _{smax}) (ts)	150°C 200°C 60 -120 seconds
Time maintained above: - Temperature (T _L) - Time (T _L)	217°C 60-150 seconds
Peak Temperature (T _p)	260°C
Time within $\begin{matrix} +0 \\ -5 \end{matrix}$ °C of actual Peak Temperature (tp) ²	10 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8minutes max.



Lead-Free Current Sensing Resistors
RLS Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLS-XX0S002G
Issued date	2024/6/18
page	11/11

15. Recommend Wave-Solder profile (solder: Sn96.5 / Ag3 / Cu0.5)



16. ECN

Engineering Change Notice: The customer will be informed with ECN if there is significant modification on the characteristics and materials described in Approval Sheet.

17. Manufacturing Country & City

TA-I TECHNOLOGY CO., LTD. (Taiwan- Tao Yuan)

Tel: (+886) 3-3246169 Fax: (+886) 3-3246167

Associated companies:

(1) TA-I TECHNOLOGY (SU ZHOU) CO., LTD. (China - Su Zhou)

Tel :(+86) 512-63457879 Fax: (+86) 512-63457869

(2) TA-I TECHNOLOGY ELECTRONIC (DONGGUAN) CO., LTD. (China -Dongguan)

Tel : (+86) 769-8339-4790~3 Fax: (+86) 769-8339-4794

(3) FORTUNE TASK RESISTOR FACTORY (China - Dongguan)

Tel : (+86) 769-8339-4790~3 Fax: (+86) 769-8339-4794

(4) TAI OHM ELECTRONICS (M) SDN. BHD. (Malaysia - Penang)

Tel :(+60) 4- 3900480 Fax: (+60) 4-3901481

单击下面可查看定价，库存，交付和生命周期等信息

[>>TA-I\(大毅\)](#)