

Features

- Fixed Output Voltage: 2.048V, 2.5V, 3V, 4.096V, 5V, 8.192V and 10V
- High Initial Accuracy and Low Temperature Coefficient
 - Max 0.1%, 25ppm/°C – A Grade
 - Max 0.2%, 50ppm/°C – B Grade
- Operation From -40°C to 125°C
- Sink Current Capability: 150µA to 15mA
- Stable with Any Capacitive Loads


Applications

- Power
- Led Lighting
- Current Sensing
- Instrumentation
- Industry


Description

The TPR6040 is shunt voltage reference with guaranteed temperature stability over the entire operating temperature range. The device temperature range is extended for the automotive version from -40 °C up to +125 °C. The TPR6040 operate with a wide current range from 0.15 to 15 mA with a typical dynamic impedance of 0.3 Ω.

Pin Configuration



Typical Connection



$$I_R = (V_{BIAS} - V_{OUT}) / R_{BIAS} - I_{O_{OUT}}$$

$$I_{R_{MIN}}(0.15mA) \leq I_R \leq I_{R_{MAX}}(15mA)$$

Order Information

Order Number	Output Voltage	Grade	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity
TPR6040F20-S3TR-S	2.048	A	-40 to 125°C	SOT23-G	R6B	MSL 3	3000
TPR6040F25-S3TR-S	2.5	A	-40 to 125°C	SOT23-G	R6C	MSL 3	3000
TPR6040F30-S3TR-S	3	A	-40 to 125°C	SOT23-G	R6D	MSL 3	3000
TPR6040F33-S3TR-S ^{Note1}	3.3	A	-40 to 125°C	SOT23-G	R6E	MSL 3	3000
TPR6040F40-S3TR-S	4.096	A	-40 to 125°C	SOT23-G	R6F	MSL 3	3000
TPR6040F50-S3TR-S	5	A	-40 to 125°C	SOT23-G	R6G	MSL 3	3000
TPR6040F80-S3TR-S ^{Note1}	8.192	A	-40 to 125°C	SOT23-G	R6H	MSL 3	3000
TPR6040FA0-S3TR-S ^{Note1}	10	A	-40 to 125°C	SOT23-G	R6I	MSL 3	3000
TPR6040F20-S3TR	2.048	B	-40 to 125°C	SOT23-G	R6B	MSL 3	3000
TPR6040F25-S3TR	2.5	B	-40 to 125°C	SOT23-G	R6C	MSL 3	3000
TPR6040F30-S3TR	3	B	-40 to 125°C	SOT23-G	R6D	MSL 3	3000
TPR6040F33-S3TR ^{Note1}	3.3	B	-40 to 125°C	SOT23-G	R6E	MSL 3	3000
TPR6040F40-S3TR	4.096	B	-40 to 125°C	SOT23-G	R6F	MSL 3	3000
TPR6040F50-S3TR	5	B	-40 to 125°C	SOT23-G	R6G	MSL 3	3000
TPR6040F80-S3TR ^{Note1}	8.192	B	-40 to 125°C	SOT23-G	R6H	MSL 3	3000
TPR6040FA0-S3TR ^{Note1}	10	B	-40 to 125°C	SOT23-G	R6I	MSL 3	3000

Note 1: The sample will be ready after 2 months when production start.

Table of Contents

Features	1
Applications	1
Description	1
Pin Configuration	1
Typical Connection	1
Order Information	2
Table of Contents	3
Revision History	3
Absolute Maximum Ratings ^{Note 1}	4
ESD Rating	4
Thermal Information	4
Recommended Operating Conditions	4
Electrical Characteristics – TPR6040F20, 2.048V Output	5
Electrical Characteristics – TPR6040F25, 2.5V Output	6
Electrical Characteristics – TPR6040F30, 3.0V Output	7
Electrical Characteristics – TPR6040F33, 3.3V Output	8
Electrical Characteristics – TPR6040F40, 4.096V Output	9
Electrical Characteristics – TPR6040F50, 5V Output	10
Electrical Characteristics – TPR6040F80, 8.196V Output	11
Electrical Characteristics – TPR6040FA0, 10V Output	12
Typical Performance Characteristics – TPR6040F25	13
Tape and Reel Information	15
Package Outline Dimensions	16
SOT23-G	16

Revision History

Date	Revision	Notes
2019/12/25	Rev.Pre	Pre-Release version
2020/7/15	Rev.A	Initial version
2020/7/25	Rev.A.1	Add pin3 description in pin configuration. Add Tape and Reel Information.

Absolute Maximum Ratings ^{Note 1}

Parameters	Rating
Reverse current	20 mA
Forward current	10 mA
Maximum Junction Temperature	150°C
Operating Temperature Range	-40 to 125°C
Storage Temperature Range	-65 to 150°C
Lead Temperature (Soldering, 10 sec)	260°C

Note 1: Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD Rating

Symbol	Parameter	Condition	Minimum Level	Unit
HBM	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001	4	kV
CDM	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002	1	kV

Thermal Information

Package Type	θ_{JA}	θ_{JC}	Unit
3-Pin SOT23	250	81	°C/W

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
I_R	Cathode Reverse Current	0.15	15	mA

Electrical Characteristics – TPR6040F20, 2.048V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$				0.8	mV	
			-40 to 125°C			1	mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$					2	mV
			-40 to 125°C				3	mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			72		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			40		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F25, 2.5V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$				0.8	mV	
			-40 to 125°C			1	mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$					2	mV
			-40 to 125°C				3	mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			90		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			50		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F30, 3.0V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			108		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			60		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F33, 3.3V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			119		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			66		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F40, 4.096V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			148		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			82		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F50, 5V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			180		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			100		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040F80, 8.196V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			295		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			164		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Electrical Characteristics – TPR6040FA0, 10V Output

All test condition is at $T_A = 25^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	T_A	Min	Typ	Max	Unit	
Power Supply								
V_R	Reverse Breakdown Voltage Tolerance	$I_R = 1\text{mA}$, A Grade, "-S" suffix		-0.1		0.1	%	
		$I_R = 1\text{mA}$, B Grade		-0.2		0.2	%	
$\Delta V_R / \Delta V_T$	Average Reverse Breakdown Voltage Temperature Coefficient	$I_R = 1\text{mA}$, A Grade, "-S" suffix	-40 to 125°C	-25		25	ppm	
		$I_R = 1\text{mA}$, B Grade		-50		50	ppm	
I_{RMIN}	Minimum Operating Current				100	150	μA	
			-40 to 125°C			150	μA	
$\Delta V_R / \Delta I_R$	Reverse Breakdown Voltage Change with Operating Current Change ^{Note 1}	$I_{RMIN} \leq I_R < 1\text{mA}$					mV	
			-40 to 125°C				mV	
		$I_{RMIN} \leq I_R < 15\text{mA}$						mV
			-40 to 125°C					mV
	Wideband Noise	$I_R = 100\ \mu\text{A}$, $10\ \text{Hz} \leq f \leq 10\ \text{kHz}$			360		μV_{RMS}	
	Output voltage noise	$f = 0.1\ \text{Hz}$ to $10\ \text{Hz}$			200		μV_{pp}	
Z_R	Reverse Dynamic Impedance	$I_R = 1\text{mA}$, $f = 120\text{Hz}$			0.3	0.8	Ω	
	Long Term Stability	0 to 1000hours	25°C				ppm	
		1000 to 2000hours	25°C				ppm	
	Thermal Hysteresis						ppm	

Note 1. Output changes due to die temperature change must be taken into account separately.

Typical Performance Characteristics – TPR6040F25




Figure 1. V_{OUT} vs. Temperature, 125 μ A, 12pcs Sample




Figure 2. V_{OUT} vs. Temperature, 1mA, 12pcs Sample




Figure 3. V_{OUT} vs. Temperature, 10mA, 12pcs Sample




Figure 4. 0.1 to 10Hz Noise



Figure 5. Power Up, 100 μ s, V_{BIAS} =6.5V, R_{BIAS} =0.5K



Figure 6. Power Up, 15ms, V_{BIAS} =6.5V, R_{BIAS} =0.5K



Figure 7. Power Up, 100µs, $V_{BIAS}=6.5V$, $R_{BIAS}=2.5K$



Figure 8. Power Up, 15ms, $V_{BIAS}=6.5V$, $R_{BIAS}=2.5K$




Figure 9. Power Up, 100µs, $V_{BIAS}=6.5V$, $R_{BIAS}=20K$




Figure 10. Power Up, 15ms, $V_{BIAS}=6.5V$, $R_{BIAS}=20K$


Tape and Reel Information



D1: Reel Diameter




W1: Reel Width



Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPR6040FXX-S3TR-S	3-Pin SOT23-G	178	12.1	3.15	2.77	1.22	4.0	8.0	Q3
TPR6040FXX-S3TR	3-Pin SOT23-G	178	12.1	3.15	2.77	1.22	4.0	8.0	Q3

Package Outline Dimensions

SOT23-G



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.15Max.		0.045Max.	
A1	0.000	0.100	0.000	0.004
A2	0.900	1.100	0.035	0.043
b	0.300	0.500	0.012	0.020
c	0.132	0.202	0.005	0.008
D	2.800	3.000	0.110	0.118
E	2.250	2.550	0.089	0.100
E1	1.200	1.400	0.047	0.055
e	1.800	2.000	0.071	0.079
L	0.300	0.500	0.012	0.020
L1	0.550 REF.		0.022 REF.	
theta	0°	8°	0°	8°

 ***3PEAK and the 3PEAK logo are registered trademarks of 3PEAK INCORPORATED. All other trademarks are the property of their respective owners.***

单击下面可查看定价，库存，交付和生命周期等信息

[>>3PEAK\(思瑞浦\)](#)