

HDMI Connectors

1 2 3 4 5 6 7 8 9 10

Specification

(HJ) HDMI Jack

(HP) HDMI Plug

Number of Contacts

(19) 19 Contacts

Connector Body (Style)

> For Receptacle

> For Overmolded with Cable

(P) Front Fastened

(A) With Strain Relief

Connector (Housing) Gender

(M) Male (Plug)

(F) Female (Jack)

Contact Gender

(M) Male (Stamp)

(F) Female (Stamp)

Assemble Style

> For Receptacle

> For Overmolded with Cable

(R) 90° PCB Type

(M) Overmolded with Cable

Mating Style

(Q) Latch

Backshell

> For Receptacle

> For Overmolded with Cable

(S) Rectangle

(L) Straight

Waterproof Rating

(7) IP 67

More information

> For Receptacle

> For Overmolded with Cable

(001), (002).....

(□)+(■) : Cable Type + Cable Length

Without Cable : Different Versions

EX. (A01) = UL20276 Cable + 1M

(□) : Cable Type (■) : Cable Length

(A) UL20276 Cable From 1M to 5M

EX. (01) = 1M

Innovation in Waterproof Solution

单击下面可查看定价，库存，交付和生命周期等信息

[>>Amphenol\(安费诺\)](#)