



SIGN	DATE	DESCRIPTION	APPROVER
△	01/25'05	Part No. changed.	Marvin
△	06/26'06	Current rating(cULus) is changed from 10A to 20A	Marvin
△	06/26'06	Solid/Stranded wire(AWG) is changed from 12-22 to 12-24	Marvin
△	8/10'06	Added VDE and TUV standard	梁仁松
△	7/21'08	Body is changed.	Marvin
△	2010.03.08	Add the 2P mark	Jacke
△	2014.11.14	Update the drawing	Evan

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

**Material**

- Item ① Clamp: Brass(CuZn) Ni plated
- Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Female contact: PhBz ,Tin plated
- Item ④ Terminal Cover: Thermoplastic (UL94V-0)
- Item ⑤ Terminal housing: Thermoplastic (UL94V-0)
- △ Electrical cULus/VDE/TUV
  - Voltage rating: 300VAC/300VAC/300VAC
  - Current rating: 20A/20A/20A
  - Wire range: 2.5mm<sup>2</sup>/0.34-2.5mm<sup>2</sup>
  - △ ● Solid wire(AWG): 12-24
  - △ ● Stranded wire(AWG): 12-24
  - Torque: 5Lb-In/0.5Nm/0.56Nm
  - Screw: M3
  - Wire strip length: 7-8mm
  - Withstanding Voltage: 1.6KV/2.5KV/2.5KV
  - Operating temperature: -40°C to +115°C
  - Safety Approval: cULus VDE TUV
  - Use with 0Q1.0x1.0mm square pin, Withdrawal force:200 - 500gf /pole
  - Critical dimension: ▽

**TJ xx 51 x 3 xxxx G △**

02 2 CONTACTS	0 Black (RAL9005)	RoHS compliant (lead<4%) In copper Alloy  000 0 Standard @ Logo 000 A Standard ANY Logo 0091 Standard ANY Logo △ Any special item by customer request, please contact sales department.
03 3 CONTACTS	3 Orange(RAL2011/P)	
... ..	4 Yellow(RAL1018/A)	
24 24 CONTACTS	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	
	9 White(RAL1102)	
	C Green(RAL6018/U)	

DIMENSION

L	N×5.08
A	(N-1)×5.08
B	N×5.08+0.1

N=Number of poles

Poles	Tolerance	
	DIM A	DIM L&DIM B
2p-6p	±0.15	±0.20
7p-12p	±0.20	±0.25
13p-18p	±0.25	±0.30
19p-24p	±0.30	±0.40

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TJ-5.08mm Series 2P-24P		DWG NO.		8TJ0007	
PART NO.		TJxx51x3xxxxG		APPROVED		Tolerance	
CHECKED		DESIGNED		DRAWN		UNIT: mm	
Evan		Evan		Evan		X.X ±0.30	
2014.11.14		2014.11.14		2014.11.14		X.XX ±0.10	
SHEET: 01/01		REV: H		CUST NO.		X° ±1°	

单击下面可查看定价，库存，交付和生命周期等信息

[>>Amphenol\(安费诺\)](#)