



SIGN	DATE	DESCRIPTION	APPROVER
△	2009.6.08	Add UL standard	Jacke
△	2009.6.08	The current rating and operating temperature are changed	Jacke
△	2009.6.08	Corrected dimension △ from 2.3mm to 2.5mm	Jacke
△	2010.01.22	The demension is changed from 1.60mm to 1.10mm	Jacke
△	2010.01.22	The demension is changed from 0.40mm to 0.20~0.30mm	Jacke
△	2010.03.31	The material is changed from Brass to Copper	Jacke
△	2010.04.01	The design is changed	Jacke

**THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!**

- Material**
- △ ● Item (a) Short contact pin: Copper Tin plated
  - Item (b) Long contact pin : Copper Tin plated
  - Item (c) Terminal (housing): Thermoplastic (UL94V-0)
  - Item (d) Terminal (cover): Thermoplastic (UL94V-0)
- Electrical**
- Voltage rating: 300VAC
  - △ ● Current rating: 8A
  - Wire range:
    - Solid wire(AWG):
    - Stranded wire(AWG):
  - Withstanding Voltage: 1.6KV
  - Operating temperature: -40°C to +115°C
  - △ ● Soldering temperature: 250°C±10°C/5 Sec
  - △ ● Safety Approval: us

**VL xx 1 3 x 1 xxxx G**

- G: Pb<40000ppm
- |                  |                     |                      |
|------------------|---------------------|----------------------|
| <b>POLES</b>     | <b>COLOR</b>        | 000 0 "@ logo        |
| 04 2x2 CONTACTS  | 0 Black (RAL9005)   | 000 A "ANY" logo     |
| 06 2x3 CONTACTS  | 2 Red (RAL3001/D)   | Any special item by  |
| ...              | 3 Orange(RAL2011/P) | customer request,    |
| 48 2x24 CONTACTS | 4 Yellow(RAL1018/A) | please contact sales |
|                  | 5 Green(RAL6018/T)  | department.          |
|                  | 6 Blue (RAL5015/A)  |                      |
|                  | 8 Grey(RAL7035/D)   |                      |

Poles	04	06	08	10	12	14	16	18	20	22	24	26
Dim L	8.5	12.0	15.5	19.0	22.5	26.0	29.5	33.0	36.5	40.0	43.5	47.0
Dim B	3.50	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
TOL	±0.15						±0.20					
Poles	28	30	32	34	36	38	40	42	44	46	48	
Dim L	50.5	54.0	57.5	61.0	64.5	68.0	71.5	75.0	78.5	82.0	85.5	
Dim B	45.5	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	
TOL	±0.25						±0.30					

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		VL-3.5mm Right -Angle Series "B Type"					
PART NO.		VLxx13x1xxxxG			DWG NO.		8VL0402
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
		Jacke	Jacke				X. ±0.50
		2010.03.31	2010.01.22				X.X ±0.30
							X.XX ±0.10
							X° ±1°
						UNIT: mm	
						SCALE: NONE	
						SHEET: 01/01	
						REV.: D	

单击下面可查看定价，库存，交付和生命周期等信息

[>>Amphenol\(安费诺\)](#)