



SIGN	DATE	DESCRIPTION	APPROVER
△	12/14'11	Add is cULus Mark	ChenMing
△	12/14'11	Torque(Lb-In) is changed from 2.0(Lb-In) to 2.6(Lb-In)	ChenMing
△	12/14'11	The dimension are added	ChenMing

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Terminal (Body):Thermoplastic (UL94V-0)
- Item (b) Terminal (Cover):Thermoplastic (UL94V-0)
- Item (c) Terminal screw:Steel Zinc plating "-" slot type
- Item (d) Clamp:Brass(CuZn) Ni plating
- Item (e) Contact Pin: Brass, Tin plated
- Item (f) Flange nut: Brass

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 8A
- Solid wire(AWG): 14-30
- Stranded wire(AWG): 14-30
- △ Torque(Lb-In): 2.6
- Screw: M2
- Wire strip length: 7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- △ Safety Approval:
- Critical dimension: ▽

V8 xx 31 x 1 xxxx G

No. OF POLES

- 02 2 CONTACTS
- 03 3 CONTACTS
-
- 24 24 CONTACTS

Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

RoHS compliant
(lead<4%)
In copper Alloy

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request.
please contact sales department.

Dimension

N=Number of poles

Dim A	N×3.81
Dim B	N×3.81+0.88
Dim C	(N-1)×3.81
Dim D	(N-1)×3.81+9.0
Dim E	N×3.81+10.40

POLES	Tolerance
2p-6p	±0.15
7p-13p	±0.20
14p-18p	±0.30
19p-24p	±0.40

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		V8 -3.81 Series 2P-24P (With flange & Nut type)	
PART NO.	V8xx31x1xxxxG	DWG NO.	8V80102
APPROVED	CHECKED	DESIGNED	DRAWN
		Aaron 2011.12.20	ChenMing 2011.12.14
SHEET: 01/01		Tolerance	
UNIT: mm		X. ±0.5	
SCALE: NONE		X.X ±0.3	
REV.: C		X.XX ±0.1	
		X° ±1°	

单击下面可查看定价，库存，交付和生命周期等信息

[>>Amphenol\(安费诺\)](#)