

## General Description

The AOZ8211 is a one-line transient voltage suppressor diode designed to protect voltage sensitive electronics from high transient conditions and ESD.

This device incorporates one TVS diode in an ultra-small SOD923 package. During transient conditions, the one-line TVS diode directs the transient to ground. It may be used to meet the ESD immunity requirements of IEC 61000-4-2, Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge).

The AOZ8211 comes in an RoHS compliant SOD923 package and is rated over a  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  ambient temperature range.

The ultra-small  $1.0 \times 0.6 \times 0.4\text{mm}$  SOD923 package makes it ideal for applications where PCB space is a premium. The small size and high ESD protection makes it ideal for protecting voltage sensitive electronics from high transient conditions and ESD.

## Features


- ESD protection for high-speed data lines:
  - Exceeds: IEC 61000-4-2 (ESD)  $\pm 28\text{kV}$  (air),  $\pm 28\text{kV}$  (contact)
  - Human Body Model (HBM)  $\pm 30\text{kV}$
- Small package saves board space
- Low insertion loss
- Low clamping voltage
- Low operating voltage: 5V and 12V

## Applications

- Portable handheld devices
- Keypads, data lines, buttons
- Notebook computers
- Digital Cameras
- Portable GPS
- MP3 players




## Typical Application



Unidirection Protection of Single Line

## Pin Configuration



## Ordering Information

Part Number	Ambient Temperature Range	Package	Environmental
AOZ8211NI-05L	-40°C to +85°C	SOD923	RoHS Compliant Green Product
AOZ8211NI-12L			



All AOS products are offered in packages with Pb-free plating and compliant to RoHS standards. Parts marked as Green Products (with "L" suffix) use reduced levels of Halogens, and are also RoHS compliant. Please visit [www.aosmd.com/web/quality/rohs\\_compliant.jsp](http://www.aosmd.com/web/quality/rohs_compliant.jsp) for additional information.

## Absolute Maximum Ratings

Exceeding the Absolute Maximum ratings may damage the device.

Parameter	Rating
Peak Pulse Current ( $I_{PP}$ ), $t_P = 8/20\mu s$	5A
Storage Temperature ( $T_S$ )	-65°C to +150°C
ESD Rating per IEC61000-4-2, Contact <sup>(1)</sup>	±28kV
ESD Rating per IEC61000-4-2, Air <sup>(1)</sup>	±28kV
ESD Rating per Human Body Model <sup>(2)</sup>	±30kV

### Notes:

- IEC 61000-4-2 discharge with  $C_{Discharge} = 150pF$ ,  $R_{Discharge} = 330\Omega$ .
- Human Body Discharge per MIL-STD-883, Method 3015  $C_{Discharge} = 100pF$ ,  $R_{Discharge} = 1.5k\Omega$ .

## Maximum Operating Ratings

Parameter	Rating
Junction Temperature ( $T_J$ )	-40°C to +85°C

## Electrical Characteristics

$T_A = 25^\circ C$  unless otherwise specified.

Symbol	Parameter	Symbol	Parameter
$I_{PP}$	Maximum Reverse Peak Pulse Current	$I_T$	Test Current
$V_{CL}$	Clamping Voltage @ $I_{PP}$	$I_F$	Forward Current
$V_{RWM}$	Working Peak Reverse Voltage	$V_F$	Forward Voltage @ $I_F$
$I_R$	Maximum Reverse Leakage Current @ $V_{RWM}$	$P_{pk}$	Peak Power Dissipation
$V_{BR}$	Breakdown Voltage @ $I_T$	$C_J$	Max. Capacitance @ $V_R = 0$ and $f = 1MHz$


## Electrical Characteristics

$T_A = 25^\circ C$  unless otherwise noted,  $V_F = 0.9V$  Max. @  $I_F = 10mA$  for all types


Device	Device Marking	$V_{RWM}$ (V) Max.	$V_{BR}$ (V) Max.	$I_R$ ( $\mu A$ ) Max.	$V_F$ (V) Typ.	$V_{CL}$ Max.			$C_J$ (pF) Typ.
						$I_{PP} = 1A$	$I_{PP} = 5A$	$I_{PP} = 12A$	
AOZ8211NI-05L	C	5.0	6.0	0.1	0.75	8.00	9.00	10.00	16
AOZ8211NI-12L	D	12.0	15.0	0.1	0.75	18.00	20.00	21.00	30

## Typical Performance Characteristics


**Clamping Voltage vs. Peak Pulse Current**  
(tperiod = 100ns, tr = 1ns)




**Forward Voltage vs. Forward Current**  
(tperiod = 100ns, tr = 1ns)




**I/O – Gnd Insertion Loss (S21) vs. Frequency**  
(V<sub>p</sub> = 3.3V)




**Capacitance vs. Reverse Bias**




**Analog Crosstalk (I/O–I/O) vs. Frequency**




Package Dimensions, SOD923




TOP VIEW



BOTTOM VIEW




SIDE VIEW



VIEW 'C'

RECOMMENDED LAND PATTERN



Dimensions in millimeters

Symbols	Min.	Nom.	Max.
A	—	—	0.41
A1	0.00	—	0.05
b	0.15	0.20	0.25
c	0.07	0.12	0.14
D	0.55	0.60	0.65
E	0.75	0.80	0.85
E1	0.95	1.00	1.05
L	0.15	0.20	0.25
aaa	0.08		

Dimensions in inches


Symbols	Min.	Nom.	Max.
A	—	—	0.016
A1	0.00	—	0.002
b	0.006	0.008	0.010
c	0.003	0.005	0.006
D	0.022	0.024	0.026
E	0.030	0.031	0.033
E1	0.037	0.039	0.041
L	0.006	0.008	0.010
aaa	0.003		

Notes:

1. All dimensions are in millimeters.
2. Dimensions are inclusive of plating.
3. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.
4. The cathode mark is optional.
5. Package body sizes exclude mold flash and gate burrs. Mold flash at the non-lead sides should be less than 3 mils each.

## Tape and Reel Dimensions, SOD923


### Tape



UNIT: mm

Package	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOD923	0.70 ±0.05	1.12 ±0.05	0.48 ±0.05	∅1.50 ±0.1	∅0.5 ±0.05	8.0 ±0.2	1.75 ±0.1	3.5 ±0.05	2.0 ±0.05	4.0 ±0.1	2.0 ±0.05	0.229 ±0.02


### Reel




UNIT: mm

Tape Size	Reel Size	M	N	W	W1	H	H1	K	K1	S	S1	E
8mm	∅180	∅177.7 ±0.5	∅54.4 ±0.5	8.8 ±0.5	1.15 +0.2/-0.0	∅13.2 ±0.3	∅15.8	10.4	11.7	2.3 ±0.1	4.9 ±0.1	2.8 ±0.1

### Leader/Trailer and Orientation



## Part Marking



**This data sheet contains preliminary data; supplementary data may be published at a later date. Alpha & Omega Semiconductor reserves the right to make changes at any time without notice.**

### LIFE SUPPORT POLICY

ALPHA & OMEGA SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

单击下面可查看定价，库存，交付和生命周期等信息

[>>AOS\(万代\)](#)