

1 2 3 4 5 6 7

A B C D E F G H

A B C D E F G H

NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 100 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN. @ 500 VDC.
5. DIELECTRIC STRENGTH : 750 VAC 60Hz, 1MIN.
6. CATEGORY 5e CHARACTERISTIC:

Frequency	Near-End Cross Talk dB, MIN.	Return Loss dB, MIN.	Attenuation dB, MAX.
1.0 MHZ	65.0	35.5	0.1
4.0 MHZ	65.0	35.5	0.1
8.0 MHZ	64.9	35.5	0.1
10.0 MHZ	63.0	35.5	0.1
16.0 MHZ	58.9	35.5	0.2
20.0 MHZ	57.0	34.0	0.2
25.0 MHZ	55.0	32.0	0.2
31.25 MHZ	53.1	30.1	0.2
62.5 MHZ	47.1	24.0	0.3
100.0 MHZ	43.0	20.0	0.4

MECHANICAL:

1. HOUSING MATERIAL : PC UL94V-0
2. INSERT MATERIAL : GLASS FILLED POLYESTER UL94V-0 BK.
3. PCB MATERIAL : FR-4 THICKNESS 1.6mm
4. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN t=0.35mm

ENVIRONMENTAL:

1. STORAGE: -40°C TO +85°C.
2. OPERATION: 0°C TO 70°C.

CONFORMING TO TIA/EIA 568B  
MATES WITH MODULAR PLUG CONFORMING TO  
FCC PART 68, SUBPART F.

LOGO ABOVE THE  
SURFACE 0.20mm

**RoHS compliant**

Scale	Free					Date	Name	Customer-No.
TOLERANCE					Drawn	02.07.2013	Winnie	
.X	±0.20				Approved	02.07.2013	Winnie	ASSMANN WSW-No. <b>A-TA3534</b>
.XX	±0.15							Drawing-No.
.XXX	±0.10							<b>ASS 5822 CO</b> rev00
DIM	TOL							Sheet
Angle	±5°							
Angle	TOL	Id.	Modification	Date	Name			

1 2 3 4 5 6 7

Downloaded From [Oneyac.com](http://Oneyac.com)

CON0131

单击下面可查看定价，库存，交付和生命周期等信息

[>>ASSMANN WSW](#)