


RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

700B Series NPO Porcelain and Ceramic Multilayer Capacitors



FEATURES

- Case B Size (.110" x .110")
- Capacitance Range 0.1 pF to 5100 pF
- Extended WVDC up to 1500 VDC
- Low ESR/ESL
- High Q
- Low Noise
- Ultra-Stable Performance
- High Self-Resonance
- Established Reliability (QPL)

GENERAL DESCRIPTION

KYOCERA AVX, the industry leader, is announcing new improved ESR/ESL performance for the 700B Series RF/Microwave Capacitors. The superior high self-resonance and zero TCC characteristic of this Series provide excellent performance over a broad range of RF and microwave applications requiring minimum drift, including RF power. Porcelain and ceramic construction provide a rugged, hermetic package.

FUNCTIONAL APPLICATIONS

- Bypass
- Impedance Matching
- Coupling
- DC Blocking
- Tuning

CIRCUIT APPLICATIONS

- Timing Power Amplifiers
- RF Power Amplifiers
- Filters
- Oscillators

ENVIRONMENTAL CHARACTERISTICS

Thermal Shock	Mil-STD-202, Method 107, Condition A
Moisture Resistance	Mil-STD-202, Method 106
Low Voltage Humidity	Mil-STD-202, Method 103, condition A, with 1.5 VDC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours
Life Test	MIL-STD-202, Method 108, for 2000 hours, at 125°C. Voltage applied. 200% of WVDC for capacitors rated at 500 volts DC or less. 120% of WVDC for capacitors rated at 1250 volts DC or less. 100% of WVDC for capacitors rated above 1250 volts DC
Termination Styles	Available in various surface mount and leaded styles. See Mechanical Configurations
Terminal Strength	Terminations for chips and pellets withstand a pull of 5 lbs. min., 15 lbs. typical, for 5 seconds in direction perpendicular to the termination surface of the capacitor.

AVX 700B Series Capacitors are designed and manufactured to meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123.

PACKAGING OPTIONS



Tape & Reel



Vertical Orientation Tape & Reel



Cap Pac® (100 pcs)



ELECTRICAL SPECIFICATIONS

Temperature Coefficient (TCC)	0 ±30 PPM/°C (-55°C to +125°C)
Capacitance Range	0.1 pF to 5100 pF
Operating Temperature	0.1 to 200 pF: from -55°C to +175°C 220 to 5100 pF: from -55°C to +125°C
Quality Factor	Greater than 10,000 (1 pF to 200 pF) @ 1 MHz. Greater than 2000 (220 pF to 1000 pF) @ 1 MHz. Greater than 2000 (1100 pF to 5100 pF) @ 1 KHz.
Insulation Resistance (IR)	0.1 pF to 470 pF: 10 ⁶ Megohms min. @ +25°C at rated WVDC. 10 ⁵ Megohms min. @ +125°C at rated WVDC. 510 pF to 5100 pF: 10 ⁵ Megohms min. @ +25°C at rated WVDC. 10 ⁴ Megohms min. @ +125°C at rated WVDC.
Working Voltage (WVDC)	See Capacitance Values table
Dielectric Withstanding Voltage (DWV)	250% of WVDC for capacitors rated at 500 volts DC or less for 5 seconds. 150% of WVDC for capacitors rated at 1250 volts DC or less for 5 seconds. 120% of WVDC for capacitors rated above 1250 Volts DC for 5 seconds
Aging Effects	None
Piezoelectric Effects	None
Capacitance Drift	± (0.02% or 0.02 pF), whichever is greater
Retrace	Less than ±(0.02% or 0.02 pF), whichever is greater.

RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

700B Series NPO Porcelain and Ceramic Multilayer Capacitors




CAPACITANCE VALUES

Cap. Code	Cap. (pF)	Tol.	Rated WVDC		Cap. Code	Cap. (pF)	Tol.	Rated WVDC		Cap. Code	Cap. (pF)	Tol.	Rated WVDC		CAP. CODE	CAP. (pF)	TOL.	RATED WVDC							
			STD.	EXT.				STD.	EXT.				STD.	EXT.				STD.	EXT.						
0R1	0.1	B	500	1500	3R3	3.3	B, C, D	500	1500	330	33	F, G, J, K, M	500	VOLT	331	330	F, G, J, K, M	200							
0R2	0.2				3R6	3.6				360	36				361	360									
0R3	0.3	B, C			EXTENDED VOLTAGE	3R9				3.9	1500				EXTENDED VOLTAGE	390				39	1000	EXTENDED VOLTAGE	391	390	
0R4	0.4					4R3				4.3						430				43			431	430	
0R5	0.5	B, C, D			EXTENDED VOLTAGE	4R7				4.7	500				EXTENDED VOLTAGE	470				47	300	EXTENDED VOLTAGE	471	470	
0R6	0.6					5R1				5.1						510				51			511	510	
0R7	0.7					5R6				5.6						560				56			561	560	
0R8	0.8					6R2				6.2						620				62			621	620	
0R9	0.9					B, C, J, K, M				6R8						6.8				680			68	681	680
1R0	1.0									7R5						7.5				750			75	751	750
1R1	1.1		B, C, D	EXTENDED VOLTAGE		8R2	8.2	500	EXTENDED VOLTAGE	820		82	1000	EXTENDED VOLTAGE		821	820								
1R2	1.2					9R1	9.1			910		91				911	910								
1R3	1.3					100	10			101		100				102	1000								
1R4	1.4					110	11			111		110				112	1100								
1R5	1.5	120			12	121	120			122	1200														
1R6	1.6	F, G, J, K, M			130	13	131			130	152	1500													
1R7	1.7				150	15	151			150	182	1800													
1R8	1.8				160	16	161			160	222	2200													
1R9	1.9				180	18	181			180	272	2700													
2R0	2.0				200	20	201			200	302	3000													
2R1	2.1		220	22	221	220	332	3300																	
2R2	2.2		240	24	241	240	392	3900																	
2R4	2.4		270	27	271	270	472	4700																	
2R7	2.7		300	30	301	300	512	5100																	
3R0	3.0																								

SPECIAL VALUES, TOLERANCES, DIFFERENT WVDC AND MATCHING AVAILABLE. • ENCAPSULATION OPTION AVAILABLE. PLEASE CONSULT FACTORY.
Capacitance values in bold type indicate porcelain dielectric. All other capacitance values indicate ceramic dielectric.

HOW TO ORDER



The above part number refers to a 700B Series (case size B) 330 pF capacitor, J tolerance (±5%), 500 WVDC, with W termination (Tin/Lead, Solder Plated over Nickel Barrier), laser marking and Tape and Reel packaging.

RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

700B Series NPO Porcelain and Ceramic Multilayer Capacitors



MECHANICAL CONFIGURATION

Series & Case Size	Term. Code	MIL-PRF-55681	Case Size & Type	Outline W/T is a Termination Surface	Body Dimensions inches (mm)			Lead and Termination Dimensions and Material			Pkg Type	Pkg Code	
					Length (L)	Width (W)	Thickness (T)	Overlap (Y)	Materials				
700B	W	CDR14BP	B Solder Plate		110+.025-.010 (2.79+0.64-0.25)	.110±.015 (2.79±0.38)	.102 (2.59) max.	.015 (0.38) ±.010 (0.25)	Tin/Lead, Solder Plated over Nickel Barrier Termination		T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100	
700B	P	CDR14BP	B Pellet		110+.025-.010 (2.79+0.64-0.25)	.110±.015 (2.79±0.38)	.102 (2.59)		Heavy Tin/Lead Coated, over Nickel Barrier Termination		T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100	
700B	T	N/A	B Solderable Nickel Barrier		110+.025-.010 (2.79+0.64-0.25)	.110±.015 (2.79±0.38)	.102 (2.59)		RoHS Compliant Tin Plated over Nickel Barrier Termination		T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100	
700B	CA	CDR13BP	B Gold Chip		110+.025-.010 (2.79+0.64-0.25)	.110±.015 (2.79±0.38)	.102 (2.59)		RoHS Compliant Gold Plated over Nickel Barrier Termination		T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100	
700B	MS	CDR21BP	B Microstrip		.135±.015 (3.43±0.38)	.110±.015 (2.79±0.38)	.120 (3.05) max.	N/A	Length (L _L)	Width (W _L)	Thickness (T _L)	Cap Pac, 20 pcs	C20
700B	AR	CDR22BP	B Axial Ribbon						.250 (6.35) min.	.093±.005 (2.36±0.13)	.004±.001 (.102±.025)	Box, 20 or 100 pcs	B20 or B100
700B	RR	CDR24BP	B Radial Ribbon		.145±.020 (3.68±0.51)	.102 (2.59) max.	.500 (12.7)		#26 AWG., .016 (.406) dia.nominal		Box, 20 or 100 pcs	B20 or B100	
700B	RW	CDR23BP	B Radial Wire				.950 min.				Box, 20 or 100 pcs	B20 or B100	
700B	AW	CDR25BP	B Axial Wire								Box, 20 or 100 pcs	B20 or B100	

Additional lead styles available: Narrow Microstrip (NM), Narrow Axial Ribbon (NA) and Vertical Narrow Microstrip (H). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and are RoHS compliant.

RF/Microwave Capacitors

RF/Microwave Multilayer Capacitors (MLC)

700B Series NPO Porcelain and Ceramic Multilayer Capacitors



MECHANICAL CONFIGURATION

Series & Case Size	Term. Code	MIL-PRF-55681	Case Size & Type	Outline W/T is a Termination Surface	Body Dimensions inches (mm)			Lead and Termination Dimensions and Material			Pkg Type	Pkg Code						
					Length (L)	Width (W)	Thickness (T)	Overlap (Y)	Materials									
700B	WN	Meets Requirements	B Non-Mag Solder Plate		.110 +.020 -.010 (2.79 +0.51 -0.25)	.110 ±.015 (2.79 ±0.38)	.102 (2.59) max.	.015 (0.38) ±.010 (0.25)	Tin / Lead, Solder Plated over Non-Magnetic Barrier Termination			T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100					
700B	PN	Meets Requirements	B Non-Mag Pellet		.110 +.035 -.010 (2.79 +0.89 -0.25)	.110 ±.015 (2.79 ±0.38)			Heavy Tin / Lead, Coated over Non-Magnetic Barrier Termination			T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100					
700B	TN	Meets Requirements	B Non-Mag Solderable Barrier		.110 +.020 -.010 (2.79 +0.51 -0.25)	.110 ±.015 (2.79 ±0.38)			RoHS Compliant Tin Plated over Non-Magnetic Barrier Termination			T&R, 1000 or 500 pcs Vertical T&R, 1000 or 500 pcs Cap Pac, 100 pcs	T1K or T TV1K or TV C100					
700B	MN	Meets Requirements	B Non-Mag Microstrip		.135 ±.015 (3.43 ±0.38)	.110 ±.015 (2.79 ±0.38)	.120 (3.05) max.	N/A	Length (L)	Width (W.)	Thickness (T.)	Cap Pac, 20 pcs	C20					
700B	AN	Meets Requirements	B Non-Mag Axial Ribbon						.250 (6.35) (6.35) min.	.093 ± .005 (2.36 ± 0.13)	.004 ± .001 (.102 ± .025)			Box, 20 or 100 pcs	B20 or B100			
700B	FN	Meets Requirements	B Non-Mag Radial Ribbon						.145 ±.020 (3.68 ±0.51)	.102 (2.59) max.	N/A			.500 (12.7) min.	#26 AWG., .016 (.406) dia. nominal	Box, 20 or 100 pcs	B20 or B100	
700B	RN	Meets Requirements	B Non-Mag Axial Wire													.950 min.	Box, 20 or 100 pcs	B20 or B100
700B	BN	Meets Requirements	B Non-Mag Radial Wire															

*Capacitors with values greater than 200 pF contain a trace magnetic element that may exhibit weak magnetic properties.

** Additional lead styles available: Narrow Microstrip (DN), Narrow Axial Ribbon (GN) and Vertical Narrow Microstrip (HN). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and RoHS compliant.

SUGGESTED MOUNTING PAD DIMENSIONS

Horizontal
Electrode Orientation


Vertical
Electrode Orientation

Case B Vertical Mount					
Cap Value	Pad Size	A Min.	B Min.	C Min.	D Min.
0.1 pF	Normal	.065	.050	.075	.175
	High Density	.045	.030	.075	.135
0.2 pF	Normal	.090	.050	.075	.175
	High Density	.070	.030	.075	.135
0.3 to 510 pF	Normal	.110	.050	.075	.175
	High Density	.090	.030	.075	.135
> 510 pF	Normal	.120	.050	.075	.175
	High Density	.100	.030	.075	.135


Horizontal Mount					
All Values	Pad Size	A Min.	B Min.	C Min.	D Min.
All Values	Normal	.130	.050	.075	.175
	High Density	.110	.030	.075	.135

PERFORMANCE DATA


**ESR VS. CAPACITANCE
SERIES 700, CASE B**




**Q VS. CAPACITANCE
SERIES 700, CASE B**



**ESR VS. CAPACITANCE
SERIES 700, CASE B**




**Q VS. CAPACITANCE
SERIES 700, CASE B**




PERFORMANCE DATA


ESR VS. CAPACITANCE
SERIES 700, CASE B




Q VS. CAPACITANCE
SERIES 700, CASE B




SERIES RESONANCE VS. CAPACITANCE
SERIES 700, CASE B




CURRENT RATING VS. CAPACITANCE
SERIES 700, CASE B



CURRENT RATING VS. CAPACITANCE
SERIES 700, CASE B




CURRENT RATING VS. CAPACITANCE
SERIES 700, CASE B




PERFORMANCE DATA


CURRENT CHANGE VS. TEMPERATURE
SERIES 700, CASE B



CURRENT RATING VS. CAPACITANCE
SERIES 700, CASE B, EXTENDED VOLTAGE



CURRENT RATING VS. CAPACITANCE
SERIES 700, CASE B, EXTENDED VOLTAGE



RF/Microwave Capacitors
RF/Microwave Multilayer Capacitors (MLC)
700B Series NPO Porcelain and Ceramic Multilayer Capacitors



SAMPLE KITS

Kit #	RoHS Compliant	Item Number	Description	Cap. Value Range (pF)	Cap Value (pF)	Tol.	Price
Kit 11	-	DK0011	700B Porcelain and Ceramic 16 different values, 15 pcs. min. per value	1.0 to 10	1.0, 1.2, 1.5, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3.....	±0.1	\$165.00
Kit 11T		DK0011T			3.9, 4.7, 5.6, 6.8, 8.2 3.9, 4.7, 5.6, 6.8, 8.2	±0.25	
Kit 12	-	DK0012	700B Porcelain and Ceramic 16 different values, 15 pcs. min. per value	10 to 100	10, 12, 15, 18, 20, 22, 24, 27, 30, 33, 39, 47, 56, 68, 82, 100	±5%	\$165.00
Kit 12T		DK0012T					
Kit 13	-	DK0013	700B Porcelain and Ceramic 16 different values, 15 pcs. min. per value	100 to 1000	100, 120, 150, 180, 200, 220, 240, 270, 300, 330, 390, 470	± 5%	\$165.00
Kit 13T		DK0013T			560, 680, 820, 1000.....	±10%	

单击下面可查看定价，库存，交付和生命周期等信息

[>>AVX](#)