
MLCC Low Profile




General Specifications



GENERAL DESCRIPTION


AVX introduces the LT series comprising a range of low profile products in our X5R and X7R dielectric. X5R is a Class II dielectric with temperature varation of capacitance within ±15% from -55°C to +85°C. Offerings include 0201, 0402, 0603, 0805 1206, and 1210 packages in compact, low profile designs. The LT series is ideal for decoupling and filtering applications where height clearance is limited. AVX is also expanding the low profile products in our X7R dielectric. X7R is a Class II dielectric with temperature variation of capacitance within ±15% from -55°C to +125°C. Please contact the factory for availability of any additional values not listed.

PART NUMBER (see page 2 for complete part number explanation)



NOTE: Contact factory for availability of tolerance options for specific part numbers.

SIZE			LT01	LT02				LT03				LT05				LT06			LT10	
	WVDC		4	4	6.3	10	16	4	6.3	16	25	6.3	10	16	25	10	16	25	16	25
Cap	104	0.10	Z		Q		S													
(µF)		0.22									Х									
		0.47									Х							Х		
	105	1.0		С		S				S	Х			Х	Х					
		1.5																		
		2.2		S					S	Х				Х						
		4.7						S	Х				S	Х			W	W	W	
	106	10						X/W				Х	Х				W		W	
		22																		
		47																		
	WVDC		4	4	6.3	10	16	4	6.3	16	25	6.3	10	16	25	10	16	25	16	25
	SIZE		LT01	LT02				LT03				LT05				LT06			LT10	





单击下面可查看定价,库存,交付和生命周期等信息

>>AVX