

Bridgelux® Vesta™ Tunable Linear Gen 3 2 SMD Rows

Product Data Sheet DS138

Lengths: 280mm, 560mm, 1120mm


CRIs: 80, 90

CCT Ranges: 2700-5000K, 2700-6500K




Product Feature Map

Bridgelux Vesta Series Tunable White Linear (TL) modules are fully engineered devices that provide consistent thermal and optical performance on an engineered mechanical platform. The linear products incorporate several features to simplify design integration and assembly. Please visit www.bridgelux.com for more information on the Vesta Series family of products.



Product Nomenclature

The part number designation for Bridgelux Vesta Series TL Gen 3 with 2 SMD rows is explained as follows:



Product Selection Guide

Table 1: Product Performance ($T_c = 25^\circ\text{C}$)

Part Number	Nominal CCT ¹ (K)	Minimum CRI	Typical Flux ^{2,3} (lm)	Nominal Drive Current (mA)	Typical V_f (V)	Typical Power (W)	Typical Efficacy (lm/W)			
BXEB-TL-L0280Z-2750E1000-A-C3	2700	80	1663	500	19.4	9.7	171			
	5000		1836				189			
BXEB-TL-L0280Z-2765E1000-A-C3	2700		1663				171			
	6500		1826				188			
BXEB-TL-L0280Z-2750G1000-A-C3	2700	90	1418				1000	19.4	19.4	146
	5000		1556							160
BXEB-TL-L0280Z-2765G1000-A-C3	2700		1418							146
	6500		1556							160
BXEB-TL-L0560Z-2750E2000-A-C3	2700	80	3325	1000	19.4	19.4				171
	5000		3672							189
BXEB-TL-L0560Z-2765E2000-A-C3	2700		3325							171
	6500		3652							188
BXEB-TL-L0560Z-2750G2000-A-C3	2700	90	2836				1000	19.4	19.4	146
	5000		3111							160
BXEB-TL-L0560Z-2765G2000-A-C3	2700		2836							146
	6500		3111							160
BXEB-TL-L1120Z-2750E4000-A-C3	2700	80	6650	1000	38.8	38.8				171
	5000		7344							189
BXEB-TL-L1120Z-2765E4000-A-C3	2700		6650							171
	6500		7303							188
BXEB-TL-L1120Z-2750G4000-A-C3	2700	90	5671				1000	38.8	38.8	146
	5000		6222							160
BXEB-TL-L1120Z-2765G4000-A-C3	2700		5671							146
	6500		6222							160

Notes for Table 1:

1. Nominal CCT as defined by ANSI C78.377-2011.
2. Data is at nominal test current where temperature of center case temperature point $T_c = 25^\circ\text{C}$.
3. Bridgelux maintains a $\pm 7\%$ tolerance on typical flux data (typical SMD flux bins)

Electrical Characteristics

Table 2: Electrical Characteristics

Part Number	Drive Current (mA)	Forward Voltage $T_{c2} = 25^{\circ}\text{C}$ (V) ^{1, 2, 3}			Typical Coefficient of Forward Voltage ⁴ $\Delta V_f / \Delta T$ (mV/ $^{\circ}\text{C}$)	Driver Selection Voltages ⁵ (V)	
		Minimum	Typical	Maximum		V_f Min, Hot $T_{c2} = 85^{\circ}\text{C}$ (V)	V_f Max, Cold $T_{c2} = -40^{\circ}\text{C}$ (V)
BXEB-TL-L0280Z-27xxE1000-A-C3	500	18.0	19.4	20.8	-5.7	17.7	21.1
	1000	19.5	21.0	22.5		19.2	22.8
BXEB-TL-L0280Z-27xxG1000-A-C3	500	18.0	19.4	20.8	-5.7	17.7	21.1
	1000	19.5	21.0	22.5		19.2	22.8
BXEB-TL-L0560Z-27xxE2000-A-C3	1000	18.0	19.4	20.8	-5.7	17.7	21.1
	2000	19.5	21.0	22.5		19.2	22.8
BXEB-TL-L0560Z-27xxG2000-A-C3	1000	18.0	19.4	20.8	-5.7	17.7	21.1
	2000	19.5	21.0	22.5		19.2	22.8
BXEB-TL-L1120Z-27xxE4000-A-C3	1000	36.1	38.8	41.5	-11.4	35.4	42.3
	2000	39.1	42.0	44.9		38.4	45.7
BXEB-TL-L1120Z-27xxG4000-A-C3	1000	36.1	38.8	41.5	-11.4	35.4	42.3
	2000	39.1	42.0	44.9		38.4	45.7

Notes for Table 2:

1. Voltage minimum and maximum are provided for reference only and are not a guarantee of performance.
2. Bridgelux maintains a tolerance of ± 0.1 V on forward voltage data.
3. This product has been designed and manufactured per IEC 62031:2014. The working voltage designated for the insulation is 60 Vdc. The maximum allowable voltage across the module must be determined in the end product application.
4. Typical coefficient of forward voltage tolerance is ± 0.1 mV for nominal current.
5. V_f min hot and max cold values are provided as reference only and are not guaranteed. These values are provided to aid in driver design and selection over the operating range of the product.

Absolute Maximum Ratings

Table 3: Maximum Ratings

Parameter	Maximum Rating		
Storage Temperature	-40°C to +85°C		
Operating Case Temperature ² (T _c)	85°C		
Soldering Temperature	350°C or lower for a maximum of 5 seconds		
Maximum Reverse Voltage	Modules are not designed to be driven in reverse bias		
	BXEB-TL-L0280Z-27xy1000-A-C3	BXEB-TL-L0560Z-27xy2000-A-C3	BXEB-TL-L1120Z-27xy4000-A-C3
Drive Current, Maximum Combined ³	1000 mA	2000 mA	2000 mA
Drive Current, Maximum Per Channel ³	1000 mA	2000 mA	2000 mA

Notes for Table 3

- For IEC 62717 requirement, please consult your Bridgelux sales representative.
- Lumen maintenance (L70) and lifetime predictions are valid for drive current and case temperature conditions used for LM-80 testing as included in the applicable LM-80 test report for the SMDs used in the modules. Contact your Bridgelux sales representatives for LM-80 report.
- The Maximum Combined Drive Current is defined as the sum of the drive currents in both channels.
 - Example #1: If 1000mA is applied to the 2700K (warm white) channel of the BXEB-TL-L0280Z-27xy1000-A-C3 module, then 0mA may be applied to the alternate cool white channel.
 - Example #2: If 1500mA is applied to the cool white channel of the BXEB-TL-L0560Z-27xy2000-A-C3 module, then a maximum of 500mA may be applied to the warm white channel.

Performance Curves

Figure 1: Current vs. Forward Voltage (280mm only)




Figure 2: Flux vs. Current (280mm only)




Figure 3: Current vs. Forward Voltage (560mm only)




Figure 4: Flux vs. Current (560mm only)




Figure 5: Current vs. Forward Voltage (1120mm only)





Figure 6: Flux vs. Current (1120mm only)



Notes for Figures 1-6:

1. All measurements were performed at $T_c=25^\circ\text{C}$

Performance Curves

Figure 7: Flux vs. Current Ratio (2700K-5000K)




Figure 8: CCT vs. Current Ratio (2700K-5000K)




Figure 9: Flux vs. Current Ratio (2700K-6500K)





Figure 10: CCT vs. Current Ratio (2700K-6500K)



Notes for Figures 7-10:

1. All measurements were performed at $T_c = 25^\circ\text{C}$
2. Current Ratio is calculated by dividing the channel with the lower drive current by the channel with the higher drive current. For example if the CW channel is operated at 1500mA and the WW channel is operated at 300mA, then the W/W current ratio = $300/1500 = 0.2$

Performance Curves

Figure 11: Voltage vs Case Temperature




Figure 12: Flux vs Case Temperature (2700K-5000K)






Figure 13: Flux vs Case Temperature (2700K-6500K)



Typical Radiation Pattern

Figure 14: Typical Spatial Radiation Pattern



Notes for Figure 14:

1. Typical viewing angle is 120°.FWHM
2. The viewing angle is defined as the full-width off-axis angle where the intensity is 50% of the peak value.

Typical Color Spectrum

Figure 15: Typical Color Spectra, 80 CRI





Figure 16: Typical Color Spectra, 90 CRI



Note for Figures 15 & 16:

1. Color spectra measured at nominal current for $T_c = 65^\circ\text{C}$

Mechanical Dimensions

Figure 17: Drawing Overview for 280mm




Figure 18: Drawing Overview for 560mm





Figure 19: Drawing Overview for 1120mm



Notes for Figures 17, 18 & 19:

1. Solder pads are labeled "+" to denote positive polarity, and "-" to denote negative polarity.
2. "WW" labels stand for Warm White and refer to the low CCT SMDs on the module (i.e. 2700K). "CW" labels stand for Cool White and refer to the high CCT SMDs on the module (i.e. 5000K or 6500K).
3. Dimensions are in millimeters.
4. Refer to Bridgelux assembly drawing 15-000715, 15-000716, and 15-000717 for complete product configuration.

Table 5: Module Dimensions & Connector Wiring

Parameter	BXEB-TL-L0280Z-27xyy1000-A-C3	BXEB-TL-L0560Z-27xyy2000-A-C3	BXEB-TL-L1120Z-27xyy4000-A-C3
Linear length	280.0 mm	560.0 mm	1120.0 mm
Linear width	31 mm		
Overall thickness	5.6 mm		
PCB thickness	1.6 mm		
Input wire cross-section	18-24 AWG		
Wire strip length	7-9 mm		

Color Binning Information

Figure 20: 3 SDCM Color Bins in CIE 1931 xy Color Space




Table 6: Bin Coordinates and Associated Typical CCT

CCT	Color Consistency	CIE Center Point (x, y)	Corresponding CCT Range
2700K	3 SDCM	(0.458, 0.410)	2651K - 2794K
5700K	3 SDCM	(0.329, 0.342)	5490K - 5820K
6500K	3 SDCM	(0.312, 0.328)	6250K - 6745K

Notes for Table 6

1. Color binning at solder point temperature Tsp of SMDs at 25°C for 80 CRI and 85°C for 90 CRI.
2. Bridgelux maintains a tolerance of ± 0.007 on x and y color coordinates in the CIE 1931 color space.
3. Quadrangular ANSI bins shown for reference only

Packaging and Labeling

Figure 21: Vesta Series Packaging and Labeling




Table 7: Packaging Structure

Box Parameter	L0280 modules	L0560 modules	L1120 modules
Quantity	320	160	160
Dimension	63.7 cm x 4.17 cm x 15.0 cm	63.7 cm x 4.17 cm x 15.0 cm	115.9 cm x 41.7 cm x 15.0 cm

Figure 22: Product Labeling

Bridgelux Vesta Series modules contain a label on the front to help with product identification. In addition to the product identification markings, Bridgelux Vesta Series modules also contain markings for internal Bridgelux manufacturing use only. The image below shows which markings are for customer use and which ones are for Bridgelux internal use only. The Bridgelux internal manufacturing markings are subject to change without notice, however these will not impact the form, function or performance of the module.



Vesta Series Gen3
280mm 1000lm 500mA

Customer Use- 2D Barcode
Scannable barcode provides
product part number and other
Bridgelux internal production
information.

Design Resources

Application Notes

Bridgelux has developed a comprehensive set of application notes and design resources to assist customers in successfully designing with the Vesta Series product family. For a list of resources under development, visit www.bridgelux.com.

Optical Source Models

Optical source models and ray set files are available for all Bridgelux products. For a list of available formats, visit www.bridgelux.com.

3D CAD Models

Three dimensional CAD models depicting the product outline of all Bridgelux Vesta Series modules are available in both IGES and STEP formats. Please contact your Bridgelux sales representative for assistance.

Precautions

CAUTION: CHEMICAL EXPOSURE HAZARD

Exposure to some chemicals commonly used in luminaire manufacturing and assembly can cause damage to the LED linear. Please consult Bridgelux Application Note for additional information.

CAUTION: EYE SAFETY

Eye safety classification for the use of Bridgelux Vesta Series is in accordance with IEC/TR62778: Application of IEC 62471 for the assessment of blue light hazard to light sources and luminaires. Vesta Series linears are classified as Risk Group 1 (TBD) when operated at or below the maximum drive current. Please use appropriate precautions. It is important that employees working with LEDs are trained to use them safely.

CAUTION: RISK OF BURN

Do not touch the Vesta Series modules during operation. Allow the linear to cool for a sufficient period of time before handling. The Vesta Series modules may reach elevated temperatures such that could burn skin when touched.

CAUTION

CONTACT WITH LIGHT EMITTING SURFACE (LES)

Avoid any contact with the LES. Do not touch or apply stress to the module SMD LESs (yellow phosphor resin area). Contact may cause damage to the module.

Optics and reflectors must not be mounted in contact with the LES (yellow phosphor resin area).

Optical devices may be mounted on the top surface of the module. Use the mechanical features of the module housing, edges and/or mounting holes to locate and secure optical devices as needed.

Disclaimers

STANDARD TEST CONDITIONS

Unless otherwise stated, module testing is performed at the nominal drive current.

MINOR PRODUCT CHANGE POLICY

The rigorous qualification testing on products offered by Bridgelux provides performance assurance. Slight cosmetic changes that do not affect form, fit, or function may occur as Bridgelux continues product optimization.

About Bridgelux: Bridging Light and Life™

At Bridgelux, we help companies, industries and people experience the power and possibility of light. Since 2002, we've designed LED solutions that are high performing, energy efficient, cost effective and easy to integrate. Our focus is on light's impact on human behavior, delivering products that create better environments, experiences and returns—both experiential and financial. And our patented technology drives new platforms for commercial and industrial luminaires.

For more information about the company, please visit

bridgelux.com

twitter.com/Bridgelux

facebook.com/Bridgelux

youtube.com/user/Bridgelux

linkedin.com/company/Bridgelux

WeChat ID: BridgeluxInChina



46430 Fremont Blvd
Fremont, CA 94538 USA
Tel (925) 583-8400
Fax (925) 583-8401
www.bridgelux.com

© 2020 Bridgelux, Inc. All rights reserved. Product specifications are subject to change without notice. Bridgelux and the Bridgelux stylized logo design and Vesta are registered trademarks of Bridgelux, Inc. EB Series and Bridging Light and Life are trademarks of Bridgelux, Inc. All other trademarks are the property of their respective owners.

Bridgelux Vesta TL Gen3 2R Data Sheet DS138 Rev. A (06/2020)

单击下面可查看定价，库存，交付和生命周期等信息

[>>Bridgelux\(普瑞光电\)](#)