



**Ordering Information:**

A2012H-XP - \*\*\*  
1 2

- 1.Part No.
- 2.Material:  
(blank):Nylon 66,UL94V-0  
GWT:Nylon 66,UL94V-0,GWT 750°C

**SPECIFICATIONS:**

- Current Rating: 3A AC,DC
- Voltage Rating: 250V AC,DC
- Temperature Range: -40°C ~ +105°C
- Contact Resistance: 10mΩ Max.
- Insulation Resistance: 1000MΩ Min.
- Withstanding Voltage: 800V AC/minute
- Material: Nylon 66,UL94V-0(White)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.00	4.30	6.00	9P	16.00	18.30	20.00
3P	4.00	6.30	8.00	10P	18.00	20.30	22.00
4P	6.00	8.30	10.00	11P	20.00	22.30	24.00
5P	8.00	10.30	12.00	12P	22.00	24.30	26.00
6P	10.00	12.30	14.00	13P	24.00	26.30	28.00
7P	12.00	14.30	16.00	14P	26.00	28.30	30.00
8P	14.00	16.30	18.00	15P	28.00	30.30	32.00

**CJTconn** CHANGJIANG CONNECTORS CO.,LTD.

Unit mm	Scale 4:1	Sheet 1 of 1	Title : <b>2.00mm Pitch Housing</b>
Draw By: Dlankul Wan	Approved : Jack Yln		
General Tolerance			
A1	CHANGE THE DIMENSIONS	2019.06.27	DRAW NO : <b>A2012H-XP</b>
A0	NEW RELEASE	2012.12.27	
REV	DESCRIPTION	DATE	

PROJECT

REV A1

A1	CHANGE THE DIMENSIONS	2019.06.27	x.xx±0.25
A0	NEW RELEASE	2012.12.27	x.xx±0.20
REV	DESCRIPTION	DATE	x.xxx±0.15

单击下面可查看定价，库存，交付和生命周期等信息

[>>CJTconn](#)