

Ordering Information:


A1251WR-S-XP - **
1 2

1.Part No.

2.Finish:

(blank): Tin over Nickel

G: Gold over Nickel



SPECIFICATIONS:

Current Rating: 1A AC,DC

Voltage Rating: 125V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 100MΩ Min.

Withstanding Voltage: 500V AC/minute

Pin Material: Phosphor Bronze/Tin over Nickel

Solder Tabs: Phosphor Bronze/Tin over Nickel

Material: LCP,UL94V-0(Ivory)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	1.25	7.25	10P	11.25	17.25
3P	2.50	8.50	11P	12.50	18.50
4P	3.75	9.75	12P	13.75	19.75
5P	5.00	11.00	13P	15.00	21.00
6P	6.25	12.25	14P	16.25	22.25
7P	7.50	13.50	15P	17.50	23.50
8P	8.75	14.75	16P	18.75	24.75
9P	10.00	16.00			



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1

Title :

1.25mm PITCH

Draw By:	Approved :
Diankui Wan	Jack Yin

90° WAFER - SMT TYPE

General Tolerance

A1	CHANGE THE MATERIAL	2018.10.23	x.x±0.25	PROJECT
A0	NEW RELEASE	2005.05.10	x.xx±0.20	
REV	DESCRIPTION	DATE	x.xxx±0.15	

DRAW NO : A1251WR-S-XP

REV A1

单击下面可查看定价，库存，交付和生命周期等信息

[>>CJTconn\(长江连接器\)](#)