

IGBT Module

Features



- 1200V 75A, $V_{CE(sat)(typ.)} = 2.3\text{ V}$
- SPT(Soft Punch Through)technology
- Lower losses
- Higher system efficiency
- Excellent short-circuit capability
- Square RBSOA

Mechanical Data

- **Case:** D1 (34mm)(plastic package).
Lead free; RoHS compliant
- **Molding Compound Flammability Rating:**
UL 94 V-0

Benefits

- Inverter for motor drive
- AC and DC servo drive amplifier
- Excellent Current Sharing in Parallel Operation



Equivalent Circuit Schematic

Applications

CREATEK's IGBTs offer lower losses and higher energy for application such as motor drive ,UPS, inverter and other soft switching applications.

Absolute Maximum Ratings of IGBT

Symbol	Parameter	Value	Units
V_{CES}	Collector to Emitter Voltage	1200	V
V_{GES}	Continuous Gate to Emitter Voltage	± 30	V
I_C	Continuous Collector Current	$T_C = 25^\circ\text{C}$	150
		$T_C = 100^\circ\text{C}$	75
I_{CM}	Pulse Collector Current	$T_J = 150^\circ\text{C}$	150
P_D	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ\text{C}, T_J = 150^\circ\text{C}$	320
t_{sc}	Short Circuit Withstand Time	> 10	μs
T_J	Maximum IGBT Junction Temperature	150	$^\circ\text{C}$
T_{JOP}	Maximum Operating Junction Temperature Range	-40 to +150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-40 to +125	$^\circ\text{C}$

Absolute Maximum Ratings of Freewheeling Diode

Symbol	Parameter	Value	Units
V_{RRM}	Repetitive Peak Reverse Voltage Preliminary Data	1200	V
I_F	Diode Continuous Forward Current	$T_C = 25^\circ\text{C}$	150
	Diode Continuous Forward Current	$T_C = 100^\circ\text{C}$	75
I_{FM}	Diode Maximum Forward Current	150	A

Electrical Characteristics of IGBT ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	TestConditions	Min.	Typ.	Max.	Units
BV_{CES}	Collector to Emitter Breakdown Voltage	$V_{GE} = 0V, I_C = 1mA$	1200			V
I_{CES}	Collector to Emitter Leakage Current	$V_{GE} = 0V, V_{CE} = V_{CES}$			1	mA
I_{GES}	Gate to Emitter Leakage Current	$V_{GE} = \pm 30V, V_{CE} = 0V$			200	nA
$V_{GE(th)}$	Gate Threshold Voltage	$I_C = 1mA, V_{CE} = V_{GE}$	4.5		5.7	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Module Level)	$I_C = 75A, V_{GE} = 15V$		2.30	2.50	V
				2.70		

Electrical Characteristics of IGBT ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	TestConditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600V$ $I_C = 75A$ $R_G = 7.5\Omega$ $V_{GE} = \pm 15V$ Inductive Load	$T_J = 25^{\circ}\text{C}$		20	ns
			$T_J = 125^{\circ}\text{C}$		25	
t_r	Turn-on Rise Time		$T_J = 25^{\circ}\text{C}$		30	ns
			$T_J = 125^{\circ}\text{C}$		40	
$t_{d(off)}$	Turn-off Delay Time		$T_J = 25^{\circ}\text{C}$		230	ns
			$T_J = 125^{\circ}\text{C}$		240	
t_f	Turn-off Fall Time		$T_J = 25^{\circ}\text{C}$		110	ns
			$T_J = 125^{\circ}\text{C}$		190	
E_{on}	Turn-on Switching Loss		$T_J = 25^{\circ}\text{C}$		3.40	mJ
			$T_J = 125^{\circ}\text{C}$		4.30	
E_{off}	Turn-off Switching Loss	$T_J = 25^{\circ}\text{C}$		1.90	mJ	
		$T_J = 125^{\circ}\text{C}$		3.40		
Q_g	Total Gate Charge	$T_J = 25^{\circ}\text{C}$		490	nC	
R_{gint}	Integrated gate resistor	$f = 1M;$ $V_{pp} = 1V$	$T_J = 25^{\circ}\text{C}$	2.3		Ω
C_{ies}	Input Capacitance	$V_{CE} = 25V$ $V_{GE} = 0V$ $f = 1MHz$	$T_J = 25^{\circ}\text{C}$	5.2	nF	
C_{oes}	Output Capacitance		$T_J = 25^{\circ}\text{C}$	0.69		
C_{res}	Reverse Transfer Capacitance		$T_J = 25^{\circ}\text{C}$	0.45		
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case (IGBT)				0.39	$^{\circ}\text{C/W}$

Electrical and Switching Characteristics of Freewheeling Diode

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F = 75A$,	$T_J = 25^\circ C$		1.90	2.20	V
		$V_{GE} = 0V$	$T_J = 125^\circ C$		1.90		
t_{rr}	Diode Reverse Recovery Time	$I_F = 75A$, $di/dt = 1400A/\mu s$, $V_{rr} = 600V$,	$T_J = 25^\circ C$		120		ns
			$T_J = 125^\circ C$		260		
I_{rr}	Diode Peak Reverse Recovery Current		$T_J = 25^\circ C$		80		A
			$T_J = 125^\circ C$		90		
Q_{rr}	Diode Reverse Recovery Charge		$T_J = 25^\circ C$		6.0		nC
			$T_J = 125^\circ C$		10.5		
E_{rr}	Diode Reverse Recovery Energy		$T_J = 25^\circ C$		2.00		mJ
			$T_J = 125^\circ C$		3.90		
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case (Diode)					0.63	$^\circ C/W$

Absolute Maximum Ratings of Freewheeling Diode

Symbol	Parameter	Min.	Typ.	Max.	Units
V_{iso}	Isolation Voltage (All Terminals Shorted), $f = 50Hz$, 1minute	2500			V
$R_{\theta CS}$	Case-To-Sink(Conductive Grease Applied)		0.1		$^\circ C/W$
M	Power Terminals Screw: M5	3.0		5.0	N·m
M	Mounting Screw: M6	4.0		6.0	N·m
G	Weight		160		g

Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)




Fig 5. switching losses IGBT, $E_{on}=f(R_g), E_{off}=f(R_g), V_{GE}=\pm 15V, I_C=75A, V_{CE}=600V$




Fig 6. transient thermal impedance IGBT, $Z_{thjc}=f(t)$




Fig 7. reverse bias safe operating area IGBT, $I_C=f(V_{CE}), V_{GE}=\pm 15V, R_{Goff}=7.5\Omega, T_j=125^\circ C$




Fig 8. forward characteristic of Diode, $I_F=f(V_F)$




Fig 9. switching losses Diode,
 $E_{rr}=f(I_F), R_{Gon}=7.5\Omega, V_{CE}=600V$






Fig 10. switching losses Diode,
 $E_{rr}=f(R_G), I_F=75A, V_{CE}=600V$



Package Dimensions(mm)



Ordering information

Order code	Package	Packaging option	Base quantity	Packaging specification
GPU75HF120D1SE	D1(32mm)	BOX	16pcs /BOX	

Revision history

Date	Revision	Changes
23-May-2016	1.0	Initial release
30-July-2018	2.0	Update

CAUTION / WARNING

Information in this document is believed to be accurate and reliable. However, CREATEK does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Users should independently evaluate the suitability of and test each product selected for their own applications, and CREATEK assumes no liability whatsoever relating to the choice, selection or use of the CREATEK products and services described herein.

CREATEK reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product.

Information in this document supersedes and replaces all information previously supplied.

Products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an CREATEK product can reasonably be expected to result in personal injury, death or severe property or environmental damage. CREATEK accepts no liability for inclusion and/or use of CREATEK products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.


This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Resale of CREATEK products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by CREATEK for the CREATEK product or service described herein and shall not create or extend in any manner whatsoever, any liability of CREATEK.

CREATEK expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. CREATEK only obligations are those in the CREATEK Standard Terms and Conditions of Sale and in no case will CREATEK be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

Specifications are subject to change without notice

© Copyright 2009, CREATEK Microelectronics

 CREATEK® is a registered trademark of CREATEK Microelectronics

All rights reserved

单击下面可查看定价，库存，交付和生命周期等信息

[>>CREATEK](#)