



CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Features

- High isolation 5000 VRMS
- CTR flexibility available see order information
- Extra low coupling capacitance
- DC input with transistor output
- Temperature range - 55 °C to 110 °C
- Regulatory Approvals
 - UL - UL1577 (E364000)
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1, GB8898
 - IEC60065, IEC60950
- Creepage distance > 8 mm
- Green Package


Applications

- Switch mode power supplies
- Computer peripheral interface
- Microprocessor system interface


Description

The CT1010, CT1011, CT1012, CT1013, CT1014, CT1015, CT1016, CT1017, CT1018, CT1019 series consists of a photo transistor optically coupled to a gallium arsenide Infrared-emitting diode in a 4-lead SOP Package.

Package Outline



Schematic





CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019 DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
V _{ISO}	Isolation voltage *1	5000	V _{RMS}	
T _{OPR}	Operating temperature	-55 ~ +110	°C	
T _{STG}	Storage temperature	-55 ~ +125	°C	
T _{SOL}	Soldering temperature *2	260	°C	
Emitter				
I _F	Forward current	50	mA	
I _{F(TRANS)}	Peak transient current (≤1μs P.W,300pps)	1	A	
V _R	Reverse voltage	6	V	
P _D	Power dissipation	85	mW	
Detector				
P _C	Power dissipation	150	mW	
B _{VCEO}	Collector-Emitter Breakdown Voltage	80	V	
B _{VECO}	Emitter-Collector Breakdown Voltage	7	V	
I _C	Collector Current	50	mA	



CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Emitter Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V_F	Forward voltage	$I_F = 10\text{mA}$		1.24	1.4	V	
		$I_F = 50\text{mA}$	-	1.45	1.5	V	
I_R	Reverse Current	$V_R = 6\text{V}$	-	-	5	μA	
C_{IN}	Input Capacitance	$f = 1\text{kHz}$	-	45	-	pF	

Detector Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$B_{V_{CEO}}$	Collector-Emitter Breakdown	$I_C = 100\mu\text{A}$	80	-	-	V	
$B_{V_{ECO}}$	Emitter-Collector Breakdown	$I_E = 100\mu\text{A}$	7	-	-	V	
I_{CEO}	Collector-Emitter Dark Current	$V_{CE} = 20\text{V}, I_F = 0\text{mA}$	-	-	100	nA	

Transfer Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
CTR	Current Transfer Ratio	CT1012	$I_F = 1\text{mA}, V_{CE} = 5\text{V}$	22	-	-	%
		CT1013		34	-	-	
		CT1014		56	-	-	
		CT1011	$I_F = 10\text{mA}, V_{CE} = 5\text{V}$	60	-	300	
		CT1012		63	-	125	
		CT1013		100	-	200	
		CT1014		160	-	320	
		CT1010	$I_F = 5\text{mA}, V_{CE} = 5\text{V}$	50	-	600	
		CT1015		50	-	150	
		CT1016		100	-	300	
		CT1017		80	-	160	
		CT1018		130	-	260	
		CT1019		200	-	400	
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	$I_F = 10\text{mA}, I_C = 1\text{mA}$	-	-	0.4	V	
R_{IO}	Isolation Resistance	$V_{IO} = 500\text{V}_{DC}$	5×10^{10}			Ω	
C_{IO}	Isolation Capacitance	$f = 1\text{MHz}$			1	pF	



CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019 DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$, $V_{CC} = 5\text{V}$ (unless otherwise specified)

Switching Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
T_{ON}	Turn On Time	$I_C = 5\text{mA}$, $V_{CE} = 5\text{V}$, $R_L = 100\Omega$	-	5	-	μs	
T_{OFF}	Turn Off Time		-	4.2	-		
t_r	Rise Time		-	2.8	-		
t_f	Fall Time		-	4.1	-		



CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019 DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Typical Characteristic Curves




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6



CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019 DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler




Figure 7




Figure 8




Figure 9





Figure 10




CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019 DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Package Dimension *Dimensions in mm unless otherwise stated*



Recommended Solder Mask *Dimensions in mm unless otherwise stated*





CT1010, CT1011, CT1012, CT1013, CT1014

CT1015, CT1016, CT1017, CT1018, CT1019

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Marking Information



Note:

CT : Denotes "CT Micro"
1019 : Part Number
V : VDE Option
Y : Fiscal Year
WW : Work Week
K : Manufacturing Code

Ordering Information

CT101X(V)(Y)-G

X = Part No. (0,1,2,3,4,5,6,7,8,9)

V = VDE Option (V or None)

Y = Tape and reel option (T1 or T2)

G = Material option (G: Green, None: Non-green)

Option	Description	Quantity
T1	Surface Mount Lead Forming – With Option 1 Taping	3000Units/Reel
T2	Surface Mount Lead Forming – With Option 2 Taping	3000Units/Reel




CT1010, CT1011, CT1012, CT1013, CT1014 CT1015, CT1016, CT1017, CT1018, CT1019


DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Carrier Tape Specifications *Dimensions in mm unless otherwise stated*

Option T1



Option T2






CT1010, CT1011, CT1012, CT1013, CT1014

CT1015, CT1016, CT1017, CT1018, CT1019

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T Amin)	150°C
Temperature Max. (Tsmax)	200°C
Time (ts) from (T Amin to Tsmax)	60-120 seconds
Ramp-up Rate (tL to tp)	3°C/second max.
Liquidous Temperature (TL)	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (tp) within 5°C of 260°C	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



**CT1010, CT1011, CT1012, CT1013, CT1014
CT1015, CT1016, CT1017, CT1018, CT1019
DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler**

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*

单击下面可查看定价，库存，交付和生命周期等信息

[>>CT-MICRO\(兆龙科技\)](#)