



### Features

- High isolation 5300 VRMS
- DC input with transistor output
- Operating temperature range - 55 °C to 125 °C
- RoHS compliance
- REACH compliance
- Halogen free
- Regulatory Approvals
  - UL - UL1577 (Pending Approval)
  - VDE - EN60747-5-5 (Pending Approval)
  - CQC – GB4943.1, GB8898 (Pending Approval)
  - IEC60065, IEC60950 (Pending Approval)


### Description

The CT785 series consists of a photo transistor optically coupled to a gallium arsenide Infrared-emitting diode in a DIP package.


### Applications

- Switch mode power supplies
- Computer peripheral interface
- Microprocessor system interface

### Package Outline



### Schematic



CT785

**Absolute Maximum Rating at 25°C**

<b>Symbol</b>	<b>Parameters</b>	<b>Ratings</b>	<b>Units</b>	<b>Notes</b>
V <sub>ISO</sub>	Isolation voltage	5300	V <sub>RMS</sub>	
P <sub>TOT</sub>	Total power dissipation	200	mW	
T <sub>OPR</sub>	Operating temperature	-55 ~ +125	°C	
T <sub>STG</sub>	Storage temperature	-55 ~ +150	°C	
T <sub>SOL</sub>	Soldering temperature	260	°C	
<b>Emitter</b>				
I <sub>F</sub>	Forward current	60	mA	
I <sub>F(TRANS)</sub>	Peak transient current (≤1μs P.W,300pps)	1000	mA	
V <sub>R</sub>	Reverse voltage	6	V	
P <sub>D</sub>	Emitter power dissipation	100	mW	
<b>Detector</b>				
P <sub>C</sub>	Detector power dissipation	150	mW	
B <sub>VCEO</sub>	Collector-Emitter Breakdown Voltage	80	V	
B <sub>VECO</sub>	Emitter-Collector Breakdown Voltage	7	V	
I <sub>C</sub>	Collector Current	80	mA	

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  (unless otherwise specified)**Emitter Characteristics**

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$V_F$	Forward voltage	$I_F = 10\text{mA}$	-	1.2	1.3	V	
$I_R$	Reverse Current	$V_R = 6\text{V}$	-	-	5	$\mu\text{A}$	
$C_{IN}$	Input Capacitance	$f = 1\text{MHz}$	-	10	30	pF	

**Detector Characteristics**

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$B_{V_{CEO}}$	Collector-Emitter Breakdown	$I_C = 100\mu\text{A}$	80	-	-	V	
$B_{V_{ECO}}$	Emitter-Collector Breakdown	$I_{EC} = 100\mu\text{A}$	7	-	-	V	
$I_{CEO}$	Collector-Emitter Dark Current	$V_{CE} = 24\text{V}, I_F = 0\text{mA}$	-	-	100	nA	
		$V_{CE} = 24\text{V}, I_F = 0\text{mA}, T_A = 85^\circ\text{C}$			50	$\mu\text{A}$	

**Transfer Characteristics**



Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes	
CTR	Current Transfer Ratio	CT785GB	$I_F = 5\text{mA}, V_{CE} = 5\text{V}$	100		600	%	
		CT785GR		100		300		
		CT785BLL		200		400		
$CTR_{(sat)}$	Saturated CTR	CT785GB	$I_F = 1\text{mA}, V_{CE} = 0.4\text{V}$	-	60	-	%	
		CT785GR		30	-	-		
		CT785BLL		-	60	-		
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	$I_F = 8\text{mA}, I_C = 2.4\text{mA}$	-	0.2	0.4	V		
$R_{IO}$	Isolation Resistance	$V_{IO} = 500\text{V}_{DC}$	$5 \times 10^{10}$	-	-	$\Omega$		
$C_{IO}$	Isolation Capacitance	$f = 1\text{MHz}$	-	0.25	1	pF		



### Switching Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
$t_r$	Rise Time	$I_C = 2\text{mA}$ , $V_{CE} = 2\text{V}$ $R_L = 100\Omega$	-		16	$\mu\text{s}$	
$t_f$	Fall Time		-		16		
$t_{on}$	Turn-on time				20	$\mu\text{s}$	
$t_{off}$	Turn-off time				20		

### Test Circuit





### Typical Characteristic Curves




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10





Figure 11




**Package Dimension** *Dimensions in mm unless otherwise stated*

**Standard DIP – Through Hole**




**Gullwing (400mil) Lead Forming – Through Hole (M Type)**






Surface Mount Lead Forming (S Type)



Surface Mount (Low Profile) Lead Forming (SL Type)








# CT785 Series DC 4-Pin DIP Phototransistor Optocoupler


## Surface Mount (Gullwing) Lead Forming (SLM Type)






**Recommended Solder Mask** *Dimensions in mm unless otherwise stated*

**Surface Mount Lead Forming & Surface Mount (Low Profile) Lead Forming**



**Surface Mount (Gullwing) Lead Forming**



**Marking Information**



**Note:**

- CT : Denotes "CT Micro"
- 785 : Part Number
- X : "X" is CTR Rank (X= GB, GR, BLL)
- V : VDE Safety Option (V or none)
- Y : Fiscal Year
- WW : Work Week
- K : Manufacturing Code



Ordering Information

CT785X(V)(W)(Y)

- CT : Denotes “CT Micro”
- 785 : Part Number
- X : “X” is CTR Rank (X= GB, GR ,BLL)
- V : VDE Safety Option(V or none)
- W : Lead form option (S, SL, SLM, M or none)
- Y : Tape and reel option (T1, T2 or none)

<b>Option</b>	<b>Description</b>	<b>Quantity</b>
None	Standard 4 Pin DIP	100 Units/Tube
M	Gullwing (400mil) Lead Forming	100 Units/Tube
S(T1)	Surface Mount Lead Forming – With Option 1 Taping	1500 Units/Reel
S(T2)	Surface Mount Lead Forming – With Option 2 Taping	1500 Units/Reel
SL(T1)	Surface Mount (Low Profile) Lead Forming– With Option 1 Taping	1500 Units/Reel
SL(T2)	Surface Mount (Low Profile) Lead Forming – With Option 2 Taping	1500 Units/Reel
SLM(T1)	Surface Mount (Gullwing) Lead Forming– With Option 1 Taping	1500 Units/Reel
SLM(T2)	Surface Mount (Gullwing) Lead Forming – With Option 2 Taping	1500 Units/Reel



### Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature:  $260 \pm 5^\circ\text{C}$ .

Time: 10 sec.

Preheat temperature: 25 to  $140^\circ\text{C}$ .

Preheat time: 30 to 80 sec.



### Hand soldering by soldering iron


Allow single lead soldering in every single process.

One time soldering is recommended. Temperature:  $350 \pm 5^\circ\text{C}$

Time: 3 sec max.



Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T Amin)	150°C
Temperature Max. (Tsmax)	200°C
Time (ts) from (T Amin to Tsmax)	60-120 seconds
Ramp-up Rate (tL to tp)	3°C/second max.
Liquidous Temperature (TL)	217°C
Time (tL) Maintained Above (TL)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (tp) within 5°C of 260°C	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



---

## DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

---

DISCOLORATION MIGHT OCCUR ON THE PACKAGE SURFACE AFTER SOLDERING, REFLOW OR LONG TERM USE. THIS DOES NOT IMPACT THE PRODUCT PERFORMANCE NOR THE PRODUCT RELIABILITY.

---

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*

单击下面可查看定价，库存，交付和生命周期等信息

[>>CT-MICRO\(兆龙科技\)](#)