

Sealed Choke Coil SDET25201B type

■ **Features**

Low profile : 2.5mm x 2.0mm x 1.2mm

Low coil resistance with large currents.


High magnetic shield construction should actualize high resolution for EMC protection.

100% lead (Pb) free meet RoHS standard


■ **Application**

Cellular phones, LCD displays, HDDs, DVCs, DSCs, PDAs etc..

■ **Outline Dimensions**




Code	Dimensions (mm)
L	2.0 ± 0.2
W	2.5 ± 0.2
T	1.2 Max.



Note: This graph is in regard to outline dimensions spec. For outer appearance, please refer to actual product.

■ **Recommend Land Pattern Dimensions**

The customer shall determine the land dimensions shown below after confirming and safety.



A	2.1
B	0.8
C	2.6

Unit : mm

■ Specifications

Part Number	L0 Inductance (μH) @ (0A)	R_{dc} (m Ω)		Heat Rating Current DC Amps. Idc (A)		Saturation Current DC Amps. Isat (A)	
		Typical	Maximum	Typical	Maximum	Typical	Maximum
SDET25201B-R47MS	0.47	24.0	28.5	3.70	3.35	3.90	3.50
SDET25201B-R68MS	0.68	31.0	36.0	3.30	2.97	2.90	2.60
SDET25201B-1R0MS	1.0	37.0	43.0	2.65	2.40	2.75	2.50
SDET25201B-1R5MS	1.5	63.0	72.0	2.30	2.07	2.35	2.12
SDET25201B-2R2MS	2.2	80.0	90.0	1.90	1.80	2.15	1.95
SDET25201B-3R3MS	3.3	140.0	155.0	1.50	1.35	1.70	1.60
SDET25201B-4R7MS	4.7	185.0	210.0	1.40	1.25	1.50	1.40
SDET25201B-100MS	10.0	359.0	408.0	0.90	0.81	0.87	0.80
SDET25201B-220MS	22.0	900.0	1050.0	0.52	0.46	0.56	0.50

* : If you require another part number please contact with us.

** : Inductance Tolerance $\pm 20\%$

Note 1. : All test data is referenced to 25°C ambient.

Note 2. : Test Condition:1MHz, 1.0Vrms

Note 3. : Idc : DC current (A) that will cause an approximate ΔT of 40°C









Note 4. : Isat : DC current (A) that will cause L0 to drop approximately 30%


Note 5. : Operating Temperature Range -55°C to +125°C

Note 6. : The part temperature (ambient + temp rise) should not exceed 125°C under the worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Note 7. : The rated current as listed is either the saturation current or the heating current depending on which value is lower.

Current Characteristic





单击下面可查看定价，库存，交付和生命周期等信息

[>>CYNTEC\(乾坤科技\)](#)