

Features




- $BV_{CEO} > -40V$
- $BV_{ECO} > -3V$
- $I_C = -3A$ Continuous Collector Current
- $V_{CE(sat)} < -85mV @ -1A$
- $R_{CE(sat)} = 55m\Omega$ typical
- $P_D = 1.25W$
- High Power Dissipation SOT23 Package
- High Peak Current
- Low Saturation Voltage
- 3V Reverse Blocking Voltage
- Complementary Part Number: ZXTN25040DFH
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **For automotive applications requiring specific change control (i.e.: parts qualified to AEC-Q100/101/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please refer to the related automotive grade (Q-suffix) part. A listing can be found at**
<https://www.diodes.com/products/automotive/automotive-products/>
- **This part is qualified to JEDEC standards (as references in AEC-Q) for High Reliability.**
<https://www.diodes.com/quality/product-definitions/>

Mechanical Data

- Case: SOT23
- Case Material: Molded Plastic, "Green" Molding Compound
UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish – Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 (Ⓢ)
- Weight: 0.008 grams (Approximate)

Applications

- MOSFET and IGBT gate driving
- DC-DC converters
- Motor drives
- High-side drivers




Ordering Information (Note 4)

| Product | Marking | Reel size (inches) | Tape width (mm) | Quantity per reel |
|----------------|---------|--------------------|-----------------|-------------------|
| ZXTP25040DFHTA | 024 | 7 | 8 | 3,000 |

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
 2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen and Antimony free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 4. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.

Marking Information



024 = Product Type Marking Code

Absolute Maximum Ratings @ T_A = +25°C, unless otherwise specified.

| Characteristic | Symbol | Value | Unit |
|--|------------------|-------|------|
| Collector-Base Voltage | V _{CB0} | -45 | V |
| Collector-Emitter Voltage (Forward Blocking) | V _{CEO} | -40 | V |
| Emitter-collector voltage (Reverse Blocking) | V _{ECO} | -3 | V |
| Emitter-Base Voltage | V _{EBO} | -7 | V |
| Continuous Collector Current | I _C | -3 | A |
| Peak Pulse Current | I _{CM} | -9 | A |

Thermal Characteristics @ T_A = +25°C unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|---|-----------------------------------|-------------|------------|
| Power Dissipation Linear derating factor | P _D | 0.73 | W mW/°C |
| | | 5.84 | |
| | | 0.78 | |
| | | 6.24 | |
| | | 1.05 | |
| | | 8.4 | |
| | | 1.25 | |
| | | 9.6 | |
| | | 1.81 | |
| | | 14.5 | |
| Thermal Resistance, Junction to Ambient | R _{θJA} | 171 | °C/W |
| | | 160 | |
| | | 119 | |
| | | 100 | |
| | | 69 | |
| Thermal Resistance, Junction to Lead | R _{θJL} | 74.95 | °C/W |
| Thermal Resistance, Junction to Case | R _{θJC} | 45 | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | °C |





- Notes:
5. For a device surface mounted on 15mm x 15mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
 6. Same as note (5), except the device is mounted on FR4 substrate PCB layout with minimum recommended pad layout.
 7. Same as note (5), except the device is surface mounted on 25mm x 25mm with 2 oz copper.
 8. Same as note (5), except the device is surface mounted on 50mm x 50mm with 2 oz copper.
 9. Same as note (8), except the device is measured at t<5secs.
 10. Thermal resistance from junction to solder-point (at the end of the collector lead).
 11. Thermal resistance from junction to the top of the case.

ESD Ratings (Note 12)

| Characteristic | Symbol | Value | Unit | JEDEC Class |
|--|---------|-------|------|-------------|
| Electrostatic Discharge - Human Body Model | ESD HBM | 4,000 | V | 3A |
| Electrostatic Discharge - Machine Model | ESD MM | 400 | V | C |

- Note: 12. Refer to JEDEC specification JESD22-A114 and JESD22-A115.

Thermal Characteristics and Derating Information








Electrical Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|---|---------------|-----|------|-------|---------------|---|
| Collector-Base Breakdown Voltage | BV_{CBO} | -45 | -75 | - | V | $I_C = -100\mu\text{A}$ |
| Collector-Emitter Breakdown Voltage (Note 13) | BV_{CEO} | -40 | -65 | - | V | $I_C = -10\text{mA}$ |
| Emitter-Base Breakdown Voltage | BV_{EBO} | -7 | -8.2 | - | V | $I_E = -100\mu\text{A}$ |
| Emitter-Collector Breakdown Voltage | BV_{ECO} | -3 | -8.7 | - | V | $I_E = -100\mu\text{A}$ |
| Collector-Base Cutoff Current | I_{CBO} | - | < -1 | -50 | nA | $V_{CB} = -45\text{V}$ |
| | | - | - | -0.5 | μA | $V_{CB} = -45\text{V}, T_{amb} = +100^\circ\text{C}$ |
| Emitter-Base Cutoff Current | I_{EBO} | - | < -1 | -50 | nA | $V_{EB} = -5.6\text{V}$ |
| Static Forward Current Transfer Ratio (Note 13) | h_{FE} | 300 | 450 | 900 | - | $I_C = -10\text{mA}, V_{CE} = -2\text{V}$ |
| | | 200 | 300 | - | | $I_C = -1\text{A}, V_{CE} = -2\text{V}$ |
| | | 30 | 60 | - | | $I_C = -3\text{A}, V_{CE} = -2\text{V}$ |
| Collector-Emitter Saturation Voltage (Note 13) | $V_{CE(sat)}$ | - | -170 | -260 | mV | $I_C = -1\text{A}, I_B = -20\text{mA}$ |
| | | - | -65 | -85 | | $I_C = -1\text{A}, I_B = -100\text{mA}$ |
| | | - | -165 | -220 | | $I_C = -3\text{A}, I_B = -300\text{mA}$ |
| Base-Emitter Saturation Voltage (Note 13) | $V_{BE(sat)}$ | - | -930 | -1000 | mV | $I_C = -3\text{A}, I_B = -300\text{mA}$ |
| Base-Emitter Saturation Voltage (Note 13) | $V_{BE(on)}$ | - | -830 | -900 | mV | $I_C = -3\text{A}, V_{CE} = -2\text{V}$ |
| Output Capacitance | C_{obo} | - | 17.4 | | pF | $V_{CB} = -10\text{V}, f = 1\text{MHz}$ |
| Transition Frequency | f_T | - | 270 | - | MHz | $V_{CE} = -10\text{V}, I_C = -50\text{mA}, f = 100\text{MHz}$ |
| Turn-on Time | $t_{(on)}$ | - | 75.5 | - | ns | $V_{CC} = -15\text{V}, I_C = -750\text{mA},$ |
| Turn-off Time | $t_{(off)}$ | - | 320 | - | ns | $I_{B1} = -I_{B2} = -15\text{mA}$ |

Note: 13. Measured under pulsed conditions. Pulse width $\leq 300\mu\text{s}$. Duty cycle $\leq 2\%$.


Typical Electrical Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)



Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SOT23




| SOT23 | | | |
|----------------------|-------|-------|-------|
| Dim | Min | Max | Typ |
| A | 0.37 | 0.51 | 0.40 |
| B | 1.20 | 1.40 | 1.30 |
| C | 2.30 | 2.50 | 2.40 |
| D | 0.89 | 1.03 | 0.915 |
| F | 0.45 | 0.60 | 0.535 |
| G | 1.78 | 2.05 | 1.83 |
| H | 2.80 | 3.00 | 2.90 |
| J | 0.013 | 0.10 | 0.05 |
| K | 0.890 | 1.00 | 0.975 |
| K1 | 0.903 | 1.10 | 1.025 |
| L | 0.45 | 0.61 | 0.55 |
| L1 | 0.25 | 0.55 | 0.40 |
| M | 0.085 | 0.150 | 0.110 |
| a | 0° | 8° | -- |
| All Dimensions in mm | | | |

Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SOT23



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 2.0 |
| X | 0.8 |
| X1 | 1.35 |
| Y | 0.9 |
| Y1 | 2.9 |

IMPORTANT NOTICE

1. DIODES INCORPORATED AND ITS SUBSIDIARIES (“DIODES”) MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes products. Diodes products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of the Diodes products for their intended applications, (c) ensuring their applications, which incorporate Diodes products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes’ websites, harmless against all damages and liabilities.
4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes’ website) under this document.
5. Diodes products are provided subject to Diodes’ Standard Terms and Conditions of Sale (<https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/>) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
6. Diodes products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

Copyright © 2021 Diodes Incorporated

www.diodes.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Diodes Incorporated\(达达科技\(美台\)\)](#)