

TRENCH SCHOTTKY RECTIFIER

REVERSE VOLTAGE – 150 Volts
FORWARD CURRENT – 10 Amperes

FEATURES

- Super Low Forward Voltage Drop
- Reliable High Temperature Operation
- Softest, fast switching capability
- Qualified according to AEC-Q101 Rev_D


APPLICATIONS

- Device optimized for ultra-low forward voltage drop to maximize efficiency in Power Supply application

MECHANICAL DATA


- Case: JEDEC TO-220ABFP
- Case Material: "Green" Molding compound, UL flammability classification 94V-0, "Halogen-free".
- Lead free finish, RoHS compliant
- Marking code: G10H150CTFW
- Weight: 1.558 grams (Approximate)

ITO-220(S)AB



ITO-220(S)AB		
DIM	MIN	MAX
A	14.95	15.95
B	10.00	10.40
C	2.76	3.36
D	8.50	8.80
E	2.10	2.50
F	13.00	13.70
G	1.15	1.37
H	2.40	2.70
I	0.50	0.80
J	0.45	0.70
K	3.00	3.30
L	4.46	4.87
M	2.48	2.80
N	2.50	2.80

All dimension in millimeter



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

ABSOLUTE RATINGS

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	150	V
Maximum DC blocking voltage	V_{DC}	150	V
Maximum Average rectified forward current	I_{AV}	10	A
Peak forward surge 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	180	A
Operating and Storage temperature range	T_J, T_{STG}	-55 ~ +175	°C

STATIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITION	SYMBOL	TYP	MAX	UNIT
Forward voltage (Note 1)	$I_F = 5A$ $T_J = 25^\circ C$ $T_J = 125^\circ C$	V_F	--	0.79 0.63	V
Reverse leakage current	$V_R = 150V$ $T_J = 25^\circ C$ $T_J = 125^\circ C$	I_R	--	8 10	μA mA

DYNAMIC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TYP	UNIT
Typical junction capacitance (Note 2)	C_J	550	pF

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	TYP	UNIT
Typical thermal resistance (Note 3,4)	R_{thJL} R_{thJc}	6 5	°C/W

Note :

- (1) 300us pulse width, 2% duty cycle
- (2) Measured at 1.0MHz and applied reverse voltage of 4.0 VDC
- (3) Thermal Resistance test performed in accordance with JESD-51.
- (4) The unit mounted on Aluminum fin-type heatsink (23mm x 20mm x 8.7mm)

REV-0, Oct.-2020, KTHC238

Please be aware that an **Important Notice and Disclaimer** concerning availability, disclaimers, and use in critical applications of LSC products thereto appears at the end of this Data Sheet.

FIG.1 FORWARD CURRENT DERATING CURVE




FIG.2 MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 TYPICAL FORWARD CHARACTERISTICS




FIG.4 TYPICAL JUNCTION CAPACITANCE




FIG.5 TYPICAL REVERSE CHARACTERISTICS




FIG.6- AVERAGE FORWARD POWER DISSIPATION VS AVERAGE FORWARD CURRENT






FIG.7- NORMALIZED AVALANCHE POWER
DERATING VERSUS PULSE DURATION




Marking information:




Packaging Information:


1. TUBE



2. AIR BAG




3. INNERBOX



Packaging Information:

4. CARTON



Unit:mm

P/N	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	Q'ty/per	REMARK
TUBE	536	5.6	31.8	50	/
AIR BAG	800	550	/	/	/
INNERBOX	555	165	105	2000	40TUBE
CARTON	575	179	225	4K	2 INNER BOX

IMPORTANT NOTICE AND DISCLAIMER

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design purchase or use.

ALL INFORMATION ARE PROVIDED AS-IS, EVEN IT HAS QUALIFIED BY THE AEC-Q101 WHICH SATISFY INDUSTRIAL APPLICATION REQUIREMENT, EXCEPT AS EXPRESSLY STATED IN THIS DATA SHEET IS APPLIED FOR AUTOMOTIVE GRADE, LSC MAKE NO WARRANTIES, REPRESENTATION OR GUARANTEE, WHETHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING, WITHOUT LIMITATION, REGARDING ANY MERCHANTABILITY, SATISFACTORY QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE LSC TECHNOLOGY.

LSC DOES NOT ASSUME ANY LIABILITY OR COMPENSATION FOR ANY APPLICATION ASSISTANCE OR CUSTOMER PRODUCT DESIGN, AND MAKE NO WARRANTY OR ACCEPT ANY LIABILITY WITH PRODUCTS, WHICH ARE PURCHASED OR USED FOR ANY UNINTENDED OR UNAUTHORIZED APPLICATION.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Diodes Incorporated\(达达科技\(美台\)\)](#)