



6 PIN DIP PHOTODARLINGTON PHOTOCOUPLER TIL113, 4NXX, H11BX Series



Schematic



Pin Configuration

1. Anode
2. Cathode
3. No Connection
4. Emitter
5. Collector
6. Base

Features:

- 4NXX series: 4N29, 4N30, 4N31, 4N32, 4N33
- H11BX series: H11B1, H11B2, H11B3, H11B255
- High isolation voltage between input and output (Viso=5000 V rms)
- Creepage distance >7.62 mm
- Operating temperature up to +110°C
- Compact small outline package
- The product itself will remain within RoHS compliant version
- Compliance with EU REACH
- UL and cUL approved(No. E214129)
- VDE approved (No. 132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CQC approved

Description

The TIL113, 4NXX and H11BX series of devices each consist of an infrared emitting diode optically coupled to a photo darlington detector.

They are packaged in a 6-pin DIP package and available in wide-lead spacing and SMD option.

Applications

- Low power logic circuits
- Telecommunications equipment
- Portable electronics
- Interfacing coupling systems of different potentials and impedances

Absolute Maximum Ratings (Ta=25°C)

| | Parameter | Symbol | Rating | Unit |
|--------|--|-----------|----------|-------|
| Input | Forward current | I_F | 60 | mA |
| | Peak forward current (1us, pulse) | I_{FP} | 1 | A |
| | Reverse voltage | V_R | 6 | V |
| | Power dissipation No derating required up to Ta = 100°C | P_D | 120 | mW |
| | | | 3.8 | mW/°C |
| Output | Power dissipation Derating factor (above Ta = 80°C) | P_C | 150 | mW |
| | | | 6.5 | mW/°C |
| | Collector-Emitter voltage | V_{CEO} | 55 | V |
| | Collector-Base voltage | V_{CBO} | 55 | V |
| | Emitter-Collector voltage | V_{ECO} | 7 | V |
| | Emitter-Base voltage | V_{EBO} | 7 | V |
| | Total power dissipation | P_{TOT} | 200 | mW |
| | Isolation voltage | V_{ISO} | 5000 | Vrms |
| | Operating temperature | T_{OPR} | -55~+100 | °C |
| | Storage temperature | T_{STG} | -55~+125 | °C |
| | Soldering temperature *2 | T_{SOL} | 260 | °C |

Notes:

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 & 3 are shorted together, and pins 4, 5 & 6 are shorted together.

*2 For 10 seconds

Electro-Optical Characteristics (Ta=25°C unless specified otherwise)

Input

| Parameter | Symbol | Min. | Typ.* | Max. | Unit | Condition |
|-------------------|----------|------|-------|------|---------------|--|
| Forward Voltage | V_F | - | 1.2 | 1.5 | V | $I_F = 10\text{mA}$ $I_F = 50\text{mA}$ for H11B3 |
| Reverse Current | I_R | - | - | 10 | μA | $V_R = 6\text{V}$ |
| Input capacitance | C_{in} | - | 50 | - | pF | $V = 0, f = 1\text{MHz}$ |

Output

| Parameter | Symbol | Min. | Typ.* | Max. | Unit | Condition |
|-------------------------------------|------------|------|-------|------|------|-----------------------|
| Collector-Emitter dark current | I_{CEO} | - | - | 100 | nA | $V_{CE} = 10\text{V}$ |
| Collector-Emitter breakdown voltage | BV_{CEO} | 55 | - | - | V | $I_c = 1\text{mA}$ |
| Emitter-Collector breakdown voltage | BV_{CBO} | 55 | - | - | V | $I_C = 0.1\text{mA}$ |
| Emitter-Collector breakdown voltage | BV_{ECO} | 7 | - | - | V | $I_E = 0.1\text{mA}$ |

Transfer Characteristics (Ta=25°C unless specified otherwise)

| Parameter | Symbol | Min | Typ. | Max. | Unit | Condition | |
|------------------------|--------------|-----|------|------|------|--|---|
| Current transfer ratio | 4N32 4N33 | 500 | - | - | | $I_F = 10\text{mA}, V_{CE} = 10\text{V}$ | |
| | 4N29 4N30 | 100 | - | - | | | |
| | 4N31 | 50 | - | - | | | |
| | H11B1 | CTR | 500 | - | - | | % |
| | H11B2 | | 200 | - | - | | $I_F = 1\text{mA}, V_{CE} = 5\text{V}$ |
| | H11B3 | | 100 | - | - | | |
| | H11B255 | | 100 | - | - | | $I_F = 10\text{mA}, V_{CE} = 5\text{V}$ |
| | TIL113 | | 300 | - | - | | $I_F = 10\text{mA}, V_{CE} = 1\text{V}$ |

Transfer Characteristics ($T_a=25^\circ\text{C}$ unless specified otherwise)

| Parameter | Symbol | Min | Typ. | Max. | Unit | Condition |
|--------------------------------------|--|-----------|------|-----------|---------------|--|
| Collector-emitter saturation voltage | 4N29 4N30 4N32 4N33 | - | - | 1.0 | | $I_F = 8\text{mA}, I_C = 2\text{mA}$ |
| | 4N31 TIL113 | - | - | 1.2 | V | $I_F = 8\text{mA}, I_C = 2\text{mA}$ |
| | H11B1 H11B2 H11B3 | - | - | 1.0 | | $I_F = 1\text{mA}, I_C = 1\text{mA}$ |
| | H11B255 | - | - | 1.0 | | $I_F = 50\text{mA}, I_C = 50\text{mA}$ |
| Isolation resistance | R_{IO} | 10^{11} | - | - | Ω | $V_{IO} = 500\text{Vdc}$ |
| Input-output Capacitance | C_{IO} | - | 0.8 | - | pF | $V_{IO} = 0, f = 1\text{MHz}$ |
| Turn-on time | H11B1 H11B2 H11B3 H11B255 | - | 25 | - | | $V_{CC} = 10\text{V}, I_F = 10\text{mA}, R_L = 100\Omega$ |
| | 4N29 4N30 4N31 4N32 4N33 TIL113 | - | - | 5 | μs | $V_{CC} = 10\text{V}, I_C = 50\text{mA}, I_F = 200\text{mA}$ |
| Turn-off time | H11B1 H11B2 H11B3 H11B255 | - | 18 | - | | $V_{CC} = 10\text{V}, I_F = 10\text{mA}, R_L = 100\Omega$ |
| | 4N32 4N33 TIL113 4N29 4N30 4N31 | - | - | 100 40 | μs | $V_{CC} = 10\text{V}, I_C = 50\text{mA}, I_F = 200\text{mA}$ |

* Typical values at $T_a = 25^\circ\text{C}$

Typical Electro-Optical Characteristics Curves

Figure 1. Forward Current vs Forward Voltage




Figure 2. Current Transfer Ratio vs. Ambient Temperature




Figure 3. Normalized Current Transfer Ratio vs Forward Current




Figure 4. Collector Dark Current vs Ambient Temperature




Figure 5. Turn-on Time vs Forward Current





Figure 6. Turn-off Time vs Forward Current






Figure 7. Switching Time Test Circuit & Waveforms

EVERLIGHT

Order Information

Part Number

4NXXY(Z)-V
or **H11BXY(Z)-V**
or **TIL113Y(Z)-V**




Note

XX = Part No. for 4NXX series (29, 30, 31, 32 or 33)
X = Part No. for H11BX series (1, 2, 3 or 255)
Y = Lead form option (S, S1, M or none)
Z = Tape and reel option (TA, TB or none).
V = VDE safety (optional)




| Option | Description | Packing quantity |
|---------|---|---------------------|
| None | Standard DIP-6 | 65 units per tube |
| M | Wide lead bend (0.4 inch spacing) | 65 units per tube |
| S (TA) | Surface mount lead form + TA tape & reel option | 1000 units per reel |
| S (TB) | Surface mount lead form + TB tape & reel option | 1000 units per reel |
| S1 (TA) | Surface mount lead form (low profile) + TA tape & reel option | 1000 units per reel |
| S1 (TB) | Surface mount lead form (low profile) + TB tape & reel option | 1000 units per reel |

Package Dimension (Dimensions in mm)


Standard DIP Type




Option M Type




Option S Type



Option S1 Type




Recommended pad layout for surface mount leadform



Notes

Suggested pad dimension is just for reference only.
 Please modify the pad dimension based on individual need.

Device Marking




Notes


- EL denotes Everlight
- 4N33
- TIL113
- H11B1 denotes Part Number
- Y denotes 1 digit Year code
- WW denotes 2 digit Week code
- V denotes VDE safety (optional)

Tape & Reel Packing Specifications


Option TA




Direction of feed from reel




Option TB



Direction of feed from reel



Tape dimensions




| | | | | | | |
|---------------|-----------|-----------|-----------|------------|----------|----------|
| Dimension No. | A | B | Do | D1 | E | F |
| Dimension(mm) | 10.8±0.1 | 7.55±0.1 | 1.5±0.1 | 1.5+0.1/-0 | 1.75±0.1 | 7.5±0.1 |
| Dimension No. | Po | P1 | P2 | t | W | K |
| Dimension(mm) | 4.0±0.15 | 12±0.1 | 2.0±0.1 | 0.35±0.03 | 16.0±0.2 | 4.5±0.1 |

Precautions for Use

1. Soldering Condition

1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile



Note:

Reference: IPC/JEDEC J-STD-020D

Preheat

| | |
|--|-----------------|
| Temperature min (T_{smin}) | 150 °C |
| Temperature max (T_{smax}) | 200°C |
| Time (T_{smin} to T_{smax}) (t_s) | 60-120 seconds |
| Average ramp-up rate (T_{smax} to T_p) | 3 °C/second max |

Other

| | |
|--|------------------|
| Liquidus Temperature (T_L) | 217 °C |
| Time above Liquidus Temperature (t_L) | 60-100 sec |
| Peak Temperature (T_P) | 260°C |
| Time within 5 °C of Actual Peak Temperature: $T_P - 5^\circ\text{C}$ | 30 s |
| Ramp- Down Rate from Peak Temperature | 6°C /second max. |
| Time 25°C to peak temperature | 8 minutes max. |
| Reflow times | 3 times |

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Everlight \(亿光\)](#)