



Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
20V	18m Ω @4.5V	5A
	22m Ω @2.5V	


Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge
- Low Gate Resistance


Application

- Power Switching Application

MARKING:



8205A = Device Code



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	20	V
Gate - Source Voltage	V_{GS}	± 10	V
Continuous Drain Current ^{1,5}	I_D	5	A
Pulsed Drain Current ²	I_{DM}	20	A
Power Dissipation ^{4,5}	P_D	0.65	W
Thermal Resistance from Junction to Ambient ⁵	$R_{\theta JA}$	190	$^\circ\text{C}/\text{W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 18V, V _{GS} = 0V			1	μA
Gate - body Leakage Current	I _{GSS}	V _{GS} = ±10V, V _{DS} = 0V			±100	nA
On Characteristics³						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	0.4	0.7	1	V
Drain-source On-resistance	R _{DS(on)}	V _{GS} = 4.5V, I _D = 3A	15	18	26	mΩ
		V _{GS} = 2.5V, I _D = 3A	18	22	35	
Forward Transconductance	g _{FS}	V _{DS} = 5V, I _D = 4.5A		10.5		S
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = 10V, V _{GS} = 0V, f = 1MHz		354		pF
Output Capacitance	C _{oss}			66		
Reverse Transfer Capacitance	C _{rss}			57		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		1.5		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = 10V, V _{GS} = 4.5V, I _D = 5A		10		nC
Gate-source Charge	Q _{gs}			2.8		
Gate-drain Charge	Q _{gd}			3.0		
Turn-on Delay Time	t _{d(on)}	V _{DD} = 10V, V _{GS} = 4.5V, R _L = 2Ω, R _G = 3Ω		15		ns
Turn-on Rise Time	t _r			7		
Turn-off Delay Time	t _{d(off)}			35		
Turn-off Fall Time	t _f			18		
Source - Drain Diode Characteristics						
Diode Forward Voltage ³	V _{SD}	V _{GS} = 0V, I _S = 1.25A			1.2	V


Notes :

- 1.The maximum current rating is limited by package.
- 2.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.
- 3.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.
- 4.The power dissipation P_D is limited by T_{J(MAX)} = 150°C.
- 5.Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C.

Typical Characteristics



SOT-23-6L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0	0.150	0.000	0.006
A2	1.050	1.250	0.041	0.049
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	2.650	2.950	0.104	0.116
E1	1.500	1.700	0.059	0.067
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
L1	0.600REF		0.024REF	
θ	0°	8°	0°	8°

单击下面可查看定价，库存，交付和生命周期等信息

[>>GP\(格瑞宝\)](#)