

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
30V	94mΩ@4.5V	1.4A
	137mΩ@2.5V	


Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge


Application

- Load Switch
- DC/DC Converter


MARKING:



SOT-23



Schematic diagram



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	30	V
Gate - Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ^{1,5}	I_D	1.4	A
Pulsed Drain Current ²	I_{DM}	6.0	A
Power Dissipation ^{4,5}	P_D	1.25	W
Thermal Resistance from Junction to Ambient ⁵	$R_{\theta JA}$	100	$^\circ\text{C/W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V , I _D = 250μA	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 0V			1	μA
Gate - Body Leakage Current	I _{GSS}	V _{GS} = ±12V, V _{DS} = 0V			±100	nA
On Characteristics ³						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	0.5	1.0	1.5	V
Drain-source On-resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 3A		86	112	mΩ
		V _{GS} = 4.5V, I _D = 3A		94	122	
		V _{GS} = 2.5V, I _D = 3A		137	180	
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = 15V, V _{GS} = 0V, f = 1MHz		125		pF
Output Capacitance	C _{oss}			19		
Reverse Transfer Capacitance	C _{rss}			14		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		9.7		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = 15V, V _{GS} = 4.5V, I _D = 4A		2.1		nC
Gate-source Charge	Q _{gs}			0.6		
Gate-drain Charge	Q _{gd}			0.7		
Turn-on Delay Time	t _{d(on)}	V _{DD} = 15V, V _{GS} = 10V, R _L = 15Ω, R _G = 3Ω		3.5		ns
Turn-on Rise Time	t _r			1.5		
Turn-off Delay Time	t _{d(off)}			12		
Turn-off Fall Time	t _f			2		
Source - Drain Diode Characteristics						
Diode Forward Voltage ³	V _{SD}	V _{GS} = 0V, I _S = 1A			1.2	V

Notes :

- 1.The maximum current rating is limited by package.
- 2.Pulse Test : Pulse Width $\leq 10\mu s$, duty cycle $\leq 1\%$.
- 3.Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 4.The power dissipation P_D is limited by $T_{J(MAX)} = 150^\circ\text{C}$.
- 5.Device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics



SOT-23 Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0	0.100	0	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.150	1.500	0.045	0.059
E1	2.250	2.650	0.089	0.104
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

单击下面可查看定价，库存，交付和生命周期等信息

[>>GP\(格瑞宝\)](#)