


Product Summary


The GESDB5V0D51S is designed to protect voltage sensitive electronic components from ESD and other transients. Excellent clamping capability, low leakage, low capacitance, and fast response time provide best in class protection on designs that are exposed to ESD.

The combination of small size, low capacitance, and high level of ESD protection makes them a flexible solution for applications such as HDMI, Display Port TM, and MDDI interfaces. It is designed to replace multiplayer varistors (MLV) in consumer

SOD-523



Schematic diagram



Feature

- Low reverse stand-off voltage: 5V Max.
- Low capacitance: 3pF(Typ.)
- Low leakage current
- Fast response time
- ESD Rating of Class 3(>16kV) Per Human Body Model
- IEC 61000-4-2 Level 4 ESD protection

Application

- Computers and peripherals
- Portable electronics
- High speed data lines
- Audio and video equipment
- Cellular handsets and accessories
- Other electronic equipment communication systems

Marking:



Front Side

HD=Device Code

Absolute Maximum Ratings ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
IEC 61000-4-2 ESD Voltage	$V_{ESD}^{1)}$	± 15	kV
IEC 61000-4-2 ESD Voltage		± 15	
ESD Voltage		± 16	
ESD Voltage		± 0.4	
Peak Pulse Power	$P_{PP}^{2)}$	45	W
Peak Pulse Current	$I_{PP}^{2)}$	3	A
Lead Solder Temperature – Maximum (10 Second Duration)	T_L	260	$^\circ\text{C}$
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55~ +150	$^\circ\text{C}$

1) Device stressed with ten non-repetitive ESD pulses.



2) Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5.

ESD standards compliance
IEC61000-4-2 Standard

Contact Discharge		Air Discharge	
Level	Test Voltage kV	Level	Test Voltage kV
1	2	1	2
2	4	2	4
3	6	3	8
4	8	4	15


JESD22-A114-B Standard

ESD Class	Human Body Discharge V
0	0~249
1A	250~499
1B	500~999
1C	1000~1999
2	2000~3999
3A	4000~7999
3B	8000~15999

Contact discharge current waveform per IEC61000-4-2

8/20 μs waveform per IEC61000-4-5


Electrical Parameter






Symbol	Parameter
V _C	Clamping Voltage @ I _{PP}
I _{PP}	Peak Pulse Current
V _{BR}	Breakdown Voltage @ I _{BR}
I _{BR}	Test Current
I _R	Reverse Leakage Current @ V _{RWM}
V _{RWM}	Reverse Standoff Voltage




Electrical Characteristics ($T_a=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse standoff voltage	V _{RWM}				5	V
Reverse leakage current	I _R	V _{RWM} =5V			1	µA
Breakdown voltage	V _{BR} ¹⁾	I _T =1mA	5.6		9	V
Clamping voltage	V _{C1}	I _{PP} =1A		9	11	V
	V _{C2}	I _{PP} =2A		12	15	V
Junction capacitance	C _J	V _R =0V, f=1MHz		3		pF

1) V_{BR} is measured with a pulse test current IT at an ambient temperature of 25°C

Typical Characteristics


SOD-523 Package Outline Dimension


	Dimensions In Millimeters	
	Min.	Max.
A	1.10	1.30
B	0.70	0.90
C	1.50	1.70
D	0.50	0.70
D1	0.51	0.77
E	0.25	0.35
F	0.20REF	
H	0.07	0.20



电子元器件线上授权代理开拓者
原厂授权 · 正品现货 · 一件即发

单击下面可查看定价，库存，交付和生命周期等信息

[>>GP\(格瑞宝\)](#)