


1) Nur für Buchanan Crimpwerkzeug Einstell ϕ 1,0
 only for Buchanan crimping tool adjusting $\phi 0,1$



Bestell-Nummer versilbert <i>silver plated</i>	/ Part No. vergoldet <i>gold plated</i>	D	Leiterquerschnitt <i>wire gauge</i>		Abisolierlänge der Litze <i>stripping length</i>
			mm ²	AWG	
09 15 000 6204	09 15 000 6224	0,90	0,14-0,37	26-22	8
09 15 000 6203	09 15 000 6223	1,10	0,5	20	
09 15 000 6205	09 15 000 6225	1,30	0,75	18	
09 15 000 6202	09 15 000 6222	1,45	1	18	
09 15 000 6201	09 15 000 6221	1,75	1,5	16	6
09 15 000 6206	09 15 000 6226	2,25	2,5	14	
09 15 000 6207	09 15 000 6227	0,90	0,14-0,37	26-22	8

All Dimensions in mm Original Size DIN A 4	Techn. Character.			Nicht tolerierte Maße/ Free size tolerances	
		Dat.	Name	Maßstab/ Scale 2:1	
		Detail.	16.06.10 Rull		
		Insp.	Sch		
	Stand.				
	HARTING Electric GmbH & Co. KG D-32339 Espelkamp			Han D / Buchsenkontakt Crimpkontakt gedreht 10A crimpcontact twisted 10A	
A	Name			TB 09 15 000 62..	
				Sub. TB 09 15 000 62.. v. 22.03.99	

单击下面可查看定价，库存，交付和生命周期等信息

[>>HARTING](#)