

HSX111SK SERIES

SEAM SEALING PACKAGE

RoHS Compliant
 Pb Free
 AEC Qualified




STANDARD SPECIFICATION


Items	Parameter	
Frequency Range	24~30MHz	31~52MHz
Mode	Fundamental	
Frequency Tolerance (at.25 °C)	±10ppm	
Load Capacitance	7pF Min.	
Drive Level	10μW (300μW Max.)	10μW (200μW Max.)
Equivalent Series Resistance	100Ω Max.	50Ω Max.
Storage Temp. Range	-55 ~ +125 °C	

DIMENSION

Unit:mm




Bottom View




Pin Connections	
#1	Crysta
#2	GND/Lid
#3	Crystal
#4	NC

Internal Connection (Top View)



Recommended Land Pattern Tolerance: ±0.1



FREQUENCY STABILITY OVER OPERATING TEMPERATURE RANGE

Operating Temperature	Stability
-40 ~ +85 °C	±15 ppm
-40 ~ +105 °C	±20 ppm
-40 ~ +125 °C	±40 ppm

*For other specification, please contact us.

Packing Unit : 3,000pcs/Reel.

Actual Size

单击下面可查看定价，库存，交付和生命周期等信息

[>>HELE\(加高\)](#)