


## FEATURES


- Output current in excess of 1.5A
- Internal short current circuit limiting
- Internal thermal overload protection
- Output voltage offered of 4% tolerance




## ORDERING INFORMATION

| DEVICE       | Package Type | MARKING | Packing | Packing Qty  |
|--------------|--------------|---------|---------|--------------|
| LM7905CT     | TO-220-3     | LM7905C | TUBE    | 1000pcs/box  |
| LM7906CT     | TO-220-3     | LM7906C | TUBE    | 1000pcs/box  |
| LM7908CT     | TO-220-3     | LM7908C | TUBE    | 1000pcs/box  |
| LM7909CT     | TO-220-3     | LM7909C | TUBE    | 1000pcs/box  |
| LM7912CT     | TO-220-3     | LM7912C | TUBE    | 1000pcs/box  |
| LM7915CT     | TO-220-3     | LM7915C | TUBE    | 1000pcs/box  |
| LM7918CT     | TO-220-3     | LM7918C | TUBE    | 1000pcs/box  |
| LM7924CT     | TO-220-3     | LM7924C | TUBE    | 1000pcs/box  |
| LM7905CS2/TR | TO-263-2     | LM7905C | REEL    | 500 pcs/reel |
| LM7906CS2/TR | TO-263-2     | LM7906C | REEL    | 500 pcs/reel |
| LM7908CS2/TR | TO-263-2     | LM7908C | REEL    | 500 pcs/reel |
| LM7909CS2/TR | TO-263-2     | LM7909C | REEL    | 500 pcs/reel |
| LM7912CS2/TR | TO-263-2     | LM7912C | REEL    | 500 pcs/reel |
| LM7915CS2/TR | TO-263-2     | LM7915C | REEL    | 500 pcs/reel |
| LM7918CS2/TR | TO-263-2     | LM7918C | REEL    | 500 pcs/reel |
| LM7924CS2/TR | TO-263-2     | LM7924C | REEL    | 500 pcs/reel |
| LM7905CS/TR  | TO-263-3     | LM7905C | REEL    | 500 pcs/reel |
| LM7906CS/TR  | TO-263-3     | LM7906C | REEL    | 500 pcs/reel |
| LM7908CS/TR  | TO-263-3     | LM7908C | REEL    | 500 pcs/reel |
| LM7909CS/TR  | TO-263-3     | LM7909C | REEL    | 500 pcs/reel |
| LM7912CS/TR  | TO-263-3     | LM7912C | REEL    | 500 pcs/reel |
| LM7915CS/TR  | TO-263-3     | LM7915C | REEL    | 500 pcs/reel |
| LM7918CS/TR  | TO-263-3     | LM7918C | REEL    | 500 pcs/reel |
| LM7924CS/TR  | TO-263-3     | LM7924C | REEL    | 500 pcs/reel |


## PIN CONFIGURATION



TO-220-3



TO-263-3



TO-263-2

## ABSOLUTE MAXIMUM RATINGS

| Condition                                       | VALUE    | UNIT             |
|---|----------|------------------|
| Maximum input voltage at $T_J=25^\circ\text{C}$ | -35      | V                |
| Maximum operating junction temperature          | +125     | $^\circ\text{C}$ |
| Operating Temperature Range                     | 0 ~ +125 | $^\circ\text{C}$ |
| Lead Temperature (TL) (Soldering, 10 seconds)   | +245     | $^\circ\text{C}$ |

**Note:** Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but specific performance is not ensured.

## ELECTRICAL CHARACTERISTICS LM7905C

( $V_{IN} = -10\text{V}$ ,  $I_O = 500\text{mA}$ ,  $C_{IN} = 2.2\mu\text{F}$ ,  $C_O = 1.0\mu\text{F}$ ,  $T_J = 25^\circ\text{C}$ , unless otherwise noted)

| CHARACTERISTIC           | SYMBOL       | TEST CONDITION   | NORMS |                            | UNIT |
|--------------------------|--------------|--|-------|----------------------------|------|
|                          |              |  | Min   | Max                        |      |
| Output Voltage           | $V_O$        | $-7.0\text{V} \geq V_{IN} \geq -20\text{V}$<br>$5.0\text{mA} \leq I_O \leq 1.0\text{A}$  | -4.8  | -5.2                       | V    |
| Line Regulation          | $\Delta U_V$ | $I_O = 100\text{mA}$ , $-7.0\text{V} \geq V_{IN} \geq -25\text{V}$<br>$I_O = 100\text{mA}$ , $-8.0\text{V} \geq V_{IN} \geq -12\text{V}$<br>$I_O = 500\text{mA}$ , $-7.0\text{V} \geq V_{IN} \geq -25\text{V}$<br>$I_O = 500\text{mA}$ , $-8.0\text{V} \geq V_{IN} \geq -12\text{V}$ |       | 47.5<br>23.5<br>95<br>47.5 | mV   |
| Load Regulation          | $\Delta U_I$ | $5.0\text{mA} \leq I_O \leq 1.5\text{A}$<br>$250\text{mA} \leq I_O \leq 750\text{mA}$  |       | 95<br>47.5                 | mV   |
| Quiescent Current        | $I_B$        |  |       | 7.8                        | mA   |
| Quiescent Current Change | $\Delta I_B$ | $-7.0\text{V} \geq V_{IN} \geq -25\text{V}$<br>$5.0\text{mA} \leq I_O \leq 1.5\text{A}$  |       | 1.25<br>0.48               | mA   |

**ELECTRICAL CHARACTERISTICS LM7906C**

 (V<sub>IN</sub> = -11V, I<sub>o</sub> = 500mA, C<sub>IN</sub> = 2.2μF, C<sub>o</sub> = 1.0μF, T<sub>J</sub> = 25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS |                         | UNIT |
|--------------------------|-----------------|--|-------|-------------------------|------|
|                          |                 |  | Min   | Max                     |      |
| Output Voltage           | V <sub>o</sub>  | -8.0V ≥ V <sub>IN</sub> ≥ -21V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.0 A   | -5.76 | -6.24                   | V    |
| Line Regulation          | ΔU <sub>v</sub> | I <sub>o</sub> = 100mA, -8.0V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>o</sub> = 100mA, -9.0V ≥ V <sub>IN</sub> ≥ -13V<br>I <sub>o</sub> = 500mA, -8.0V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>o</sub> = 500mA, -9.0V ≥ V <sub>IN</sub> ≥ -13V |       | 57<br>28.5<br>114<br>57 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>o</sub> ≤ 1.5 A<br>250mA ≤ I <sub>o</sub> ≤ 750mA   |       | 114<br>57               | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |       | 7.8                     | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -8.0V ≥ V <sub>IN</sub> ≥ -25V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.5 A   |       | 1.25<br>0.48            | mA   |

**ELECTRICAL CHARACTERISTICS LM7908C**

 (V<sub>IN</sub> = -14V, I<sub>o</sub> = 500mA, C<sub>IN</sub> = 2.2μF, C<sub>o</sub> = 1.0μF, T<sub>J</sub> = 25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS |                       | UNIT |
|--------------------------|-----------------|--|-------|-----------------------|------|
|                          |                 |  | Min   | Max                   |      |
| Output Voltage           | V <sub>o</sub>  | -10.5V ≥ V <sub>IN</sub> ≥ -23V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.0 A  | -7.68 | -8.32                 | V    |
| Line Regulation          | ΔU <sub>v</sub> | I <sub>o</sub> = 100mA, -10.5V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>o</sub> = 100mA, -11V ≥ V <sub>IN</sub> ≥ -17V<br>I <sub>o</sub> = 500mA, -10.5V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>o</sub> = 500mA, -11V ≥ V <sub>IN</sub> ≥ -17V |       | 76<br>38<br>152<br>76 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>o</sub> ≤ 1.5 A<br>250mA ≤ I <sub>o</sub> ≤ 750mA   |       | 152<br>76             | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |       | 7.8                   | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -10.5V ≥ V <sub>IN</sub> ≥ -25V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.5 A  |       | 0.98<br>0.48          | mA   |

**ELECTRICAL CHARACTERISTICS LM7909C**

 (V<sub>IN</sub> = -16V, I<sub>O</sub> = 500mA, C<sub>IN</sub> = 2.2μF, C<sub>O</sub> = 1.0μF, T<sub>J</sub> = 25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS |                       | UNIT |
|--------------------------|-----------------|--|-------|-----------------------|------|
|                          |                 |  | Min   | Max                   |      |
| Output Voltage           | V <sub>O</sub>  | -10.5V ≥ V <sub>IN</sub> ≥ -25V<br>5.0mA ≤ I <sub>O</sub> ≤ 1.0 A  | -8.60 | -9.40                 | V    |
| Line Regulation          | ΔU <sub>V</sub> | I <sub>O</sub> = 100mA, -11.8V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>O</sub> = 100mA, -12V ≥ V <sub>IN</sub> ≥ -20V<br>I <sub>O</sub> = 500mA, -11.8V ≥ V <sub>IN</sub> ≥ -25V<br>I <sub>O</sub> = 500mA, -12V ≥ V <sub>IN</sub> ≥ -20V |       | 86<br>43<br>172<br>86 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>O</sub> ≤ 1.5 A<br>250mA ≤ I <sub>O</sub> ≤ 750mA   |       | 171<br>86             | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |       | 7.8                   | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -10.5V ≥ V <sub>IN</sub> ≥ -25V<br>5.0mA ≤ I <sub>O</sub> ≤ 1.5 A  |       | 1.02<br>0.48          | mA   |

**ELECTRICAL CHARACTERISTICS LM7912C**

 (V<sub>IN</sub> = -19V, I<sub>O</sub> = 500mA, C<sub>IN</sub> = 2.2μF, C<sub>O</sub> = 1.0μF, T<sub>J</sub> = 25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS  |                           | UNIT |
|--------------------------|-----------------|--|--------|---------------------------|------|
|                          |                 |  | Min    | Max                       |      |
| Output Voltage           | V <sub>O</sub>  | -14.5V ≥ V <sub>IN</sub> ≥ -21V<br>5.0mA ≤ I <sub>O</sub> ≤ 1.0 A  | -11.52 | -12.48                    | V    |
| Line Regulation          | ΔU <sub>V</sub> | I <sub>O</sub> = 100mA, -14.5V ≥ V <sub>IN</sub> ≥ -30V<br>I <sub>O</sub> = 100mA, -16V ≥ V <sub>IN</sub> ≥ -22V<br>I <sub>O</sub> = 500mA, -14.5V ≥ V <sub>IN</sub> ≥ -30V<br>I <sub>O</sub> = 500mA, -16V ≥ V <sub>IN</sub> ≥ -22V |        | 114<br>58.5<br>228<br>114 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>O</sub> ≤ 1.5 A<br>250mA ≤ I <sub>O</sub> ≤ 750mA   |        | 228<br>114                | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |        | 7.8                       | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -14.5V ≥ V <sub>IN</sub> ≥ -30V<br>5.0mA ≤ I <sub>O</sub> ≤ 1.5 A  |        | 1.25<br>0.48              | mA   |

**ELECTRICAL CHARACTERISTICS LM7915C**

 (V<sub>IN</sub>= -23V, I<sub>o</sub> = 500mA, C<sub>IN</sub>=2.2μF, C<sub>O</sub>=1.0μF, T<sub>J</sub>=25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS |                         | UNIT |
|--------------------------|-----------------|--|-------|-------------------------|------|
|                          |                 |  | Min   | Max                     |      |
| Output Voltage           | V <sub>o</sub>  | -17.5V ≥ V <sub>IN</sub> ≥ -30V<br>5.0mA ≥ I <sub>o</sub> ≥ 1.0 A  | -14.4 | -15.6                   | V    |
| Line Regulation          | ΔU <sub>v</sub> | I <sub>o</sub> = 100mA, -17.5V ≥ V <sub>IN</sub> ≥ -30V<br>I <sub>o</sub> = 100mA, -20V ≥ V <sub>IN</sub> ≥ -26V<br>I <sub>o</sub> = 500mA, -17.5V ≥ V <sub>IN</sub> ≥ -30V<br>I <sub>o</sub> = 500mA, -20V ≥ V <sub>IN</sub> ≥ -26V |       | 142<br>71<br>285<br>142 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>o</sub> ≤ 1.5 A<br>250mA ≤ I <sub>o</sub> ≤ 750mA   |       | 285<br>142              | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |       | 7.8                     | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -17.5V ≥ V <sub>IN</sub> ≥ -30V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.5 A  |       | 0.98<br>0.48            | mA   |

**ELECTRICAL CHARACTERISTICS LM7918C**


 (V<sub>IN</sub>= -27V, I<sub>o</sub> = 500mA, C<sub>IN</sub>=2.2μF, C<sub>O</sub>=1.0μF, T<sub>J</sub>=25°C, unless otherwise noted)

| CHARACTERISTIC           | SYMBOL          | TEST CONDITION   | NORMS  |                           | UNIT |
|--------------------------|-----------------|--|--------|---------------------------|------|
|                          |                 |  | Min    | Max                       |      |
| Output Voltage           | V <sub>o</sub>  | -21V ≥ V <sub>IN</sub> ≥ -33V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.0 A  | -17.28 | -18.72                    | V    |
| Line Regulation          | ΔU <sub>v</sub> | I <sub>o</sub> = 100mA, -21V ≥ V <sub>IN</sub> ≥ -33V<br>I <sub>o</sub> = 100mA, -24V ≥ V <sub>IN</sub> ≥ -30V<br>I <sub>o</sub> = 500mA, -21V ≥ V <sub>IN</sub> ≥ -33V<br>I <sub>o</sub> = 500mA, -24V ≥ V <sub>IN</sub> ≥ -30V |        | 171<br>85.5<br>342<br>171 | mV   |
| Load Regulation          | ΔU <sub>I</sub> | 5.0mA ≤ I <sub>o</sub> ≤ 1.5 A<br>250mA ≤ I <sub>o</sub> ≤ 750mA   |        | 342<br>171                | mV   |
| Quiescent Current        | I <sub>B</sub>  |  |        | 7.8                       | mA   |
| Quiescent Current Change | ΔI <sub>B</sub> | -21V ≥ V <sub>IN</sub> ≥ -33V<br>5.0mA ≤ I <sub>o</sub> ≤ 1.5 A  |        | 0.98<br>0.48              | mA   |


**ELECTRICAL CHARACTERISTICS LM7924C**

 ( $V_{IN} = -33V$ ,  $I_o = 500mA$ ,  $C_{IN} = 2.2\mu F$ ,  $C_o = 1.0\mu F$ ,  $T_J = 25^\circ C$ , unless otherwise noted)

| CHARACTERISTIC           | SYMBOL       | TEST CONDITION   | NORMS |                          | UNIT |
|--------------------------|--------------|--|-------|--------------------------|------|
|                          |              |  | Min   | Max                      |      |
| Output Voltage           | $V_o$        | $-27V \geq V_{IN} \geq -38V$<br>$5.0mA \leq I_o \leq 1.0 A$  | -23   | -25                      | V    |
| Line Regulation          | $\Delta U_v$ | $I_o = 100mA$ , $-27V \geq V_{IN} \geq -38V$<br>$I_o = 100mA$ , $-30V \geq V_{IN} \geq -36V$<br>$I_o = 500mA$ , $-27V \geq V_{IN} \geq -38V$<br>$I_o = 500mA$ , $-30V \geq V_{IN} \geq -36V$ |       | 228<br>114<br>446<br>228 | mV   |
| Load Regulation          | $\Delta U_l$ | $5.0mA \leq I_o \leq 1.5 A$<br>$250mA \leq I_o \leq 750mA$   |       | 446<br>228               | mV   |
| Quiescent Current        | $I_B$        |  |       | 7.8                      | mA   |
| Quiescent Current Change | $\Delta I_B$ | $-27V \geq V_{IN} \geq -33V$<br>$5.0mA \leq I_o \leq 1.5 A$  |       | 0.98<br>0.48             | mA   |

**PHYSICAL DIMENSIONS**
**TO-263-3**

**Dimensions In Millimeters(TO-263-3)**


| Symbol: | A    | A1   | B    | C    | D    | D1   | E     | F     | G    | a    | b       |
|---------|------|------|------|------|------|------|-------|-------|------|------|---------|
| Min:    | 4.45 | 1.22 | 10   | 1.89 | 13.7 | 8.38 | 0     | 8.332 | 7.70 | 0.71 | 2.54BSC |
| Max:    | 4.62 | 1.32 | 10.4 | 2.19 | 14.6 | 8.89 | 0.305 | 8.552 | 8.10 | 0.97 |         |

**TO-220-3**

**Dimensions In Millimeters(TO-220-3)**

| Symbol: | A    | A1   | B    | D    | D1    | D2   | F    | G     | a    | d    | b      | q       |
|---------|------|------|------|------|-------|------|------|-------|------|------|--------|---------|
| Min:    | 4.45 | 1.22 | 10   | 28.2 | 22.22 | 8.50 | 8.30 | 12.55 | 0.71 | 0.33 | 2.54BS | 3.80TYP |
| Max:    | 4.62 | 1.32 | 10.4 | 28.9 | 22.62 | 9.10 | 8.55 | 12.75 | 0.97 | 0.42 | C      |         |

**PHYSICAL DIMENSIONS**

TO-263-2



**Dimensions In Millimeters(TO-263-2)**

| Symbol: | A    | A1   | B    | C    | D    | D1   | E     | F    | G    | a    | e    | b       |
|---------|------|------|------|------|------|------|-------|------|------|------|------|---------|
| Min:    | 4.45 | 1.22 | 10   | 2.25 | 14.5 | 8.45 | 0     | 8.30 | 7.70 | 0.71 | 1.10 | 2.54BSC |
| Max:    | 4.62 | 1.32 | 10.4 | 2.85 | 15.4 | 9.10 | 0.305 | 8.55 | 8.10 | 0.97 | 1.70 |         |



## REVISION HISTORY

| DATE      | REVISION  | PAGE |
|-----------|---|------|
| 2018-1-5  | New   | 1-10 |
| 2023-9-13 | Update Lead Temperature、 Update Package Type、 Add annotation for Maximum Ratings. | 1、 2 |

**IMPORTANT STATEMENT:**

Huaguan Semiconductor reserves the right to change its products and services without notice. Before ordering, the customer shall obtain the latest relevant information and verify whether the information is up to date and complete. Huaguan Semiconductor does not assume any responsibility or obligation for the altered documents.

Customers are responsible for complying with safety standards and taking safety measures when using Huaguan Semiconductor products for system design and machine manufacturing. You will bear all the following responsibilities: Select the appropriate Huaguan Semiconductor products for your application; Design, validate and test your application; Ensure that your application meets the appropriate standards and any other safety, security or other requirements. To avoid the occurrence of potential risks that may lead to personal injury or property loss.

Huaguan Semiconductor products have not been approved for applications in life support, military, aerospace and other fields, and Huaguan Semiconductor will not bear the consequences caused by the application of products in these fields. All problems, responsibilities and losses arising from the user's use beyond the applicable area of the product shall be borne by the user and have nothing to do with Huaguan Semiconductor, and the user shall not claim any compensation liability against Huaguan Semiconductor by the terms of this Agreement.

The technical and reliability data (including data sheets), design resources (including reference designs), application or other design suggestions, network tools, safety information and other resources provided for the performance of semiconductor products produced by Huaguan Semiconductor are not guaranteed to be free from defects and no warranty, express or implied, is made. The use of testing and other quality control technologies is limited to the quality assurance scope of Huaguan Semiconductor. Not all parameters of each device need to be tested.

The documentation of Huaguan Semiconductor authorizes you to use these resources only for developing the application of the product described in this document. You have no right to use any other Huaguan Semiconductor intellectual property rights or any third party intellectual property rights. It is strictly forbidden to make other copies or displays of these resources. You should fully compensate Huaguan Semiconductor and its agents for any claims, damages, costs, losses and debts caused by the use of these resources. Huaguan Semiconductor accepts no liability for any loss or damage caused by infringement.

单击下面可查看定价，库存，交付和生命周期等信息

[>>HGSEMI\(华冠\)](#)