

QUADRUPLE DIFFERENTIAL COMPARATORS



DESCRIPTION

The LM339 consists of four independent voltage comparators. These were designed specifically to operate from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage. The outputs can be connected to other open-collector outputs to achieve wired-AND relationships.

FEATURES

- Wide supply voltage range
- Low supply current drain independent of supply voltage.
- Low input biasing current
- Low input offset current
- Low input offset voltage
- Input common-mode voltage range includes GND
- Differential input voltage range equal to the power supply voltage
- Low output saturation voltage
- Output voltage compatible with TTL, MOS and CMOS logic

PACKAGE INFORMATION



ELECTRICAL CHARACTERISTICS

 at specified free-air temperature, $V_{CC}=5V$ (unless otherwise noted)

| PARAMETER | TEST CONDITIONS* | | MIN | TYP | MAX | UNIT |
|---|--|---------------|-------------------|-----|------|---------|
| V_{IO} Input offset voltage | $V_{CC}=5V$ to $30V$ $V_{IC}=V_{ICRmin}$, $V_O=1.4V$ | $25^{\circ}C$ | | 2 | 5 | mV |
| | | Full range | | | 9 | |
| I_{IO} Input offset current | $V_O=1.4V$ | $25^{\circ}C$ | | 5 | 50 | nA |
| | | Full range | | | 150 | |
| I_{IB} Input bias current | $V_O=1.4V$ | $25^{\circ}C$ | | -25 | -250 | nA |
| | | Full range | | | -400 | |
| V_{ICR} Common-mode input voltage range** | | $25^{\circ}C$ | 0 to $V_{CC}-1.5$ | | | V |
| | | Full range | 0 to $V_{CC}-2$ | | | |
| A_{VD} Large-signal differential voltage amplification | $V_{CC}=15V$, $V_O=1.4V$ to $11.4V$, $R_L \geq 15k\Omega$ to V_{CC} | $25^{\circ}C$ | 50 | 200 | | V/mV |
| I_{OH} High-level output current | $V_{OH}=5V$, $V_{ID}=1V$ | $25^{\circ}C$ | | 0.1 | 50 | nA |
| | $V_{OH}=30V$, $V_{ID}=1V$ | Full range | | | 1 | μA |
| V_{OL} Low-level output voltage | $I_{OL}=4mA$, $V_{ID}=-1V$ | $25^{\circ}C$ | | 150 | 400 | mV |
| | | Full range | | | 700 | |
| I_{OL} Low-level output current | $V_{OL}=1.5V$, $V_{ID}=-1V$ | $25^{\circ}C$ | 6 | | | mA |
| I_{CC} Supply current | $R_L = \infty$ | $V_{CC}=5V$ | $25^{\circ}C$ | 0.8 | 2 | mA |
| | | $V_{CC}=30V$ | Full range | | 2.5 | |

* Full range (MIN to MAX), for the LM339 is $-40^{\circ}C$ to $125^{\circ}C$. All characteristics are measured with zero common-mode input voltage unless otherwise specified.

** The voltage at either input or common-mode should not be allowed to go negative by more than $0.3V$. The upper end of the common-mode voltage range is $V_{CC}-1.5V$, but either or both inputs can go to $30V$ without damage.

SWITCHING CHARACTERISTICS, $V_{CC}=5V$, $T_A=25^{\circ}C$


| PARAMETER | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|---------------|---|---------------------------------------|-----|-----|-----|---------|
| Response time | R_L connected to $5V$ through $5.1k\Omega$, $C_L=15pF$ * (See Note 1) | 100-mV input step with 5-mV overdrive | | 1.3 | | μs |
| | | TTL-level input step | | 0.3 | | |

* C_L includes probe and jig capacitance.

NOTE 1: The response time specified is the interval between the input step function and the instant, when the output crosses $1.4V$.

PACKAGE


SOP14



UNIT: mm

| DIM. | MIN | TYP | MAX | DIM. | MIN | TYP | MAX |
|------|-------|-------|-------|------|-------|-------|-------|
| A | 4.520 | 4.570 | 4.620 | a | 0.400 | 0.420 | 0.440 |
| A1 | 0.100 | - | 0.250 | b | 1.260 | 1.270 | 1.280 |
| B | 8.500 | 8.750 | 9.000 | Q | 0° | - | 8° |
| C | 5.800 | 6.100 | 6.250 | | | | |
| C1 | 3.800 | 3.900 | 4.000 | | | | |
| D | 0.400 | - | 0.950 | | | | |

DIP14



UNIT: mm

| DIM. | MIN | TYP | MAX | DIM. | MIN | TYP | MAX |
|------|--------|--------|--------|------|-------|-------|-------|
| A | 6.100 | 6.300 | 6.680 | a | 1.504 | 1.524 | 1.544 |
| B | 18.940 | 19.200 | 19.560 | c | 0.437 | 0.457 | 0.477 |
| D | 8.200 | 8.700 | 9.200 | d | 2.530 | 2.540 | 2.550 |
| D1 | 7.42 | 7.62 | 7.82 | L | 0.500 | - | 0.800 |
| E | 3.100 | 3.300 | 3.550 | L1 | 3.000 | 3.200 | 3.600 |

Important statement:

Huaguan Semiconductor Co,Ltd. reserves the right to change the products and services provided without notice. Customers should obtain the latest relevant information before ordering, and verify the timeliness and accuracy of this information.

Customers are responsible for complying with safety standards and taking safety measures when using our products for system design and machine manufacturing to avoid potential risks that may result in personal injury or property damage.

Our products are not licensed for applications in life support, military, aerospace, etc., so we do not bear the consequences of the application of these products in these fields.

Our documentation is only permitted to be copied without any tampering with the content, so we do not accept any responsibility or liability for the altered documents.

单击下面可查看定价，库存，交付和生命周期等信息

[>>HGSEMI\(华冠\)](#)