

→ Honeywell.com

→ Automation & Control Solutions

HOME

ABOUT US

PRODUCTS & INFORMATION

NEWS & EVENTS

SALES & SUPPORT

LOGIN

Honeywell Sensing and Control



Search



narrow your search

Products

- Controls Monitoring and Lighting (354)
- Machine Safety (1726)
- Sensors (7016)
- Switches (9736)

Technology

- Control and Instrumentation (1063)
- Electromechanical (9297)
- Microstructure (2298)
- Optical/Infrared (1077)
- Thick Film (1764)
- More...

192-103LEW-A01 Discrete Thermistors (Home: Products)



192 Series, Uni-Curve with bare leads and epoxy, 10,000 Ohm resistance, ±1,0 °C [1.8 °F] tolerance, 25/85 BETA = 3974

Actual product appearance may vary.

Sales & Service 2

Application Notes

Distributor Inventory



Need Help?





Overview

Availability Global Resistance 10,000 Ohm ±1,0 °C [1.8 °F] Tolerance

Specs

0 °C to 70 °C [32 °F to 158 °F] Accuracy

-60 °C to 150 °C [-76 °F to 302 °F] Operating Temperature

Documentation

Diameter 2,413 mm [0.095 in]

Termination Material 32 Gauge tinned copper, alloy 180

38,1 mm [1.50 in] Lead Length

Time Constant in Air 15.0 s **Dissipation Constant** 0,75 m/W°C Series Name 192

Terms & Conditions | Privacy Statement | Site Map

单击下面可查看定价,库存,交付和生命周期等信息

>>Honeywell(霍尼韦尔)