

FEATURES

- 2.8V to 5.5V Operating Range
- Adjustable Current Limit : 200mA to 2.25A(Typ.)
- Fold-back Short Circuit Protection
- 130uA Typical On-State Supply Current
- 5uA Maximum Standby Supply Current
- Independent Open-drain Fault Flag Pin
- Thermal Shutdown Protection
- Under Voltage Lockout(UVLO)
- Output Auto Discharge Function
- Reverse Current Protection
- TJ2242 : Active High version

APPLICATION

- USB Peripherals
- General Purpose Power Switching
- ACPI Power Distribution
- Notebook PCs
- PDAs
- Hot Plug-in Power Supplies

DESCRIPTION

The TJ2242 is single-channel High-Side MOSFET switch optimized for adjustable current limited power distribution requiring circuit protection. The TJ2242 series support the following USB requirements. The TJ2242 series supply up to 2.25A as required by USB downstream devices. Maximum continuous current can be different on the types of package and ambient temperature. Switch's low on-resistance meets USB voltage drop requirement. Flag output indicate fault condition to the local USB controller. Soft-start prevents the transient voltage drop on the upstream port that can occur when the switch is enabled in bus-powered applications. Under voltage lockout (UVLO) feature disables the output switches until a valid input voltage. Auto discharge function quickly lowers the V_{OUT} to the ground level when the TJ2242 turns off. Also the TJ2242 include thermal shutdown to prevent switch failure from high-current loads and reverse current protection circuit to prevent the reverse current from V_{OUT} pin to V_{IN} pin.

SOT-23-6L

**ORDERING INFORMATION**

Device	Package
TJ2242GSF6	SOT-23-6L

Please contact us for more information about this product.

单击下面可查看定价，库存，交付和生命周期等信息

[>>HTC\(泰进\)](#)