

Features:

- 650V Schottky Diode
- Zero Reverse Recovery Current
- High Frequency Operation
- Positive Temperature Coefficient
- Temperature independent

Switching



Benefits:

- Unipolar Rectifier
- Minimal switching loss
- Higher Efficiency
- Low cooling requirement

| Symbol | Value | Unit |
|-------------------------------------|-------|------|
| V_{RRM} | 650 | V |
| I_F ($T_C = 146^\circ\text{C}$) | 15 | A |
| Q_C | 34 | nC |

Applications:

- Switch Mode Power Supply
- Booster diodes in PFC, DC/DC
- AC/DC converters

Outline

TO-220-2L
Circuit

Maximum Ratings

| Symbol | Parameter | Value | Unit | Test Conditions |
|-------------|---|------------|------------------|--|
| V_R | DC Peak Reverse Voltage | 650 | V | $T_J = 25^\circ\text{C}$ |
| V_{RRM} | Repetitive Peak Reverse | 650 | V | $T_J = 25^\circ\text{C}$ |
| V_{RSM} | Surge Peak Reverse Voltage | 650 | V | $T_J = 25^\circ\text{C}$ |
| I_F | Continuous Forward Current | 42 | A | $T_C = 25^\circ\text{C}$ |
| | | 19 | | $T_C = 135^\circ\text{C}$ |
| | | 15 | | $T_C = 146^\circ\text{C}$ |
| I_{FRM} | Repetitive Peak Forward Surge Current | 91 | A | $T_C = 25^\circ\text{C}$, $T_p = 10\text{ms}$, Half Sine Wave |
| | | 81 | | $T_C = 110^\circ\text{C}$, $T_p = 10\text{ms}$, Half Sine Wave |
| I_{FSM} | Non-Repetitive Peak Forward Surge Current | 120 | A | $T_C = 25^\circ\text{C}$, $T_p = 10\text{ms}$, Half Sine Wave |
| | | 109 | | $T_C = 110^\circ\text{C}$, $T_p = 10\text{ms}$, Half Sine Wave |
| P_D | Power Dissipation | 150 | W | $T_C = 25^\circ\text{C}$ |
| | | 50 | | $T_C = 125^\circ\text{C}$ |
| $T_{J,max}$ | Operating Junction Temperature | 175 | $^\circ\text{C}$ | |
| T_{stg} | Storage Temperature Range | -55 to 175 | $^\circ\text{C}$ | |

Thermal characteristics

| Symbol | Parameter | Min. | Typ. | Max. | Unit |
|------------|--------------------|------|------|------|-----------------------------|
| R_{thJC} | Thermal resistance | | 1.0 | | $^{\circ}\text{C}/\text{W}$ |

Electrical Characteristics

| Symbol | Parameter | Value | | | Unit | Test Conditions |
|----------|-------------------------|-------|-----------------|------------|---------------|---|
| | | Min. | Typ. | Max. | | |
| V_{DC} | DC Blocking Voltage | 650 | | | V | $I_R = 100\mu\text{A}$, $T_J = 25^{\circ}\text{C}$ |
| V_F | Forward Voltage | | 1.45 1.8 | 1.7 2.1 | V | $I_F = 15\text{A}$, $T_J = 25^{\circ}\text{C}$ $I_F = 15\text{A}$, $T_J = 175^{\circ}\text{C}$ |
| I_R | Reverse Current | | 5 10 | 100 200 | μA | $V_R = 650\text{V}$, $T_J = 25^{\circ}\text{C}$ $V_R = 650\text{V}$, $T_J = 175^{\circ}\text{C}$ |
| Q_C | Total Capacitive Charge | | 34 | | nC | $I_F = 15\text{A}$, $dI/dt = 350\text{A}/\mu\text{s}$ $T_J = 25^{\circ}\text{C}$, $V_R = 400\text{V}$ |
| C | Total Capacitance | | 644 88 85 | | pF | $V_R = 1\text{V}$, $T_J = 25^{\circ}\text{C}$, $f = 1\text{ MHz}$ $V_R = 200\text{V}$, $T_J = 25^{\circ}\text{C}$, $f = 1\text{ MHz}$ $V_R = 400\text{V}$, $T_J = 25^{\circ}\text{C}$, $f = 1\text{ MHz}$ |

Typical Performance




Fig. 1 Forward Characteristics




Fig. 2 Reverse Characteristics

Typical Performance




Fig. 3 Current Derating




Fig. 4 Power Derating




Fig. 5 Capacitance vs. Reverse Voltage




Fig. 6 Recovery Charge vs. Reverse Voltage




Fig. 7 Capacitance stored Energy





Fig. 8 Transient Thermal Impedance

Package TO-220-2L (Unit: mm)



COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

| SYMBOL | MIN | NOM | MAX |
|--------|---------|-------|-------|
| A | 4.40 | 4.57 | 4.70 |
| A1 | 1.25 | - | 1.34 |
| A2 | 2.59 | 2.69 | 2.79 |
| b | 0.77 | - | 0.89 |
| b1 | 0.76 | 0.81 | 0.86 |
| b2 | 1.23 | - | 1.36 |
| b3 | 1.22 | 1.27 | 1.32 |
| b4 | 0.67REF | | |
| b5 | 0.64REF | | |
| c | 0.36 | - | 0.45 |
| c1 | 0.35 | 0.38 | 0.41 |
| c2 | 0.59REF | | |
| c3 | 0.56REF | | |
| D | 15.15 | 15.45 | 15.75 |
| D1 | 9.05 | 9.15 | 9.25 |
| D2 | 12.20 | - | 13.00 |
| E | 9.96 | 10.16 | 10.29 |
| E1 | 7.60 | - | 8.20 |
| e | 4.98 | 5.08 | 5.18 |
| H1 | 6.10 | 6.30 | 6.48 |
| L | 12.70 | - | 13.12 |
| L1 | 2.80 | - | 3.30 |
| L2 | 2.50REF | | |
| ØP | 3.80 | 3.84 | 3.88 |
| Q | 2.60 | - | 2.90 |
| θ 1 | 5° | 7° | 9° |
| θ 2 | 1° | 3° | 5° |

NOTES:
ALL DIMENSIONS REFER TO JEDEC STANDARD
TO-220 AB DO NOT INCLUDE MOLD FLASH
OR PROTRUSIONS.

This Product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, systems, or air-traffic control systems.

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, AZ Power Inc. disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

单击下面可查看定价，库存，交付和生命周期等信息

[>>HyCore\(海科\)](#)