

## 2<sup>nd</sup> Generation thinQ!<sup>TM</sup> SiC Schottky Diode


### Features

- Revolutionary semiconductor material - Silicon Carbide
- Switching behavior benchmark
- No reverse recovery/ No forward recovery
- No temperature influence on the switching behavior
- High surge current capability
- Pb-free lead plating; RoHs compliant
- Qualified according to JEDEC<sup>1)</sup> for target applications
- Breakdown voltage tested at 5mA<sup>2)</sup>

### Product Summary

|          |     |    |
|----------|-----|----|
| $V_{DC}$ | 600 | V  |
| $Q_c$    | 24  | nC |
| $I_F$    | 10  | A  |

D<sup>2</sup>PAK (PG-TO263-3-2)



### thinQ! 2G Diode designed for fast switching applications like:

- CCM PFC
- Motor Drives

| Type      | Package              | Marking | Pin 2 | Pin 3 |
|-----------|----------------------|---------|-------|-------|
| IDB10S60C | D2PAK (PG-TO263-3-2) | D10S60C | C     | A     |

### Maximum ratings, at $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified

| Parameter   | Symbol            | Conditions   | Value       | Unit             |
|---|-------------------|--|-------------|------------------|
| Continuous forward current                          | $I_F$             | $T_C < 135\text{ }^\circ\text{C}$  | 10          | A                |
| RMS forward current                                 | $I_{F,RMS}$       | $f=50\text{ Hz}$   | 15          |                  |
| Surge non-repetitive forward current, sine halfwave | $I_{F,SM}$        | $T_C=25\text{ }^\circ\text{C}$ , $t_p=10\text{ ms}$                            | 76          |                  |
| Repetitive peak forward current                     | $I_{F,RM}$        | $T_j=150\text{ }^\circ\text{C}$ ,<br>$T_C=100\text{ }^\circ\text{C}$ , $D=0.1$ | 32          |                  |
| Non-repetitive peak forward current                 | $I_{F,max}$       | $T_C=25\text{ }^\circ\text{C}$ , $t_p=10\text{ }\mu\text{s}$                   | 350         |                  |
| $i^2t$ value  | $\int i^2 dt$     | $T_C=25\text{ }^\circ\text{C}$ , $t_p=10\text{ ms}$                            | 29          | A <sup>2</sup> s |
| Repetitive peak reverse voltage                     | $V_{RRM}$         |  | 600         | V                |
| Diode ruggedness dv/dt                              | dv/dt             | $V_R=0\dots 480\text{V}$   | 50          | V/ns             |
| Power dissipation                                   | $P_{tot}$         | $T_C=25\text{ }^\circ\text{C}$   | 83          | W                |
| Operating and storage temperature                   | $T_j$ , $T_{stg}$ |  | -55 ... 175 | $^\circ\text{C}$ |

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

**Thermal characteristics**

|   |            |  |   |    |     |     |
|---|------------|--|---|----|-----|-----|
| Thermal resistance, junction - case             | $R_{thJC}$ |  | - | -  | 1.8 | K/W |
| Thermal resistance, junction - ambient          | $R_{thJA}$ | SMD version, device on PCB, minimal Footprint                            | - | -  | 62  |     |
|   |            | SMD version, device on PCB, 6 cm <sup>2</sup> cooling area <sup>3)</sup> | - | 35 | -   |     |
| Soldering temperature, reflowsoldering @ 10sec. | $T_{sold}$ | reflow MSL1  | - | -  | 260 | °C  |

**Electrical characteristics, at  $T_j=25\text{ °C}$ , unless otherwise specified**
**Static characteristics**

|                       |          |  |     |     |      |    |
|-----------------------|----------|--|-----|-----|------|----|
| DC blocking voltage   | $V_{DC}$ | $I_R=0.14\text{ mA}$                     | 600 | -   | -    | V  |
| Diode forward voltage | $V_F$    | $I_F=10\text{ A}$ , $T_j=25\text{ °C}$   | -   | 1.5 | 1.7  |    |
|                       |          | $I_F=10\text{ A}$ , $T_j=150\text{ °C}$  | -   | 1.7 | 2.1  |    |
| Reverse current       | $I_R$    | $V_R=600\text{ V}$ , $T_j=25\text{ °C}$  | -   | 1.4 | 140  | μA |
|                       |          | $V_R=600\text{ V}$ , $T_j=150\text{ °C}$ | -   | 5   | 1400 |    |

**AC characteristics**

|                              |       |  |   |     |     |    |
|------------------------------|-------|--|---|-----|-----|----|
| Total capacitive charge      | $Q_c$ | $V_R=400\text{ V}$ , $I_F \leq I_{F,max}$ ,<br>$di_F/dt=200\text{ A}/\mu\text{s}$ ,<br>$T_j=150\text{ °C}$ | - | 24  | -   | nC |
| Switching time <sup>4)</sup> | $t_c$ |  | - | -   | <10 | ns |
| Total capacitance            | $C$   | $V_R=1\text{ V}$ , $f=1\text{ MHz}$  | - | 480 | -   | pF |
|                              |       | $V_R=300\text{ V}$ , $f=1\text{ MHz}$  | - | 60  | -   |    |
|                              |       | $V_R=600\text{ V}$ , $f=1\text{ MHz}$  | - | 60  | -   |    |

<sup>1)</sup> J-STD20 and JESD22

<sup>2)</sup> All devices tested under avalanche conditions, for a time periode of 5ms, at 5mA.


<sup>3)</sup> Device on 40mm\*40mm\*1.5mm epox PCB FR4 with 6cm<sup>2</sup> (one layer, 70μm thick) copper area for drain connection. PCB is vertikal with out blown air.

<sup>4)</sup>  $t_c$  is the time constant for the capacitive displacement current waveform (independent from  $T_j$ ,  $I_{LOAD}$  and  $di/dt$ ), different from  $t_{rr}$ , which is dependent on  $T_j$ ,  $I_{LOAD}$ ,  $di/dt$ . No reverse recovery time constant  $t_{rr}$  due to absence of minority carrier injection.

<sup>5)</sup> Only capacative charge occuring, guaranteed by design.


**1 Power dissipation**

$P_{tot}=f(T_C)$



**2 Diode forward current**


$I_F=f(T_C); T_j \leq 175\text{ °C}$



**3 Typ. forward characteristic**


$I_F=f(V_F); t_p=400\text{ }\mu\text{s}$

parameter:  $T_j$




**4 Typ. forward characteristic in surge current mode**

$I_F=f(V_F); t_p=400\text{ }\mu\text{s};$  parameter:  $T_j$



**5 Typ. forward power dissipation vs. average forward current**


$P_{F(AV)} = f(I_F)$ ,  $T_C = 100\text{ }^\circ\text{C}$ , parameter:  $D = t_p/T$



**6 Typ. reverse current vs. reverse voltage**

$I_R = f(V_R)$


parameter:  $T_j$



**7 Transient thermal impedance**


$Z_{thJC} = f(t_p)$

parameter:  $D = t_p/T$




**8 Typ. capacitance vs. reverse voltage**

$C = f(V_R)$ ;  $T_C = 25\text{ }^\circ\text{C}$ ,  $f = 1\text{ MHz}$




9 Typ. C stored energy



$$E_C = f(V_R)$$



10 Typ. Capacitive charge vs. current slope

$$Q_C = f(di_F/dt)^5; T_j = 150 \text{ °C}; I_F \leq I_{F,max}$$



**PG-TO263-3-2 (D<sup>2</sup>PAK): Outline**


| DIM | MILLIMETERS |       | INCHES |       |
|-----|-------------|-------|--------|-------|
|     | MIN         | MAX   | MIN    | MAX   |
| A   | 4.30        | 4.57  | 0.169  | 0.180 |
| A1  | 0.00        | 0.25  | 0.000  | 0.010 |
| b   | 0.65        | 0.85  | 0.026  | 0.033 |
| b2  | 0.95        | 1.15  | 0.037  | 0.045 |
| c   | 0.33        | 0.65  | 0.013  | 0.026 |
| c2  | 1.17        | 1.40  | 0.046  | 0.055 |
| D   | 8.51        | 9.45  | 0.335  | 0.372 |
| D1  | 7.10        | 7.90  | 0.280  | 0.311 |
| E   | 9.80        | 10.31 | 0.386  | 0.406 |
| E1  | 6.50        | 8.60  | 0.256  | 0.339 |
| e   | 2.54        |       | 0.100  |       |
| e1  | 5.08        |       | 0.200  |       |
| N   | 2           |       | 2      |       |
| H   | 14.61       | 15.88 | 0.575  | 0.625 |
| L   | 2.29        | 3.00  | 0.090  | 0.118 |
| L1  | 0.70        | 1.60  | 0.028  | 0.063 |
| L2  | 1.00        | 1.78  | 0.039  | 0.070 |
| F1  | 16.05       | 16.25 | 0.632  | 0.640 |
| F2  | 9.30        | 9.50  | 0.366  | 0.374 |
| F3  | 4.50        | 4.70  | 0.177  | 0.185 |
| F4  | 10.70       | 10.90 | 0.421  | 0.429 |
| F5  | 3.65        | 3.85  | 0.144  | 0.152 |
| F6  | 1.25        | 1.45  | 0.049  | 0.057 |

|                                    |
|------------------------------------|
| <b>DOCUMENT NO.</b><br>Z8B00003324 |
| <b>SCALE</b><br>0<br>5 5<br>7.5mm  |
| <b>EUROPEAN PROJECTION</b><br>     |
| <b>ISSUE DATE</b><br>30-08-2007    |
| <b>REVISION</b><br>01              |

Dimensions in mm/inches

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2007 Infineon Technologies AG**  
**All Rights Reserved.**

#### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

#### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

#### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon\(英飞凌\)](#)