

**REPETITIVE AVALANCHE AND dv/dt RATED
 HEXFET[®] TRANSISTORS
 SURFACE MOUNT (LCC-18)**

**IRFE210
 JANTX2N6784U
 JANTXV2N6784U
 REF:MIL-PRF-19500/556
 200V, N-CHANNEL**

Product Summary

| Part Number | BVDSS | RDS(on) | ID |
|-------------|-------|---------|-------|
| IRFE210 | 200V | 1.5Ω | 2.25A |



The leadless chip carrier (LCC) package represents the logical next step in the continual evolution of surface mount technology. Designed to be a close replacement for the TO-39 package, the LCC will give designers the extra flexibility they need to increase circuit board density. International Rectifier has engineered the LCC package to meet the specific needs of the power market by increasing the size of the bottom source pad, thereby enhancing the thermal and electrical performance. The lid of the package is grounded to the source to reduce RF interference.

Features:

- Surface Mount
- Small Footprint
- Alternative to TO-39 Package
- Hermetically Sealed
- Dynamic dv/dt Rating
- Avalanche Energy Rating
- Simple Drive Requirements
- Light Weight
- ESD Rating: Class 1A per MIL-STD-750, Method 1020

Absolute Maximum Ratings

| | Parameter | | Units |
|----------------------------|---|----------------|-------|
| ID @ VGS = 10V, TC = 25°C | Continuous Drain Current | 2.25 | A |
| ID @ VGS = 10V, TC = 100°C | Continuous Drain Current | 1.5 | |
| IDM | Pulsed Drain Current \hat{A} | 9.0 | |
| PD @ TC = 25°C | Max. Power Dissipation | 15 | W |
| | Linear Derating Factor | 0.12 | W/°C |
| VGS | Gate-to-Source Voltage | ±20 | V |
| EAS | Single Pulse Avalanche Energy \hat{A} | 20 | mJ |
| IAR | Avalanche Current \hat{A} | 2.25 | A |
| EAR | Repetitive Avalanche Energy \hat{A} | 1.5 | mJ |
| dv/dt | Peak Diode Recovery dv/dt \hat{A} | 3.9 | V/ns |
| TJ | Operating Junction | -55 to 150 | °C |
| TSTG | Storage Temperature Range | | |
| | Pckg. Mounting Surface Temp. | 300 (for 5 S) | |
| | Weight | 0.42 (typical) | g |

For footnotes refer to the last page

Electrical Characteristics @ T_J = 25°C (Unless Otherwise Specified)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-------------------------------------|--|-----|------|-------|-------|---|
| BV _{DSS} | Drain-to-Source Breakdown Voltage | 200 | — | — | V | V _{GS} = 0V, I _D = 1.0mA |
| ΔBV _{DSS} /ΔT _J | Temperature Coefficient of Breakdown Voltage | — | 0.23 | — | V/°C | Reference to 25°C, I _D = 1.0mA |
| R _{DS(on)} | Static Drain-to-Source On-State Resistance | — | — | 1.5 | Ω | V _{GS} = 10V, I _D = 1.5A \bar{A} |
| | | — | — | 1.725 | | V _{GS} = 10V, I _D = 2.25A \bar{A} |
| V _{GS(th)} | Gate Threshold Voltage | 2.0 | — | 4.0 | V | V _{DS} = V _{GS} , I _D = 250μA |
| g _{fs} | Forward Transconductance | 1.4 | — | — | S | V _{DS} = 15V, I _{DS} = 1.5A \bar{A} |
| I _{DSS} | Zero Gate Voltage Drain Current | — | — | 25 | μA | V _{DS} = 160V, V _{GS} = 0V |
| | | — | — | 250 | | V _{DS} = 160V V _{GS} = 0V, T _J = 125°C |
| I _{GSS} | Gate-to-Source Leakage Forward | — | — | 100 | nA | V _{GS} = 20V |
| I _{GSS} | Gate-to-Source Leakage Reverse | — | — | -100 | | V _{GS} = -20V |
| Q _g | Total Gate Charge | — | — | 6.2 | nC | V _{GS} = 10V, I _D = 2.25A |
| Q _{gs} | Gate-to-Source Charge | — | — | 1.2 | | V _{DS} = 100V |
| Q _{gd} | Gate-to-Drain ('Miller') Charge | — | — | 5.0 | | |
| t _{d(on)} | Turn-On Delay Time | — | — | 15 | ns | V _{DD} = 100V, I _D = 2.25A, V _{GS} = 10V, R _G = 7.5Ω |
| t _r | Rise Time | — | — | 20 | | |
| t _{d(off)} | Turn-Off Delay Time | — | — | 30 | | |
| t _f | Fall Time | — | — | 20 | | |
| L _S + L _D | Total Inductance | — | 6.1 | — | nH | Measured from the center of drain pad to center of source pad |
| C _{iss} | Input Capacitance | — | 150 | — | pF | V _{GS} = 0V, V _{DS} = 25V f = 1.0MHz |
| C _{oss} | Output Capacitance | — | 57 | — | | |
| C _{rss} | Reverse Transfer Capacitance | — | 15 | — | | |

Source-Drain Diode Ratings and Characteristics

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-----------------|---|--|-----|------|-------|---|
| I _S | Continuous Source Current (Body Diode) | — | — | 2.25 | A | |
| I _{SM} | Pulse Source Current (Body Diode) \bar{A} | — | — | 9.0 | | |
| V _{SD} | Diode Forward Voltage | — | — | 1.5 | V | T _J = 25°C, I _S = 2.25A, V _{GS} = 0V \bar{A} |
| t _{rr} | Reverse Recovery Time | — | — | 350 | ns | T _J = 25°C, I _F = 2.25A, di/dt ≤ 100A/μs |
| Q _{RR} | Reverse Recovery Charge | — | — | 0.66 | μC | V _{DD} ≤ 50V \bar{A} |
| t _{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L _S + L _D . | | | | |

Thermal Resistance

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|----------------------|----------------------|-----|-----|-----|-------|------------------------------------|
| R _{thJC} | Junction to Case | — | — | 8.3 | °C/W | Soldered to a copper clad PC board |
| R _{thJ-PCB} | Junction to PC Board | — | — | 27 | | |

Note: Corresponding Spice and Saber models are available on International Rectifier Web site.

For footnotes refer to the last page







Fig 3. Typical Transfer Characteristics

Fig 4. Normalized On-Resistance Vs. Temperature




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Basic Gate Charge Waveform




Fig 12c. Maximum Avalanche Energy Vs. Drain Current





Fig 13b. Gate Charge Test Circuit

Footnotes:

- ⌘ Repetitive Rating; Pulse width limited by maximum junction temperature.
- ⌘ $V_{DD} = 50V$, starting $T_J = 25^\circ C$, Peak $I_L = 2.25A$,

- ⌘ $I_{SD} \leq 2.25A$, $di/dt \leq 70A/\mu s$, $V_{DD} \leq 200V$, $T_J \leq 150^\circ C$, Suggested $R_G = 7.5 \Omega$
- ⌘ Pulse width $\leq 300 \mu s$; Duty Cycle $\leq 2\%$

Case Outline and Dimensions — LCC-18



NOTES:

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M-1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon Technologies\(英飞凌\)](#)