

### Short circuit rugged 1200 V TRENCHSTOP™ IGBT 7 technology copacked with soft, fast recovery Emitter Controlled 7 diode

#### Features


- $V_{CE} = 1200\text{ V}$
- $I_C = 75\text{ A}$
- IGBT co-packed with full current, soft and low  $Q_{rr}$  diode
- Low saturation voltage  $V_{CEsat} = 2.0\text{ V}$  at  $T_{vj} = 175^\circ\text{C}$
- Optimized for hard switching topologies (2-L inverter, 3-L NPC T-type, ...)
- Short circuit ruggedness  $8\ \mu\text{s}$
- Wide range of  $dv/dt$  controllability
- Complete product spectrum and PSpice Models: <http://www.infineon.com/igbt/>

#### Potential applications

- Industrial drives
- Industrial power supplies
- Solar inverters


#### Product validation

- Qualified for industrial applications according to the relevant tests of JEDEC47/20/22



- Halogen-free
- Lead-free
- Green
- RoHS

#### Description



Type	Package	Marking
IKQ75N120CS7	PG-TO247-3-PLUS-NN3.7	K75MCS7

## Table of contents

	<b>Description</b> .....	1
	<b>Features</b> .....	1
	<b>Potential applications</b> .....	1
	<b>Product validation</b> .....	1
	<b>Table of contents</b> .....	2
<b>1</b>	<b>Package</b> .....	3
<b>2</b>	<b>IGBT</b> .....	3
<b>3</b>	<b>Diode</b> .....	5
<b>4</b>	<b>Characteristics diagrams</b> .....	7
<b>5</b>	<b>Package outlines</b> .....	14
<b>6</b>	<b>Testing conditions</b> .....	15
	<b>Revision history</b> .....	16
	<b>Disclaimer</b> .....	17

## 1 Package

**Table 1** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Internal emitter inductance measured 5 mm (0.197 in.) from case	$L_E$			13		nH
Storage temperature	$T_{stg}$		-55		150	°C
Soldering temperature	$T_{sold}$	wave soldering 1.6 mm (0.063 in.) from case for 10 s			260	°C
Thermal resistance, junction-ambient	$R_{th(j-a)}$				40	K/W
IGBT thermal resistance, junction-case	$R_{th(j-c)}$			0.17	0.24	K/W
Diode thermal resistance, junction-case	$R_{th(j-c)}$			0.31	0.42	K/W

## 2 IGBT

**Table 2** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Collector-emitter voltage	$V_{CE}$	$T_{vj} \geq 25\text{ °C}$	1200	V	
DC collector current, limited by $T_{vjmax}$	$I_C$	limited by bondwire	$T_c = 25\text{ °C}$	154	A
			$T_c = 100\text{ °C}$	103	
Pulsed collector current, $t_p$ limited by $T_{vjmax}$	$I_{Cpulse}$		225	A	
Turn-off safe operating area		$V_{CE} \leq 1200\text{ V}, T_{vj} \leq 175\text{ °C}$	225	A	
Gate-emitter voltage	$V_{GE}$		$\pm 20$	V	
Transient gate-emitter voltage	$V_{GE}$	$t_p \leq 0.5\text{ }\mu\text{s}, D < 0.001$	$\pm 25$	V	
Short-circuit withstand time	$t_{SC}$	$V_{CC} \leq 600\text{ V}, V_{GE} = 15\text{ V}$ , Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0\text{ s}, T_{vj} = 150\text{ °C}$	8	$\mu\text{s}$	
Power dissipation	$P_{tot}$	$T_{vj} \leq 175\text{ °C}$	$T_c = 25\text{ °C}$	630	W
			$T_c = 100\text{ °C}$	315	

**Table 3 Characteristic values**

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CEsat}$	$I_C = 75\text{ A}, V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$		1.65	2	V
			$T_{vj} = 175\text{ °C}$		2		
Gate-emitter threshold voltage	$V_{GETh}$	$I_C = 1.5\text{ mA}, V_{CE} = V_{GE}$		5.1	5.7	6.5	V
Zero gate-voltage collector current	$I_{CES}$	$V_{CE} = 1200\text{ V}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$			40	$\mu\text{A}$
			$T_{vj} = 175\text{ °C}$		6600		
Gate-emitter leakage current	$I_{GES}$	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}$				100	nA
Transconductance	$g_{fs}$	$I_C = 75\text{ A}, V_{CE} = 20\text{ V}, T_{vj} = 175\text{ °C}$			30		S
Short-circuit collector current	$I_{SC}$	$V_{CC} \leq 600\text{ V}, V_{GE} = 15\text{ V}, t_{SC} \leq 8\text{ }\mu\text{s}$ , Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0\text{ s}$			450		A
Input capacitance	$C_{ies}$	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			11.2		nF
Output capacitance	$C_{oes}$	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			210		pF
Reverse transfer capacitance	$C_{res}$	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			50		pF
Gate charge	$Q_G$	$I_C = 75\text{ A}, V_{GE} = 15\text{ V}, V_{CC} = 960\text{ V}$			450		nC
Turn-on delay time	$t_{d(on)}$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{G(on)} = 2.1\text{ }\Omega, R_{G(off)} = 2.1\text{ }\Omega$	$T_{vj} = 25\text{ °C}, I_C = 75\text{ A}$		38		ns
			$T_{vj} = 175\text{ °C}, I_C = 75\text{ A}$		36		
Rise time (inductive load)	$t_r$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{G(on)} = 2.1\text{ }\Omega, R_{G(off)} = 2.1\text{ }\Omega$	$T_{vj} = 25\text{ °C}, I_C = 75\text{ A}$		23		ns
			$T_{vj} = 175\text{ °C}, I_C = 75\text{ A}$		26		
Turn-off delay time	$t_{d(off)}$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{G(on)} = 2.1\text{ }\Omega, R_{G(off)} = 2.1\text{ }\Omega$	$T_{vj} = 25\text{ °C}, I_C = 75\text{ A}$		190		ns
			$T_{vj} = 175\text{ °C}, I_C = 75\text{ A}$		253		
Fall time (inductive load)	$t_f$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{G(on)} = 2.1\text{ }\Omega, R_{G(off)} = 2.1\text{ }\Omega$	$T_{vj} = 25\text{ °C}, I_C = 75\text{ A}$		107		ns
			$T_{vj} = 175\text{ °C}, I_C = 75\text{ A}$		230		
Turn-on energy	$E_{on}$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{G(on)} = 2.1\text{ }\Omega, R_{G(off)} = 2.1\text{ }\Omega$	$T_{vj} = 25\text{ °C}, I_C = 75\text{ A}$		5.13		mJ
			$T_{vj} = 175\text{ °C}, I_C = 75\text{ A}$		7.32		

(table continues...)

**Table 3 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Turn-off energy	$E_{off}$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V},$ $R_{G(on)} = 2.1\ \Omega,$ $R_{G(off)} = 2.1\ \Omega$	$T_{vj} = 25\text{ }^\circ\text{C},$ $I_C = 75\text{ A}$		3.48		mJ
			$T_{vj} = 175\text{ }^\circ\text{C},$ $I_C = 75\text{ A}$		6.48		
Total switching energy	$E_{ts}$	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V},$ $R_{G(on)} = 2.1\ \Omega,$ $R_{G(off)} = 2.1\ \Omega$	$T_{vj} = 25\text{ }^\circ\text{C},$ $I_C = 75\text{ A}$		8.6		mJ
			$T_{vj} = 175\text{ }^\circ\text{C},$ $I_C = 75\text{ A}$		13.8		
Operating junction temperature	$T_{vj}$		-40		175	$^\circ\text{C}$	

Note: Electrical Characteristic, at  $T_{vj} = 25\text{ }^\circ\text{C}$ , unless otherwise specified.

### 3 Diode

**Table 4 Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit	
Diode forward current, limited by $T_{vjmax}$	$I_F$		$T_c = 25\text{ }^\circ\text{C}$	126	A
			$T_c = 100\text{ }^\circ\text{C}$	83	
Diode pulsed current, $t_p$ limited by $T_{vjmax}$	$I_{Fpulse}$		225	A	
Power dissipation	$P_{tot}$		$T_c = 25\text{ }^\circ\text{C}$	356	W
			$T_c = 100\text{ }^\circ\text{C}$	178	

**Table 5 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Diode forward voltage	$V_F$	$I_F = 75\text{ A}$	$T_{vj} = 25\text{ }^\circ\text{C}$		1.65	2.15	V
			$T_{vj} = 175\text{ }^\circ\text{C}$		1.6		
Diode reverse recovery time	$t_{rr}$	$V_R = 600\text{ V}, R_{G(on)} = 2.1\ \Omega$	$T_{vj} = 25\text{ }^\circ\text{C},$ $I_F = 75\text{ A}$		193		ns
			$T_{vj} = 175\text{ }^\circ\text{C},$ $I_F = 75\text{ A}$		313		
Diode reverse recovery charge	$Q_{rr}$	$V_R = 600\text{ V}, R_{G(on)} = 2.1\ \Omega$	$T_{vj} = 25\text{ }^\circ\text{C},$ $I_F = 75\text{ A}$		5.26		$\mu\text{C}$
			$T_{vj} = 175\text{ }^\circ\text{C},$ $I_F = 75\text{ A}$		10.9		

(table continues...)

**Table 5 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Diode peak reverse recovery current	$I_{rrm}$	$V_R = 600 \text{ V}, R_{G(on)} = 2.1 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		51		A
			$T_{vj} = 175 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		65		
Diode peak rate of fall of reverse recovery current	$di_{rr}/dt$	$V_R = 600 \text{ V}, R_{G(on)} = 2.1 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		-345		A/ $\mu\text{s}$
			$T_{vj} = 175 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		-245		
Reverse recovery energy	$E_{rec}$	$V_R = 600 \text{ V}, R_{G(on)} = 2.1 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		1.7		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C},$ $I_F = 75 \text{ A}$		3.84		
Operating junction temperature	$T_{vj}$			-40		175	$^\circ\text{C}$

**Note:** For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.


Dynamic test circuit, parasitic inductance  $L_\sigma = 30 \text{ nH}$ ,  $C_\sigma = 18 \text{ pF}$ .

## 4 Characteristics diagrams

### Reverse bias safe operating area

$$I_C = f(V_{CE})$$


$$T_{vj} \leq 175\text{ °C}, V_{CE} \leq 1200\text{ V}$$



### Typical output characteristic

$$I_C = f(V_{CE})$$


$$T_{vj} = 25\text{ °C}$$



### Typical output characteristic

$$I_C = f(V_{CE})$$


$$T_{vj} = 175\text{ °C}$$



### Typical transfer characteristic

$$I_C = f(V_{GE})$$


$$V_{CE} = 20\text{ V}$$



4 Characteristics diagrams


**Typical collector-emitter saturation voltage as a function of junction temperature**

$V_{CEsat} = f(T_{vj})$   
 $V_{GE} = 15 \text{ V}$




**Gate-emitter threshold voltage as a function of junction temperature**

$V_{GEth} = f(T_{vj})$   
 $I_c = 1.5 \text{ mA}$




**Typical switching times as a function of collector current**

$t = f(I_c)$   
 $V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}, R_G = 2.1 \text{ } \Omega$



**Typical switching times as a function of gate resistor**

$t = f(R_G)$   
 $I_c = 75 \text{ A}, V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}$






**Typical switching times as a function of junction temperature**

$t = f(T_{vj})$


$I_C = 75 \text{ A}, V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 2.1 \Omega$



**Typical switching energy losses as a function of collector current**

$E = f(I_C)$


$V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}, R_G = 2.1 \Omega$



**Typical switching energy losses as a function of gate resistor**

$E = f(R_G)$


$I_C = 75 \text{ A}, V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ °C}, V_{GE} = 0/15 \text{ V}$



**Typical switching energy losses as a function of junction temperature**

$E = f(T_{vj})$

$I_C = 75 \text{ A}, V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 2.1 \Omega$




4 Characteristics diagrams

**Typical switching energy losses as a function of collector emitter voltage**

$E = f(V_{CE})$


$I_C = 75 \text{ A}$ ,  $T_{vj} = 175 \text{ }^\circ\text{C}$ ,  $V_{GE} = 0/15 \text{ V}$ ,  $R_G = 2.1 \text{ } \Omega$



**Typical gate charge**

$V_{GE} = f(Q_G)$


$I_C = 75 \text{ A}$



**Typical capacitance as a function of collector-emitter voltage**

$C = f(V_{CE})$


$f = 100 \text{ kHz}$ ,  $V_{GE} = 0 \text{ V}$



**Typical short circuit collector current as a function of gate-emitter voltage**

$I_{C(SC)} = f(V_{GE})$

$T_{vj} \leq 175 \text{ }^\circ\text{C}$ ,  $V_{CC} \leq 600 \text{ V}$




4 Characteristics diagrams

**Short circuit withstand time as a function of gate-emitter voltage**

$t_{SC} = f(V_{GE})$


$T_{vj} \leq 175^\circ\text{C}, V_{CC} \leq 600\text{ V}$



**IGBT transient thermal impedance as a function of pulse width**

$Z_{th(j-c)} = f(t_p)$


$D = t_p/T$



**Diode transient thermal impedance as a function of pulse width**


$Z_{th(j-c)} = f(t_p)$

$D = t_p/T$




**Typical diode forward current as a function of forward voltage**

$I_F = f(V_F)$



**Typical diode forward voltage as a function of junction temperature**


$V_F = f(T_{vj})$



**Typical diode current slope as a function of gate resistor**

$di_F/dt = f(R_G)$


$V_R = 600$  V,  $I_F = 75$  A



**Typical reverse recovery time as a function of diode current slope**

$t_{rr} = f(di_F/dt)$


$V_R = 600$  V,  $I_F = 75$  A



**Typical reverse recovery charge as a function of diode current slope**

$Q_{rr} = f(di_F/dt)$

$V_R = 600$  V,  $I_F = 75$  A




4 Characteristics diagrams

**Typical reverse recovery current as a function of diode current slope**

$I_{rrm} = f(di_F/dt)$


$V_R = 600\text{ V}, I_F = 75\text{ A}$



**Typical diode peak rate of fall of reverse recovery current as a function of diode current slope**

$di_{rr}/dt = f(di_F/dt)$


$V_R = 600\text{ V}, I_F = 75\text{ A}$



**Typical reverse energy losses as a function of diode current slope**


$E_{rec} = f(di_F/dt)$

$V_R = 600\text{ V}, I_F = 75\text{ A}$



**5 Package outlines**

**PG-TO247-3-PLUS-NN3.7**



PACKAGE - GROUP NUMBER:		PG-TO247-3-U01	
DIMENSIONS	MILLIMETERS		
	MIN.	MAX.	
A	4.90	5.10	
A1	2.31	2.51	
A2	1.90	2.10	
b	1.16	1.26	
b1	1.96	2.06	
b2	2.77	3.38	
b3	2.96	3.25	
b4	2.96	3.06	
c	0.59	0.66	
D	20.90	21.10	
D1	16.25	16.85	
D2	1.05	1.35	
D3	0.58	0.78	
E	15.70	16.90	
E1	13.10	13.50	
E3	1.35	1.55	
e	5.44 (BSC)		
N	3		
L	19.80	20.10	
L1	3.90	4.30	
R	1.90	2.10	

NOTE:  
 DIMENSIONS DO NOT INCLUDE MOLDFLASH; PROTRUSION OR GATE BURRS

**Figure 1**

**6 Testing conditions**



**Figure 2**

## Revision history

Document revision	Date of release	Description of changes
0.10	2022-05-04	Target datasheet
1.00	2022-12-05	Final datasheet



## Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2022-12-05**

**Published by**

**Infineon Technologies AG**

**81726 Munich, Germany**

**© 2022 Infineon Technologies AG**

**All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference**

**IFX-ABB782-002**

## Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

## Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon\(英飞凌\)](#)