

IRFR540ZPbF IRFU540ZPbF


Features

- Advanced Process Technology
- Ultra Low On-Resistance
- 175°C Operating Temperature
- Fast Switching
- Repetitive Avalanche Allowed up to Tjmax
- Lead-Free
- Halogen-Free

Description

This HEXFET® Power MOSFET utilizes the latest processing techniques to achieve extremely low on-resistance per silicon area. Additional features of this design are a 175°C junction operating temperature, fast switching speed and improved repetitive avalanche rating. These features combine to make this design an extremely efficient and reliable device for use in a wide variety of applications.

HEXFET® Power MOSFET



Absolute Maximum Ratings

| | Parameter | Max. | Units |
|---------------------------------|---|--------------------------|---------------------|
| $I_D @ T_C = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ (Silicon Limited) | 35 | A |
| $I_D @ T_C = 100^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ (Silicon Limited) | 25 | |
| I_{DM} | Pulsed Drain Current ① | 140 | |
| $P_D @ T_C = 25^\circ\text{C}$ | Power Dissipation | 91 | W |
| | Linear Derating Factor | 0.61 | W/ $^\circ\text{C}$ |
| V_{GS} | Gate-to-Source Voltage | ± 20 | V |
| E_{AS} (Thermally limited) | Single Pulse Avalanche Energy ② | 39 | mJ |
| E_{AS} (Tested) | Single Pulse Avalanche Energy Tested Value ⑥ | 75 | |
| I_{AR} | Avalanche Current ① | See Fig.12a, 12b, 15, 16 | A |
| E_{AR} | Repetitive Avalanche Energy ③ | | mJ |
| T_J | Operating Junction and | -55 to + 175 | $^\circ\text{C}$ |
| T_{STG} | Storage Temperature Range | | |
| | Reflow Soldering Temperature, for 10 seconds | | |
| | Mounting Torque, 6-32 or M3 screw | 300 | |
| | | 10 lbf*in (1.1N*m) | |

Thermal Resistance

| | Parameter | Typ. | Max. | Units |
|-----------|-----------------------------------|------|------|--------------------|
| R_{0JC} | Junction-to-Case ④ | — | 1.64 | $^\circ\text{C/W}$ |
| R_{0JA} | Junction-to-Ambient (PCB mount) ⑦ | — | 40 | |
| R_{0JA} | Junction-to-Ambient | — | 110 | |


HEXFET® is a registered trademark of International Rectifier.

www.irf.com


1

09/30/10

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|---|--------------------------------------|------|-------|------|---------------------|---|
| $V_{(\text{BR})\text{DSS}}$ | Drain-to-Source Breakdown Voltage | 100 | — | — | V | $V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$ |
| $\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$ | Breakdown Voltage Temp. Coefficient | — | 0.092 | — | V/ $^\circ\text{C}$ | Reference to $25^\circ\text{C}, I_D = 1\text{mA}$ |
| $R_{\text{DS}(\text{on})}$ | Static Drain-to-Source On-Resistance | — | 22.5 | 28.5 | $\text{m}\Omega$ | $V_{\text{GS}} = 10\text{V}, I_D = 21\text{A}$ ③ |
| $V_{\text{GS}(\text{th})}$ | Gate Threshold Voltage | 2.0 | — | 4.0 | V | $V_{\text{DS}} = V_{\text{GS}}, I_D = 50\mu\text{A}$ |
| g_{fs} | Forward Transconductance | 28 | — | — | S | $V_{\text{DS}} = 25\text{V}, I_D = 21\text{A}$ |
| I_{DSS} | Drain-to-Source Leakage Current | — | — | 20 | μA | $V_{\text{DS}} = 100\text{V}, V_{\text{GS}} = 0\text{V}$ |
| | | — | — | 250 | | $V_{\text{DS}} = 100\text{V}, V_{\text{GS}} = 0\text{V}, T_J = 125^\circ\text{C}$ |
| I_{GSS} | Gate-to-Source Forward Leakage | — | — | 200 | nA | $V_{\text{GS}} = 20\text{V}$ |
| | Gate-to-Source Reverse Leakage | — | — | -200 | | $V_{\text{GS}} = -20\text{V}$ |
| Q_g | Total Gate Charge | — | 39 | 59 | nC | $I_D = 21\text{A}$ |
| Q_{gs} | Gate-to-Source Charge | — | 11 | — | | $V_{\text{DS}} = 50\text{V}$ |
| Q_{gd} | Gate-to-Drain ("Miller") Charge | — | 12 | — | | $V_{\text{GS}} = 10\text{V}$ ③ |
| $t_{\text{d}(\text{on})}$ | Turn-On Delay Time | — | 14 | — | ns | $V_{\text{DD}} = 50\text{V}$ |
| t_r | Rise Time | — | 42 | — | | $I_D = 21\text{A}$ |
| $t_{\text{d}(\text{off})}$ | Turn-Off Delay Time | — | 43 | — | | $R_G = 13 \Omega$ |
| t_f | Fall Time | — | 34 | — | | $V_{\text{GS}} = 10\text{V}$ ③ |
| L_D | Internal Drain Inductance | — | 4.5 | — | nH | Between lead, 6mm (0.25in.) from package and center of die contact |
| L_S | Internal Source Inductance | — | 7.5 | — | |  |
| C_{iss} | Input Capacitance | — | 1690 | — | pF | $V_{\text{GS}} = 0\text{V}$ |
| C_{oss} | Output Capacitance | — | 180 | — | | $V_{\text{DS}} = 25\text{V}$ |
| C_{rss} | Reverse Transfer Capacitance | — | 100 | — | | $f = 1.0\text{MHz}$ |
| C_{oss} | Output Capacitance | — | 720 | — | | $V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 1.0\text{V}, f = 1.0\text{MHz}$ |
| C_{oss} | Output Capacitance | — | 110 | — | | $V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 80\text{V}, f = 1.0\text{MHz}$ |
| $C_{\text{oss eff.}}$ | Effective Output Capacitance | — | 190 | — | | $V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 0\text{V to } 80\text{V}$ ④ |

Source-Drain Ratings and Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|-----------------|---|---|------|------|-------|---|
| I_S | Continuous Source Current (Body Diode) | — | — | 35 | A | MOSFET symbol showing the integral reverse p-n junction diode. |
| | Pulsed Source Current (Body Diode) ① | — | — | 140 | |  |
| V_{SD} | Diode Forward Voltage | — | — | 1.3 | V | $T_J = 25^\circ\text{C}, I_S = 21\text{A}, V_{\text{GS}} = 0\text{V}$ ③ |
| t_{rr} | Reverse Recovery Time | — | 32 | 48 | ns | $T_J = 25^\circ\text{C}, I_F = 21\text{A}, V_{\text{DD}} = 50\text{V}$ |
| Q_{rr} | Reverse Recovery Charge | — | 40 | 60 | nC | $dI/dt = 100\text{A}/\mu\text{s}$ ③ |
| t_{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible (turn-on is dominated by $LS+LD$) | | | | |




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Typical Forward Transconductance vs. Drain Current

IRFR/U540ZPbF

International
IR Rectifier




Fig 5. Typical Capacitance vs.
Drain-to-Source Voltage




Fig 6. Typical Gate Charge vs.
Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode
Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current vs.
Case Temperature




Fig 10. Normalized On-Resistance
vs. Temperature










Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

IRFR/U540ZPbF

International
IR Rectifier



6






Fig 15. Typical Avalanche Current vs.Pulsewidth




Fig 16. Maximum Avalanche Energy vs. Temperature

www.irf.com

**Notes on Repetitive Avalanche Curves , Figures 15, 16:
 (For further info, see AN-1005 at www.irf.com)**

1. Avalanche failures assumption:
 Purely a thermal phenomenon and failure occurs at a temperature far in excess of T_{jmax} . This is validated for every part type.
2. Safe operation in Avalanche is allowed as long as T_{jmax} is not exceeded.
3. Equation below based on circuit and waveforms shown in Figures 12a, 12b.
4. $P_{D(ave)}$ = Average power dissipation per single avalanche pulse.
5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).
6. I_{av} = Allowable avalanche current.
7. ΔT = Allowable rise in junction temperature, not to exceed T_{jmax} (assumed as 25°C in Figure 15, 16).
 t_{av} = Average time in avalanche.
 D = Duty cycle in avalanche = $t_{av} \cdot f$
 $Z_{thJC}(D, t_{av})$ = Transient thermal resistance, see figure 11)

$$P_{D(ave)} = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$$

$$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$$

$$E_{AS(AR)} = P_{D(ave)} \cdot t_{av}$$

IRFR/U540ZPbF

International
IR Rectifier




Fig 17. Peak Diode Recovery dv/dt Test Circuit for N-Channel HEXFET® Power MOSFETs




Fig 18a. Switching Time Test Circuit





Fig 18b. Switching Time Waveforms

International
IR Rectifier

IRFR/U540ZPbF

D-Pak (TO-252AA) Package Outline

Dimensions are shown in millimeters (inches)



NOTES:
 1.- DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
 2.- DIMENSION ARE SHOWN IN INCHES [MILLIMETERS]
 △ LEAD DIMENSION UNCONTROLLED IN L5.
 △ DIMENSION D1, E1, L3 & b3 ESTABLISH A MINIMUM MOUNTING SURFACE FOR THERMAL PAD.
 5.- SECTION C-C DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN .005 AND 0.10 [0.13 AND 0.25] FROM THE LEAD TIP.
 △ DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005 [0.13] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
 △ DIMENSION b1 & c1 APPLIED TO BASE METAL ONLY.
 △ DATUM A & B TO BE DETERMINED AT DATUM PLANE H.
 9.- OUTLINE CONFORMS TO JEDEC OUTLINE TO-252AA.

| SYMBOL | DIMENSIONS | | NOTES |
|--------|-------------|-----------|-----------|
| | MILLIMETERS | INCHES | |
| O | MIN. | MAX. | |
| A | 2.18 | 2.39 | .086 .094 |
| A1 | — | 0.13 | — .005 |
| b | 0.64 | 0.89 | .025 .035 |
| b1 | 0.65 | 0.79 | .025 .031 |
| b2 | 0.76 | 1.14 | .030 .045 |
| b3 | 4.95 | 5.46 | .195 .215 |
| c | 0.46 | 0.61 | .018 .024 |
| c1 | 0.41 | 0.56 | .016 .022 |
| c2 | 0.46 | 0.89 | .018 .035 |
| D | 5.97 | 6.22 | .235 .245 |
| D1 | 5.21 | — | .205 — |
| E | 6.35 | 6.73 | .250 .265 |
| E1 | 4.32 | — | .170 — |
| e | 2.29 BSC | .090 BSC | |
| H | 9.40 | 10.41 | .370 .410 |
| L | 1.40 | 1.78 | .055 .070 |
| L1 | 2.74 BSC | .108 REF. | |
| L2 | 0.51 BSC | .020 BSC | |
| L3 | 0.89 | 1.27 | .035 .050 |
| L4 | — | 1.02 | — .040 |
| L5 | 1.14 | 1.52 | .045 .060 |
| Φ | 0° | 10° | 0° 10° |
| Φ1 | 0° | 15° | 0° 15° |
| Φ2 | 25° | 35° | 25° 35° |

LEAD ASSIGNMENTS

HEXFET

- 1.- GATE
- 2.- DRAIN
- 3.- SOURCE
- 4.- DRAIN

IGBT & CoPAK


- 1.- GATE
- 2.- COLLECTOR
- 3.- Emitter
- 4.- COLLECTOR

D-Pak (TO-252AA) Part Marking Information


EXAMPLE: THIS IS AN IRFR120
WITH ASSEMBLY
LOT CODE 1234
ASSEMBLED ON WV16, 2001
IN THE ASSEMBLY LINE "A"

Note: "P" in assembly line position indicates "Lead-Free"

"P" in assembly line position indicates "Lead-Free" qualification to the consumer level



OR



Notes:


1. For an Automotive Qualified version of this part please see <http://www.irf.com/product-info/auto/>
2. For the most current drawing please refer to IR website at <http://www.irf.com/package/>

www.irf.com

IRFR/U540ZPbF

I-Pak (TO-251AA) Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
- DIMENSION ARE SHOWN IN INCHES [MILLIMETERS]
- DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005 [0.13] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
- THERMAL PAD CONTOUR OPTION WITHIN DIMENSION D4, L2, E1 & D1.
- LEAD DIMENSION UNCONTROLLED IN L3.
- DIMENSION b1, b2 & c1 APPLY TO BASE METAL ONLY.
- OUTLINE CONFORMS TO JEDEC OUTLINE TO-251AA (Date 06/02).
- CONTROLLING DIMENSION : INCHES.

| S Y M B O L | DIMENSIONS | | N O T E S | |
|----------------------------|-------------|--------|-----------------------|------|
| | MILLIMETERS | INCHES | | |
| | MIN. | MAX. | MIN. | MAX. |
| A | 2.18 | 2.39 | .086 | .094 |
| A1 | 0.89 | 1.14 | .035 | .045 |
| b | 0.64 | 0.89 | .025 | .035 |
| b1 | 0.65 | 0.79 | .025 | .031 |
| b2 | 0.76 | 1.14 | .030 | .045 |
| b3 | 0.76 | 1.04 | .030 | .041 |
| b4 | 4.95 | 5.46 | .195 | .215 |
| c | 0.46 | 0.61 | .018 | .024 |
| c1 | 0.41 | 0.56 | .016 | .022 |
| c2 | 0.46 | 0.89 | .018 | .035 |
| D | 5.97 | 6.22 | .235 | .245 |
| D1 | 5.21 | — | .205 | — |
| E | 6.35 | 6.73 | .250 | .265 |
| E1 | 4.32 | — | .170 | — |
| e | 2.29 BSC | — | .090 BSC | — |
| L | 8.89 | 9.65 | .350 | .380 |
| L1 | 1.91 | 2.29 | .045 | .090 |
| L2 | 0.89 | 1.27 | .035 | .050 |
| L3 | 1.14 | 1.52 | .045 | .060 |
| Ø1 | 0° | 15° | 0° | 15° |
| Ø2 | 25° | 35° | 25° | 35° |

LEAD ASSIGNMENTS



- HEXFET
 1.- GATE
 2.- DRAIN
 3.- SOURCE
 4.- DRAIN

I-Pak (TO-251AA) Part Marking Information

EXAMPLE: THIS IS AN IRFU120
 WITH ASSEMBLY
 LOT CODE 5678
 ASSEMBLED ON WW19, 2001
 IN THE ASSEMBLY LINE "A"

Note: "P" in assembly line position
 indicates Lead-Free"

OR



Notes:


1. For an Automotive Qualified version of this part please see <http://www.irf.com/product-info/auto/>
2. For the most current drawing please refer to IR website at <http://www.irf.com/package/>

International
IR Rectifier

IRFR/U540ZPbF


D-Pak (TO-252AA) Tape & Reel Information

Dimensions are shown in millimeters (inches)



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :

1. OUTLINE CONFORMS TO EIA-481.

Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 11).
- ② Limited by T_{Jmax} , starting $T_J = 25^\circ\text{C}$, $L = 0.17\text{mH}$ $R_G = 25\Omega$, $I_{AS} = 21\text{A}$, $V_{GS} = 10\text{V}$. Part not recommended for use above this value.
- ③ Pulse width $\leq 1.0\text{ms}$; duty cycle $\leq 2\%$.
- ④ C_{OSS} eff. is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 80% V_{DSS} .
- ⑤ Limited by T_{Jmax} , see Fig.12a, 12b, 15, 16 for typical repetitive avalanche performance.
- ⑥ This value determined from sample failure population. 100% tested to this value in production.
- ⑦ When mounted on 1" square PCB (FR-4 or G-10 Material).
- ⑧ R_g is measured at T_J approximately 90°C

Data and specifications subject to change without notice.
This product has been designed for the Industrial market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.09/2010



电子元器件线上授权代理开拓者
原厂授权 · 正品现货 · 一件即发

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon Technologies\(英飞凌\)](#)