

International
IR Rectifier
RADIATION HARDENED
POWER MOSFET
SURFACE MOUNT(SMD-2)


PD - 94325A

IRHE57133SE
JANSR2N7500U5
130V, N-CHANNEL
REF: MIL-PRF-19500/707

R5™ TECHNOLOGY

Product Summary

Part Number	Radiation Level	R _{DS(on)}	I _D	QPL Part Number
IRHE57133SE	100K Rads (Si)	0.13Ω	9.0A	JANSR2N7500U5



International Rectifier's R5™ technology provides high performance power MOSFETs for space applications. These devices have been characterized for Single Event Effects (SEE) with useful performance up to an LET of 80 (MeV/(mg/cm²)). The combination of low R_{DS(on)} and low gate charge reduces the power losses in switching applications such as DC to DC converters and motor control. These devices retain all of the well established advantages of MOSFETs such as voltage control, fast switching, ease of paralleling and temperature stability of electrical parameters.

Features:

- Single Event Effect (SEE) Hardened
- Ultra Low R_{DS(on)}
- Low Total Gate Charge
- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Surface Mount
- Ceramic Package
- Light Weight

Absolute Maximum Ratings

Pre-Irradiation

	Parameter	Units	
I _D @ V _{GS} = 12V, T _C = 25°C	Continuous Drain Current	A	9.0
I _D @ V _{GS} = 12V, T _C = 100°C	Continuous Drain Current		6.0
I _{DM}	Pulsed Drain Current ①		36
P _D @ T _C = 25°C	Max. Power Dissipation	W	25
	Linear Derating Factor	W/C	0.2
V _{GS}	Gate-to-Source Voltage	V	±20
E _{AS}	Single Pulse Avalanche Energy ②	mJ	56
I _{AR}	Avalanche Current ①	A	9.0
E _{AR}	Repetitive Avalanche Energy ①	mJ	2.5
dV/dt	Peak Diode Recovery dV/dt ③	V/ns	6.6
T _J	Operating Junction	°C	-55 to 150
T _{STG}	Storage Temperature Range		
	Pckg. Mounting Surface Temp.		300 (for 5s)
	Weight	g	0.42 (Typical)

For footnotes refer to the last page

www.irf.com

1

05/06/04

Electrical Characteristics @ $T_j = 25^\circ\text{C}$ (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	130	—	—	V	$\text{V}_{\text{GS}} = 0\text{V}$, $\text{I}_D = 1.0\text{mA}$
$\Delta \text{BV}_{\text{DSS}}/\Delta T_j$	Temperature Coefficient of Breakdown Voltage	—	0.16	—	$\text{V}/^\circ\text{C}$	Reference to 25°C , $\text{I}_D = 1.0\text{mA}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source On-State Resistance	—	—	0.13	Ω	$\text{V}_{\text{GS}} = 12\text{V}$, $\text{I}_D = 6.0\text{A}$ ④
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	2.5	—	4.5	V	$\text{V}_{\text{DS}} = \text{V}_{\text{GS}}$, $\text{I}_D = 1.0\text{mA}$
g_{fs}	Forward Transconductance	5.0	—	—	S (Ω)	$\text{V}_{\text{DS}} \geq 15\text{V}$, $\text{I}_{\text{DS}} = 6.0\text{A}$ ④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	10	μA	$\text{V}_{\text{DS}} = 104\text{V}$, $\text{V}_{\text{GS}} = 0\text{V}$
		—	—	25		$\text{V}_{\text{DS}} = 104\text{V}$, $\text{V}_{\text{GS}} = 0\text{V}$, $T_j = 125^\circ\text{C}$
I_{GSS}	Gate-to-Source Leakage Forward	—	—	100	nA	$\text{V}_{\text{GS}} = 20\text{V}$
I_{GSS}	Gate-to-Source Leakage Reverse	—	—	-100		$\text{V}_{\text{GS}} = -20\text{V}$
Q_g	Total Gate Charge	—	—	48	nC	$\text{V}_{\text{GS}} = 12\text{V}$, $\text{I}_D = 9.0\text{A}$
Q_{gs}	Gate-to-Source Charge	—	—	16		$\text{V}_{\text{DS}} = 65\text{V}$
Q_{gd}	Gate-to-Drain ('Miller') Charge	—	—	18		
$t_{\text{d(on)}}$	Turn-On Delay Time	—	—	25	ns	$\text{V}_{\text{DD}} = 65\text{V}$, $\text{I}_D = 9.0\text{A}$, $\text{V}_{\text{GS}} = 12\text{V}$, $R_G = 7.5\Omega$
t_r	Rise Time	—	—	100		
$t_{\text{d(off)}}$	Turn-Off Delay Time	—	—	35		
t_f	Fall Time	—	—	40		
$L_S + L_D$	Total Inductance	—	6.1	—	nH	Measured from the center of drain pad to center of source pad
C_{iss}	Input Capacitance	—	1020	—	pF	$\text{V}_{\text{GS}} = 0\text{V}$, $\text{V}_{\text{DS}} = 25\text{V}$ $f = 1.0\text{MHz}$
C_{oss}	Output Capacitance	—	306	—		
C_{rss}	Reverse Transfer Capacitance	—	22	—		

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	9.0	A	
I_{SM}	Pulse Source Current (Body Diode) ①	—	—	36		
V_{SD}	Diode Forward Voltage	—	—	1.5	V	$T_j = 25^\circ\text{C}$, $I_S = 9.0\text{A}$, $\text{V}_{\text{GS}} = 0\text{V}$ ④
t_{rr}	Reverse Recovery Time	—	—	250	nS	$T_j = 25^\circ\text{C}$, $I_F = 9.0\text{A}$, $dI/dt \leq 100\text{A}/\mu\text{s}$ $\text{V}_{\text{DD}} \leq 25\text{V}$ ④
Q_{RR}	Reverse Recovery Charge	—	—	1.5	μC	
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by $L_S + L_D$.				

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
R_{thJC}	Junction-to-Case	—	—	5.0	$^\circ\text{C}/\text{W}$	soldered to a copper-clad PC board
$R_{\text{thJ-PCB}}$	Junction-to-PC board	—	19	—		

Note: Corresponding Spice and Saber models are available on International Rectifier Website.

For footnotes refer to the last page

Radiation Characteristics

IRHE57133SE, JANSR2N7500U5

International Rectifier Radiation Hardened MOSFETs are tested to verify their radiation hardness capability. The hardness assurance program at International Rectifier is comprised of two radiation environments. Every manufacturing lot is tested for total ionizing dose (per notes 5 and 6) using the TO-3 package. Both pre- and post-irradiation performance are tested and specified using the same drive circuitry and test conditions in order to provide a direct comparison.

Table 1. Electrical Characteristics @ $T_j = 25^\circ\text{C}$, Post Total Dose Irradiation ⑤⑥

	Parameter	100K Rads (Si)		Units	Test Conditions ⑧
		Min	Max		
BV_{DSS}	Drain-to-Source Breakdown Voltage	130	—	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = 1.0\text{mA}$
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	2.0	4.5		$\text{V}_{\text{GS}} = \text{V}_{\text{DS}}, \text{I}_D = 1.0\text{mA}$
I_{GSS}	Gate-to-Source Leakage Forward	—	100	nA	$\text{V}_{\text{GS}} = 20\text{V}$
I_{GSS}	Gate-to-Source Leakage Reverse	—	-100		$\text{V}_{\text{GS}} = -20\text{V}$
I_{DSS}	Zero Gate Voltage Drain Current	—	10	μA	$\text{V}_{\text{DS}}=104\text{V}, \text{V}_{\text{GS}}=0\text{V}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source ④ On-State Resistance (TO-3)	—	0.111	Ω	$\text{V}_{\text{GS}} = 12\text{V}, \text{I}_D = 6.0\text{A}$
$\text{R}_{\text{DS(on)}}$	Static Drain-to-Source ④ On-State Resistance (LCC-18)	—	0.13	Ω	$\text{V}_{\text{GS}} = 12\text{V}, \text{I}_D = 6.0\text{A}$
V_{SD}	Diode Forward Voltage ④	—	1.5	V	$\text{V}_{\text{GS}} = 0\text{V}, \text{I}_D = 9.0\text{A}$

International Rectifier radiation hardened MOSFETs have been characterized in heavy ion environment for Single Event Effects (SEE). Single Event Effects characterization is illustrated in Fig. a and Table 2.

Table 2. Single Event Effect Safe Operating Area

Ion	LET MeV/(mg/cm ²)	Energy (MeV)	Range (μm)	$\text{V}_{\text{DS}} (\text{V})$				
				@ $\text{V}_{\text{GS}}=0\text{V}$	@ $\text{V}_{\text{GS}}=-5\text{V}$	@ $\text{V}_{\text{GS}}=-10\text{V}$	@ $\text{V}_{\text{GS}}=-15\text{V}$	@ $\text{V}_{\text{GS}}=-20\text{V}$
Br	36.7	309	39.5	130	130	130	130	130
I	59.8	341	32.5	130	130	130	100	50
Au	82.3	350	28.4	130	120	30	—	—




Fig a. Single Event Effect, Safe Operating Area

For footnotes refer to the last page

IRHE57133SE, JANSR2N7500U5

Pre-Irradiation




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance
Vs. Temperature

Pre-Irradiation




Fig 5. Typical Capacitance Vs.
Drain-to-Source Voltage

IRHE57133SE, JANSR2N7500U5




Fig 6. Typical Gate Charge Vs.
Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode
Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs.
Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

Pre-Irradiation

IRHE57133SE, JANSR2N7500U5




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13a. Basic Gate Charge Waveform





Fig 13b. Gate Charge Test Circuit

Footnotes:

- ① Repetitive Rating; Pulse width limited by maximum junction temperature.
- ② $V_{DD} = 50V$, starting $T_J = 25^\circ C$, $L=1.4mH$
Peak $I_L = 9.0A$, $V_{GS} = 12V$
- ③ $I_{SD} \leq 9.0A$, $dI/dt \leq 270A/\mu s$,
 $V_{DD} \leq 130V$, $T_J \leq 150^\circ C$
- ④ Pulse width $\leq 300 \mu s$; Duty Cycle $\leq 2\%$
- ⑤ **Total Dose Irradiation with V_{GS} Bias.**
12 volt V_{GS} applied and $V_{DS} = 0$ during irradiation per MIL-STD-750, method 1019, condition A.
- ⑥ **Total Dose Irradiation with V_{DS} Bias.**
104 volt V_{DS} applied and $V_{GS} = 0$ during irradiation per MIL-STD-750, method 1019, condition A.

Case Outline and Dimensions — LCC-18**NOTES:**

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M-1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES]

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105

IR LEOMINSTER : 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776

TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.
Data and specifications subject to change without notice. 05/04



电子元器件线上授权代理开拓者
原厂授权 · 正品现货 · 一件即发

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon Technologies\(英飞凌\)](#)