

BAT62

Surface mount silicon RF Schottky diode, anti-parallel pair

- Order now
- Technical documents
- Simulation
- Support

Product description

This Infineon RF Schottky diode is a silicon low barrier N-type device with an integrated guard ring on-chip for overvoltage protection. Its low barrier height, small forward voltage and low junction capacitance make BAT62 a suitable choice for mixer and detector applications for frequencies up to 6 GHz.



Feature list

- Low inductance $L_S = 2$ nH (typical)
- Low capacitance $C = 0.41$ pF (typical) at voltage $V_R = 0$ V and frequency $f = 1$ MHz
- Industry standard SOT143 package (2.9 mm x 2.4 mm x 1 mm)
- Pb-free, RoHS compliant and halogen-free

Product validation

Qualified for industrial applications according to the relevant tests of JEDEC47/20/22.

Potential applications

For mixers and detectors in:

- Wireless communication
- Smart metering
- Set top boxes
- Mobile devices

Device information




Table 1 Part information

Product name / Ordering code	Package	Configuration	Marking	Pieces / Reel
BAT62 / BAT62E6327HTSA1	SOT143	Reverse anti-parallel pair	62s	3 k

Attention: ESD (Electrostatic discharge) sensitive device, observe handling precautions!

Table of contents

Table of contents

Product description 1

Feature list 1

Product validation 1

Potential applications 1

Device information 1

Table of contents 2

1 Absolute maximum ratings 2

2 Electrical performance in test fixture 3

2.1 Electrical characteristics 3

2.2 Characteristic curves 3

3 Thermal characteristics 5

4 Package information SOT143 7

Revision history 7

Disclaimer 8

1 Absolute maximum ratings

Table 2 Absolute maximum ratings at $T_A = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Values		Unit	Note or test condition
		Min.	Max.		
Reverse voltage	V_R	-	40	V	
Forward current	I_F	-	20	mA	
Total power dissipation	P_{TOT}	-	100	mW	$T_S \leq 96\text{ °C}$ ¹⁾
Junction temperature	T_J	-	150	°C	
Operating temperature	T_{OP}	-55	125		
Storage temperature	T_{STG}	-55	150		

Attention: Stresses above the maximum values listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Exceeding only one of these values may cause irreversible damage to the component.

¹ T_S is the soldering point temperature.

Electrical performance in test fixture

2 Electrical performance in test fixture

2.1 Electrical characteristics

Table 3 Electrical characteristics at $T_A = 25\text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Breakdown voltage	V_{BR}	40	–	–	V	$I_R = 10\text{ }\mu\text{A}$
Reverse current	I_R	–	–	10	μA	$V_R = 40\text{ V}$
Forward voltage	V_F	–	0.4	–	V	$I_F = 1\text{ mA}$
		–	0.58	1		$I_F = 2\text{ mA}$
Forward voltage matching	ΔV_F	–	–	20	mV	$I_F = 2\text{ mA}$ ²⁾
Differential resistance	R_0	–	225	–	k Ω	$V_R = 0\text{ V}, f = 10\text{ kHz}$
Capacitance	C	–	0.41	0.6	pF	$V_R = 0\text{ V}, f = 1\text{ MHz}$
Inductance	L_S	–	2	–	nH	

2.2 Characteristic curves

At $T_A = 25\text{ }^\circ\text{C}$, unless otherwise specified




Figure 1 Capacitance C vs. reverse voltage V_R at frequency $f = 1\text{ MHz}$

²⁾ ΔV_F is the difference between lowest and highest V_F in a multiple diode component.

Electrical performance in test fixture




Figure 2 Forward current I_F vs. forward voltage V_F




Figure 3 Reverse current I_R vs. reverse voltage V_R

Note: The curves shown in this chapter have been generated using typical devices but shall not be understood as a guarantee that all devices have identical characteristic curves.

Thermal characteristics

3 Thermal characteristics

Table 4 Thermal resistance

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Thermal resistance (junction - soldering point)	R_{thJS}	-	540	-	K/W	$T_S = 96\text{ °C}$ ³⁾




Figure 4 Permissible forward current I_F in DC operation

³ For R_{thJS} in other conditions refer to the curves in this chapter.

Thermal characteristics




Figure 5 Thermal resistance R_{thJS} in pulse operation




Figure 6 Permissible forward current ratio I_{Fmax}/I_{DC} in pulse operation

4 Package information SOT143




Figure 7 SOT143 package

Note: For package information including footprint, packing and assembly recommendation refer to:

<https://www.infineon.com/cms/en/product/packages/PG-SOT143/PG-SOT143-4-4/>

Revision history

Document version	Date of release	Description of changes
1.0	2021-06-07	<ul style="list-style-type: none"> Change from series datasheet to individual one Initial release of datasheet Typical values and curves updated to the values of the production (No product or process change behind)

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2021-06-07

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2021 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any aspect of this document?
Email: erratum@infineon.com

Document reference
IFX-ywr1546603291726

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Infineon\(英飞凌\)](#)