



SMDJxx(C)A-AU Series 3000W Transient Voltage Suppressor

Rev.1.0


DESCRIPTION

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, telecommunications and intelligent control systems.



FEATURES


- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 3000W peak pulse power capability at 10/1000μs waveform.
- ✧ Typical I_R less than 5μA.
- ✧ Fast response time: typically less than 1.0ps from 0V to V_{BR} min.
- ✧ High temperature to reflow soldering: 260°C/40s at terminals.
- ✧ Plastic package has underwriters laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD-020, LF maximum peak of 260°C.
- ✧ Terminal: solder plated, solderable per J-STD-002.
- ✧ IEC61000-4-2 (ESD) ±30kV (air), ±30kV (contact).
- ✧ UL 497B item recognized. (File No.:E480698).
- ✧ For surface mounted applications in order to optimize board space.
- ✧ High reliability application and automotive grade (AEC-Q101 qualified).



SMC



Bi-directional



Uni-directional

Symbol


ABSOLUTE MAXIMUM RATINGS (T_A=25°C, RH=45%-75%, unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|----------------------------------|-------------|------|
| Storage and operating junction temperature range | T _{STG} /T _J | -55 to +150 | °C |
| Steady state power dissipation at T _L =75°C | P _{M(AV)} | 6.5 | W |
| Peak pulse power dissipation at 10/1000μs waveform | P _{PP} | 3000 | W |
| Maximum instantaneous forward voltage at 100A for unidirectional only | V _F | 5.0 | V |
| Peak forward surge current, 8.3ms single half sine wave(Note 1) | I _{FSM} | 300 | A |
| Typical thermal resistance junction to lead | R _{θJL} | 15 | °C/W |
| Typical thermal resistance junction to ambient | R _{θJA} | 75 | °C/W |

Notes:

1. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum

MARKING



H12C: Device Marking Code
2221: the 21th week, 2022

ELECTRICAL CHARACTERISTICS($T_A=25^{\circ}\text{C}$)

| Part Number | | Marking | | V_R | $I_R@V_R$ | $V_{BR}@I_T$ | | I_T | $V_C@I_{PP}$ | I_{PP}° |
|-------------|-------------|---------|------|-------|----------------------|--------------|--------|-------|--------------|------------------|
| Uni-Polar | Bi-Polar | Uni | Bi | V | max(μA) | min(V) | max(V) | mA | max(V) | A |
| SMDJ12A-AU | SMDJ12CA-AU | H12A | H12C | 12.0 | 5 | 13.30 | 14.70 | 1 | 19.9 | 150.8 |
| SMDJ13A-AU | SMDJ13CA-AU | H13A | H13C | 13.0 | 5 | 14.40 | 15.90 | 1 | 21.5 | 139.5 |
| SMDJ14A-AU | SMDJ14CA-AU | H14A | H14C | 14.0 | 5 | 15.60 | 17.20 | 1 | 23.2 | 129.3 |
| SMDJ15A-AU | SMDJ15CA-AU | H15A | H15C | 15.0 | 5 | 16.70 | 18.50 | 1 | 24.4 | 123.0 |
| SMDJ16A-AU | SMDJ16CA-AU | H16A | H16C | 16.0 | 5 | 17.80 | 19.70 | 1 | 26.0 | 115.4 |
| SMDJ17A-AU | SMDJ17CA-AU | H17A | H17C | 17.0 | 5 | 18.90 | 20.90 | 1 | 27.6 | 108.7 |
| SMDJ18A-AU | SMDJ18CA-AU | H18A | H18C | 18.0 | 5 | 20.00 | 22.20 | 1 | 29.2 | 102.7 |
| SMDJ20A-AU | SMDJ20CA-AU | H20A | H20C | 20.0 | 5 | 22.20 | 24.50 | 1 | 32.4 | 92.6 |
| SMDJ22A-AU | SMDJ22CA-AU | H22A | H22C | 22.0 | 5 | 24.40 | 26.90 | 1 | 35.5 | 84.5 |
| SMDJ24A-AU | SMDJ24CA-AU | H24A | H24C | 24.0 | 5 | 26.70 | 29.50 | 1 | 38.9 | 77.1 |
| SMDJ26A-AU | SMDJ26CA-AU | H26A | H26C | 26.0 | 5 | 28.90 | 31.90 | 1 | 42.1 | 71.3 |
| SMDJ28A-AU | SMDJ28CA-AU | H28A | H28C | 28.0 | 5 | 31.10 | 34.40 | 1 | 45.4 | 66.1 |
| SMDJ30A-AU | SMDJ30CA-AU | H30A | H30C | 30.0 | 5 | 33.30 | 36.80 | 1 | 48.4 | 62.0 |
| SMDJ33A-AU | SMDJ33CA-AU | H33A | H33C | 33.0 | 5 | 36.70 | 40.60 | 1 | 53.3 | 56.3 |
| SMDJ36A-AU | SMDJ36CA-AU | H36A | H36C | 36.0 | 5 | 40.00 | 44.20 | 1 | 58.1 | 51.6 |
| SMDJ40A-AU | SMDJ40CA-AU | H40A | H40C | 40.0 | 5 | 44.40 | 49.10 | 1 | 64.5 | 46.5 |
| SMDJ43A-AU | SMDJ43CA-AU | H43A | H43C | 43.0 | 5 | 47.80 | 52.80 | 1 | 69.4 | 43.2 |
| SMDJ45A-AU | SMDJ45CA-AU | H45A | H45C | 45.0 | 5 | 50.00 | 55.30 | 1 | 72.7 | 41.3 |
| SMDJ48A-AU | SMDJ48CA-AU | H48A | H48C | 48.0 | 5 | 53.30 | 58.90 | 1 | 77.4 | 38.8 |
| SMDJ51A-AU | SMDJ51CA-AU | H51A | H51C | 51.0 | 5 | 56.70 | 62.70 | 1 | 82.4 | 36.4 |

ELECTRICAL CHARACTERISTICS (T_A=25°C, continued)

| Part Number | | Marking | | V _R | I _R @V _R | V _{BR} @I _T | | I _T | V _C @I _{PP} | I _{PP} [Ⓞ] |
|-------------|-------------|---------|------|----------------|--------------------------------|---------------------------------|--------|----------------|---------------------------------|------------------------------|
| Uni-Polar | Bi-Polar | Uni | Bi | V | max(μA) | min(V) | max(V) | mA | max(V) | A |
| SMDJ54A-AU | SMDJ54CA-AU | H54A | H54C | 54.0 | 5 | 60.00 | 66.30 | 1 | 87.1 | 34.4 |
| SMDJ58A-AU | SMDJ58CA-AU | H58A | H58C | 58.0 | 5 | 64.40 | 71.20 | 1 | 93.6 | 32.1 |

Ⓞ Surge waveform: 10/1000μs


V_R: Stand-off voltage -- Maximum voltage that can be applied

V_{BR}: Breakdown voltage

V_C: Clamping voltage -- Peak voltage measured across the suppressor at a specified I_{PP}

I_R: Reverse leakage current

ORDERING INFORMATION



RATINGS AND V-I CHARACTERISTICS CURVES (T_A=25°C, unless otherwise noted)

FIG.1: V- I curve characteristics (Uni-directional)




FIG.2: V- I curve characteristics (Bi-directional)




FIG.3: Pulse waveform




FIG.4: Pulse derating curve






FIG.5: Peak pulse power dissipation vs. pulse width




SOLDERING PARAMETERS

| | | |
|---|-----------------------------------|---|
| Reflow Condition | | Pb-Free assembly (see figure at right) |
| Pre Heat | -Temperature Min ($T_{s(min)}$) | +150°C |
| | -Temperature Max($T_{s(max)}$) | +200°C |
| | -Time (Min to Max) (ts) | 60-180 secs. |
| Average ramp up rate (Liquidus Temp (T_L)to peak) | | 3°C/sec. Max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 3°C/sec. Max |
| Reflow | -Temperature(T_L)(Liquidus) | +217°C |
| | -Temperature(t_L) | 60-150 secs. |
| Peak Temp (T_p) | | +260(+0/-5)°C |
| Time within 5°C of actual Peak Temp (t_p) | | 20-40secs. |
| Ramp-down Rate | | 6°C/sec. Max |
| Time 25°C to Peak Temp (T_p) | | 8 min. Max |
| Do not exceed | | +260°C |




PACKAGE MECHANICAL DATA



| Ref. | Dimensions | | | |
|------|-------------|-------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 5.75 | 6.25 | 0.226 | 0.246 |
| B | 6.90 | 7.40 | 0.272 | 0.291 |
| C | 2.75 | 3.25 | 0.108 | 0.128 |
| D | 0.95 | 1.52 | 0.037 | 0.060 |
| E | 7.70 | 8.20 | 0.303 | 0.323 |
| F | 0.051 | 0.203 | 0.002 | 0.008 |
| G | 0.15 | 0.31 | 0.006 | 0.012 |
| H | 2.15 | 2.62 | 0.085 | 0.103 |
| J | 2.40 | | 0.094 | |
| K | | 4.20 | | 0.165 |
| L | 3.30 | | 0.130 | |

TAPE AND REEL SPECIFICATION-SMC



| Ref. | Dimensions | |
|------|-------------|----------------|
| | Millimeters | Inches |
| A0 | 6.05 ± 0.3 | 0.238 ± 0.012 |
| B0 | 8.31 ± 0.3 | 0.327 ± 0.012 |
| C | 330.0 | 13.0 |
| D0 | 1.55 ± 0.1 | 0.061 ± 0.004 |
| E | 1.75 ± 0.2 | 0.069 ± 0.008 |
| E1 | 13.3 ± 0.3 | 0.524 ± 0.012 |
| F | 7.50 ± 0.2 | 0.295 ± 0.008 |
| P0 | 4.00 ± 0.2 | 0.157 ± 0.008 |
| P1 | 8.00 ± 0.2 | 0.3145 ± 0.008 |
| P2 | 2.00 ± 0.2 | 0.079 ± 0.008 |
| W | 16.0 ± 0.2 | 0.630 ± 0.008 |
| W1 | 19.7 ± 2.0 | 0.776 ± 0.079 |

| PART No. | UNIT WEIGHT (g/PCS) typ. | REEL (PCS) | PER CARTON (PCS) | DESCRIPTION |
|---------------|-----------------------------|---------------|---------------------|-------------------|
| SMDJxxA/CA-AU | 0.31 | 3,000 | 48,000 | 13 inch reel pack |

JieJie products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable JieJie product documentation. Warranties granted by JieJie shall be deemed void for products used for any purpose not expressly set forth in applicable JieJie documentation. JieJie shall not be liable for any claims or damages arising out of products used in applications not expressly intended by JieJie as set forth in applicable JieJie documentation. The sale and use of JieJie products is subject to JieJie terms and conditions of sale, unless otherwise agreed by JieJie.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the first version which is made in 23-Sept.-2022. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ©2022 Jiangsu JieJie Microelectronics Co., Ltd. Printed All rights reserved.

单击下面可查看定价，库存，交付和生命周期等信息

[>>JW\(捷捷微\)](#)