



Description


JMT N-channel Enhancement Mode Power MOSFET

Features


- 30V,5.8A
- $R_{DS(ON)} < 25m\Omega$ @ $V_{GS} = 10V$
- $R_{DS(ON)} < 40m\Omega$ @ $V_{GS} = 4.5V$
- Advanced Trench Technology
- Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application


- Load Switch
- PWM Application
- Power management



SOT-23 top view



Marking and pin Assignment



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
3404	JMTL3404A	TAPING	SOT-23	7inch	3000	120000

Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise specified)

Symbol	Parameter		Max.	Units
V_{DSS}	Drain-Source Voltage		30	V
V_{GSS}	Gate-Source Voltage		± 20	V
I_D	Continuous Drain Current		$T_A = 25^\circ C$	5.8
			$T_A = 100^\circ C$	3.8
I_{DM}	Pulsed Drain Current ^{note1}		23.2	A
P_D	Power Dissipation	$T_A = 25^\circ C$	1.47	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		85	$^\circ C/W$
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	$^\circ C$

**Electrical Characteristics** ($T_J=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(\text{BR})\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}$, $I_D=250\mu\text{A}$	30	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=30\text{V}$, $V_{GS}=0\text{V}$,	-	-	1.0	μA
I_{GSS}	Gate to Body Leakage Current	$V_{DS}=0\text{V}$, $V_{GS}=\pm 20\text{V}$	-	-	± 100	nA
On Characteristics						
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$, $I_D=250\mu\text{A}$	1.0	1.5	2.5	V
$R_{DS(\text{on})}$ note2	Static Drain-Source on-Resistance	$V_{GS}=10\text{V}$, $I_D=5.5\text{A}$	-	18	25	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}$, $I_D=4.5\text{A}$	-	28	40	
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{DS}=15\text{V}$, $V_{GS}=0\text{V}$, $f=1.0\text{MHz}$	-	490	-	pF
C_{oss}	Output Capacitance		-	79	-	pF
C_{rss}	Reverse Transfer Capacitance		-	61	-	pF
Q_g	Total Gate Charge	$V_{DS}=15\text{V}$, $I_D=5.8\text{A}$, $V_{GS}=10\text{V}$	-	5.2	-	nC
Q_{gs}	Gate-Source Charge		-	0.9	-	nC
Q_{gd}	Gate-Drain("Miller") Charge		-	1.3	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	$V_{DS}=15\text{V}$, $I_D=3\text{A}$, $R_{\text{GEN}}=3\Omega$, $V_{GS}=10\text{V}$	-	4.5	-	ns
t_r	Turn-on Rise Time		-	2.5	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	14.5	-	ns
t_f	Turn-off Fall Time		-	3.5	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current	-	-	5.8	A	
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current	-	-	23.2	A	
V_{SD}	Drain to Source Diode Forward Voltage	$V_{GS}=0\text{V}$, $I_S=5.8\text{A}$	-	-	1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 0.5\%$







Figure1: Output Characteristics

Figure 3: On-resistance vs. Drain Current

Figure 5: Gate Charge Characteristics

Figure 2: Typical Transfer Characteristics

Figure 4: Body Diode Characteristics

Figure 6: Capacitance Characteristics


Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature





Figure 11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Test Circuit




Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveforms





Figure 3: Unclamped Inductive Switching Test Circuit & Waveforms

Package Mechanical Data-SOT-23

COMMON DIMENSIONS
(UNITS OF MEASURE=mm)

SYMBOL	MIN	NOM	MAX
A	0.90	1.05	1.20
A ₁	0.00	0.05	0.10
A ₂	0.90	1.00	1.10
b	0.30	0.40	0.50
c	0.08	0.10	0.15
D	2.80	2.90	3.00
E	1.20	1.30	1.40
E ₁	2.30	2.40	2.50
L	0.30	0.40	0.50
θ	0°	5°	10°
L ₁	0.55 REF		
e	0.95 BSC		
e ₁	1.90 REF		

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.
Copyright ©2022 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.

单击下面可查看定价，库存，交付和生命周期等信息

[>>JJW\(捷捷微\)](#)