

## SMDJxx(C)A-AU Series 3000W Transient Voltage Suppressor


Rev.1.0

### DESCRIPTION

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, telecommunications and intelligent control systems.

### FEATURES


- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 3000W peak pulse power capability at 10/1000 $\mu$ s waveform.
- ✧ Typical  $I_R$  less than 5 $\mu$ A.
- ✧ Fast response time: typically less than 1.0ps from 0V to  $V_{BR}$  min.
- ✧ High temperature to reflow soldering: 260 $^{\circ}$ C/40s at terminals.
- ✧ Plastic package has underwriters laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD-020, LF maximum peak of 260 $^{\circ}$ C.
- ✧ Terminal: solder plated, solderable per J-STD-002.
- ✧ IEC61000-4-2 (ESD)  $\pm$ 30kV (air),  $\pm$ 30kV (contact).
- ✧ UL 497B item recognized. (File No.:E480698).
- ✧ For surface mounted applications in order to optimize board space.
- ✧ High reliability application and automotive grade (AEC-Q101 qualified).



SMC



Bi-directional



Uni-directional

Symbol

### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^{\circ}$ C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Storage and operating junction temperature range	$T_{STG}/T_J$	-55 to +150	$^{\circ}$ C
Steady state power dissipation at $T_L=75^{\circ}$ C	$P_{M(AV)}$	6.5	W
Peak pulse power dissipation at 10/1000 $\mu$ s waveform	$P_{PP}$	3000	W
Maximum instantaneous forward voltage at 100A for unidirectional only	$V_F$	5.0	V
Peak forward surge current, 8.3ms single half sine wave(Note 1)	$I_{FSM}$	300	A
Typical thermal resistance junction to lead	$R_{\theta JL}$	15	$^{\circ}$ C/W
Typical thermal resistance junction to ambient	$R_{\theta JA}$	75	$^{\circ}$ C/W

#### Notes:

1. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum

## MARKING



H12C: Device Marking Code  
2221: the 21th week, 2022

ELECTRICAL CHARACTERISTICS( $T_A=25^{\circ}\text{C}$ )

Part Number		Marking		$V_R$	$I_R@V_R$	$V_{BR}@I_T$		$I_T$	$V_C@I_{PP}$	$I_{PP}^{\circ}$
Uni-Polar	Bi-Polar	Uni	Bi	V	max( $\mu\text{A}$ )	min(V)	max(V)	mA	max(V)	A
SMDJ12A-AU	SMDJ12CA-AU	H12A	H12C	12.0	5	13.30	14.70	1	19.9	150.8
SMDJ13A-AU	SMDJ13CA-AU	H13A	H13C	13.0	5	14.40	15.90	1	21.5	139.5
SMDJ14A-AU	SMDJ14CA-AU	H14A	H14C	14.0	5	15.60	17.20	1	23.2	129.3
SMDJ15A-AU	SMDJ15CA-AU	H15A	H15C	15.0	5	16.70	18.50	1	24.4	123.0
SMDJ16A-AU	SMDJ16CA-AU	H16A	H16C	16.0	5	17.80	19.70	1	26.0	115.4
SMDJ17A-AU	SMDJ17CA-AU	H17A	H17C	17.0	5	18.90	20.90	1	27.6	108.7
SMDJ18A-AU	SMDJ18CA-AU	H18A	H18C	18.0	5	20.00	22.20	1	29.2	102.7
SMDJ20A-AU	SMDJ20CA-AU	H20A	H20C	20.0	5	22.20	24.50	1	32.4	92.6
SMDJ22A-AU	SMDJ22CA-AU	H22A	H22C	22.0	5	24.40	26.90	1	35.5	84.5
SMDJ24A-AU	SMDJ24CA-AU	H24A	H24C	24.0	5	26.70	29.50	1	38.9	77.1
SMDJ26A-AU	SMDJ26CA-AU	H26A	H26C	26.0	5	28.90	31.90	1	42.1	71.3
SMDJ28A-AU	SMDJ28CA-AU	H28A	H28C	28.0	5	31.10	34.40	1	45.4	66.1
SMDJ30A-AU	SMDJ30CA-AU	H30A	H30C	30.0	5	33.30	36.80	1	48.4	62.0
SMDJ33A-AU	SMDJ33CA-AU	H33A	H33C	33.0	5	36.70	40.60	1	53.3	56.3
SMDJ36A-AU	SMDJ36CA-AU	H36A	H36C	36.0	5	40.00	44.20	1	58.1	51.6
SMDJ40A-AU	SMDJ40CA-AU	H40A	H40C	40.0	5	44.40	49.10	1	64.5	46.5
SMDJ43A-AU	SMDJ43CA-AU	H43A	H43C	43.0	5	47.80	52.80	1	69.4	43.2
SMDJ45A-AU	SMDJ45CA-AU	H45A	H45C	45.0	5	50.00	55.30	1	72.7	41.3
SMDJ48A-AU	SMDJ48CA-AU	H48A	H48C	48.0	5	53.30	58.90	1	77.4	38.8
SMDJ51A-AU	SMDJ51CA-AU	H51A	H51C	51.0	5	56.70	62.70	1	82.4	36.4

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C, continued)

Part Number		Marking		V <sub>R</sub>	I <sub>R</sub> @V <sub>R</sub>	V <sub>BR</sub> @I <sub>T</sub>		I <sub>T</sub>	V <sub>C</sub> @I <sub>PP</sub>	I <sub>PP</sub> <sup>Ⓞ</sup>
Uni-Polar	Bi-Polar	Uni	Bi	V	max(μA)	min(V)	max(V)	mA	max(V)	A
SMDJ54A-AU	SMDJ54CA-AU	H54A	H54C	54.0	5	60.00	66.30	1	87.1	34.4
SMDJ58A-AU	SMDJ58CA-AU	H58A	H58C	58.0	5	64.40	71.20	1	93.6	32.1

Ⓞ Surge waveform: 10/1000μs


V<sub>R</sub>: Stand-off voltage -- Maximum voltage that can be applied

V<sub>BR</sub>: Breakdown voltage

V<sub>C</sub>: Clamping voltage -- Peak voltage measured across the suppressor at a specified I<sub>PP</sub>


I<sub>R</sub>: Reverse leakage current

## ORDERING INFORMATION



## RATINGS AND V-I CHARACTERISTICS CURVES (T<sub>A</sub>=25°C, unless otherwise noted)

**FIG.1: V- I curve characteristics (Uni-directional)**



**FIG.2: V- I curve characteristics (Bi-directional)**




FIG.3: Pulse waveform




FIG.4: Pulse derating curve






FIG.5: Peak pulse power dissipation vs. pulse width




**SOLDERING PARAMETERS**

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(min)}$ )	+150°C
	-Temperature Max( $T_{s(max)}$ )	+200°C
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ )to peak)		3°C/sec. Max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquidus)	+217°C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_p$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp ( $T_p$ )		8 min. Max
Do not exceed		+260°C




**PACKAGE MECHANICAL DATA**



Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	5.75	6.25	0.226	0.246
B	6.90	7.40	0.272	0.291
C	2.75	3.25	0.108	0.128
D	0.95	1.52	0.037	0.060
E	7.70	8.20	0.303	0.323
F	0.051	0.203	0.002	0.008
G	0.15	0.31	0.006	0.012
H	2.15	2.62	0.085	0.103
J	2.40		0.094	
K		4.20		0.165
L	3.30		0.130	

## TAPE AND REEL SPECIFICATION-SMC



Ref.	Dimensions	
	Millimeters	Inches
A0	6.05 ± 0.3	0.238 ± 0.012
B0	8.31 ± 0.3	0.327 ± 0.012
C	330.0	13.0
D0	1.55 ± 0.1	0.061 ± 0.004
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.3 ± 0.3	0.524 ± 0.012
F	7.50 ± 0.2	0.295 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	8.00 ± 0.2	0.3145 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	16.0 ± 0.2	0.630 ± 0.008
W1	19.7 ± 2.0	0.776 ± 0.079

PART No.	UNIT WEIGHT (g/PCS) typ.	REEL (PCS)	PER CARTON (PCS)	DESCRIPTION
SMDJxxA/CA-AU	0.31	3,000	48,000	13 inch reel pack

JieJie products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable JieJie product documentation. Warranties granted by JieJie shall be deemed void for products used for any purpose not expressly set forth in applicable JieJie documentation. JieJie shall not be liable for any claims or damages arising out of products used in applications not expressly intended by JieJie as set forth in applicable JieJie documentation. The sale and use of JieJie products is subject to JieJie terms and conditions of sale, unless otherwise agreed by JieJie.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the first version which is made in 23-Sept.-2022. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ©2022 Jiangsu JieJie Microelectronics Co., Ltd. Printed All rights reserved.

单击下面可查看定价，库存，交付和生命周期等信息

[>>JW\(捷捷微\)](#)