

## Surface Mount Transient Voltage Suppressors

High temperature stability and high reliability conditions



DO-218AB



### FEATURES

- Junction passivation optimized design passivated anisotropic rectifier technology.
- $T_J = 175^\circ\text{C}$  capability suitable for high reliability and automotive requirement.
- Available in bi-directional polarity.
- Low leakage current.
- Low forward voltage drop.
- High surge capability.
- Meets ISO16750-2 surge specification(varied by test condition).
- Meets MSL-1, per J-STD-020, LF maximum peak of  $260^\circ\text{C}$ .
- AEC-Q101 qualified.
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC.

### TYPICAL APPLICATIONS

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting, especially for automotive load dump protection application.

### MECHANICAL DATA

**Case:** DO-218AB

Molding compound meets UL 94V-0 flammability rating

Base P/NHE3-RoHS-compliant, AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002

PRIMARY CHARACTERISTICS	
$V_R$	12V to 43V
$P_{PP}$ (10/1000 $\mu\text{s}$ )	6600W
$P_{PP}$ (10/10000 $\mu\text{s}$ )	5200W
$P_D$	8W
$T_{Jmax}$	$175^\circ\text{C}$
Polarity	Bi-directional
Package	DO-218AB

MAXIMUM RATINGS( $T_C=25^\circ\text{C}$ , RH=45%-75%, unless otherwise noted)			
Parameter	Symbol	Value	Unit
Peak pulse power dissipation at 10/1000 $\mu\text{s}$ waveform	$P_{PP}$	6600	Watts
Peak pulse power dissipation at 10/10000 $\mu\text{s}$ waveform		5200	Watts
Power dissipation on infinite heat sink at $T_C=25^\circ\text{C}$	$P_D$	8.0	Watts
Peak pulse current with 10/1000 $\mu\text{s}$ waveform	$I_{PPM}^{(1)}$	See next table	Amps
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +175	$^\circ\text{C}$
Typical thermal resistance, junction to case	$R_{\theta JC}$	0.9	$^\circ\text{C/W}$
Typical thermal resistance, junction to ambient	$R_{\theta JA}$	12	$^\circ\text{C/W}$

### Note

(1) Non-repetitive current pulse derated above  $T_A=25^\circ\text{C}$

ELECTRICAL CHARACTERISTICS								
Part Number	V <sub>R</sub>	I <sub>T</sub>	I <sub>R</sub> @V <sub>R</sub>		V <sub>BR</sub> @I <sub>T</sub>		V <sub>C</sub> @I <sub>PP</sub>	I <sub>PP</sub>
Bi-polar	V	mA	μA@25°C	μA@175°C	min(V)	max (V)	V	A
SM8S12CA-AL	12.0	5	5	150	13.3	14.7	19.9	332
SM8S13CA-AL	13.0	5	5	150	14.4	15.9	21.5	307
SM8S14CA-AL	14.0	5	5	150	15.6	17.2	23.2	284
SM8S15CA-AL	15.0	5	5	150	16.7	18.5	24.4	270
SM8S16CA-AL	16.0	5	5	150	17.8	19.7	26.0	253
SM8S17CA-AL	17.0	5	5	150	18.9	20.9	27.6	239
SM8S18CA-AL	18.0	5	5	150	20.0	22.1	29.2	226
SM8S20CA-AL	20.0	5	5	150	22.2	24.5	32.4	204
SM8S22CA-AL	22.0	5	5	150	24.4	26.9	35.5	186
SM8S24CA-AL	24.0	5	5	150	26.7	29.5	38.9	170
SM8S26CA-AL	26.0	5	5	150	28.9	31.9	42.1	157
SM8S28CA-AL	28.0	5	5	150	31.1	34.4	45.4	145
SM8S30CA-AL	30.0	5	5	150	33.3	36.8	48.4	136
SM8S33CA-AL	33.0	5	5	150	36.7	40.6	53.3	124
SM8S36CA-AL	36.0	5	5	150	40.0	44.2	58.1	114
SM8S40CA-AL	40.0	5	5	150	44.4	49.1	64.5	102
SM8S43CA-AL	43.0	5	5	150	47.8	52.8	69.4	95.1

**Note:**

①.Surge waveform:10/1000μs

V<sub>R</sub>: Stand-off voltage -- Maximum voltage that can be applied


V<sub>BR</sub>: Breakdown voltage

V<sub>C</sub>: Clamping voltage -- Peak voltage measured across the suppressor at a specified I<sub>PP</sub>


I<sub>R</sub>: Reverse leakage current

I<sub>T</sub>: Test current


**ORDERING INFORMATION**




**RATINGS AND CHARACTERISTICS CURVES** ( $T_A=25^\circ\text{C}$ , unless otherwise noted)




**FIG.1:** Power derating curve




**FIG.2:** Pulse waveform




**FIG.3:** Load dump power characteristics (10ms exponential waveform)



**FIG.4:** Reverse power capability




**FIG.5:** Typical transient thermal impedance



**FIG.6:** Typical junction capacitance

**MARKING**



SM	Surface Mount
8S	$P_D=8W$
36	$V_R:36V$
C	Bi-directional

**x201:**


2015	2016	2017	2018	2019	2020
5	6	7	8	9	0
2021	2022	2023	2024	...	
1	2	3	4	...	

**5x01:** Month, 1、2、3 ~ 9、O、N、D


**52xx:** Lot number

**SOLDERING PARAMETERS**

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(min)}$ )	+150°C
	-Temperature Max( $T_{s(max)}$ )	+200°C
	-Time (Min to Max) ( $t_s$ )	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ )to peak)		3°C/sec. Max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquidus)	+217°C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_P$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp ( $T_P$ )		8 min. Max
Do not exceed		+260°C




PACKAGE MECHANICAL DATA



DO-218AB

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	9.5	10.5	0.374	0.413
B	8.3	8.7	0.327	0.342
C	13.3	13.7	0.524	0.539
D	15.0	16.0	0.592	0.628
E	8.5	9.1	0.335	0.358
F	9.5	10.1	0.374	0.398
G	2.4	3.0	0.094	0.118
H	0.5	0.7	0.020	0.028
J	2.7	3.7	0.106	0.146
K	1.9	2.1	0.075	0.083
L	4.7	5.1	0.185	0.201
M	14.2	14.8	0.559	0.583
N	3.5	4.1	0.138	0.161
P	1.6	2.2	0.063	0.087

TAPE AND REEL SPECIFICATION-DO-218AB



Ref.	Dimensions	
	Millimeters	Inches
A0	10.80 ± 0.3	0.425 ± 0.012
B0	16.13 ± 0.3	0.635 ± 0.012
C	330.0 ± 0.3	13.0 ± 0.012
D0	1.55 ± 0.2	0.061 ± 0.008
D1	1.55 ± 0.2	0.061 ± 0.008
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.30 ± 0.2	0.524 ± 0.008
F	11.50 ± 0.2	0.453 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	16.00 ± 0.2	0.630 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	24.00 ± 0.2	0.945 ± 0.008
W1	25.85 ± 0.2	1.018 ± 0.008

ORDERING INFORMATION				
PART No.	UNIT WEIGHT (g) typ	REEL (PCS)	PER CARTON (PCS)	DESCRIPTION
SM8SxxCA-AL	2.985	750	3000	13 inch reel pack

JieJie products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable JieJie product documentation. Warranties granted by JieJie shall be deemed void for products used for any purpose not expressly set forth in applicable JieJie documentation. JieJie shall not be liable for any claims or damages arising out of products used in applications not expressly intended by JieJie as set forth in applicable JieJie documentation. The sale and use of JieJie products is subject to JieJie terms and conditions of sale, unless otherwise agreed by JieJie.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 4.2nd version which is made in 7-Apr.-2022. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright©2022 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.