


## SMFxx(C)A-AU Series 200W Transient Voltage Suppressor

Rev.1.0

### DESCRIPTION

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, telecommunications and intelligent control systems.




SOD-123FL

### FEATURES

- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 200W peak pulse power capability at 10/1000μs waveform.
- ✧ Typical  $I_R$  less than 1μA.
- ✧ Fast response time: typically less than 1.0ps from 0V to  $V_{BR}$  min.
- ✧ High temperature reflow soldering: 260°C/40s at terminals.
- ✧ Plastic package has underwriters laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD-020, LF maximum peak of 260°C.
- ✧ Terminal: solder plated, solderable per J-STD-002.
- ✧ IEC61000-4-2 (ESD) ±30kV (air), ±30kV (contact).
- ✧ For surface mounted applications in order to optimize board space.
- ✧ High reliability application and automotive grade (AEC-Q101 qualified).



Bi-directional



Uni-directional

Symbol

### ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Storage and operating junction temperature range	$T_{STG}/T_J$	-55 to +150	°C
Peak pulse power dissipation at 10/1000μs waveform	$P_{PP}$	200	W
Maximum instantaneous forward voltage at 20A for unidirectional	$V_F$	3.5	V
Typical thermal resistance junction to lead	$R_{\theta JL}$	100	°C/W
Typical thermal resistance junction to ambient	$R_{\theta JA}$	220	°C/W

## MARKING



10CH : Device Marking Code

ELECTRICAL CHARACTERISTICS( $T_A=25^{\circ}\text{C}$ )


Part Number		Marking		$V_R$	$I_R @ V_R$	$V_{BR} @ I_T$		$I_T$	$V_C @ I_{PP}$	$I_{PP}^{\circ}$
Uni-Polar	Bi-Polar	Uni	Bi	V	Max ( $\mu\text{A}$ )	Min (V)	Max (V)	mA	Max (V)	A
SMF10A-AU	SMF10CA-AU	KXH	10CH	10.0	1	11.10	12.30	1	17.0	11.8
SMF11A-AU	SMF11CA-AU	KZH	11CH	11.0	1	12.20	13.50	1	18.2	11.0
SMF12A-AU	SMF12CA-AU	LEH	12CH	12.0	1	13.30	14.70	1	19.9	10.1
SMF13A-AU	SMF13CA-AU	LGH	13CH	13.0	1	14.40	15.90	1	21.5	9.3
SMF14A-AU	SMF14CA-AU	LKH	14CH	14.0	1	15.60	17.20	1	23.2	8.6
SMF15A-AU	SMF15CA-AU	LMH	15CH	15.0	1	16.70	18.50	1	24.4	8.2
SMF16A-AU	SMF16CA-AU	LPH	16CH	16.0	1	17.80	19.70	1	26.0	7.7
SMF17A-AU	SMF17CA-AU	LRH	17CH	17.0	1	18.90	20.90	1	27.6	7.2
SMF18A-AU	SMF18CA-AU	LTH	18CH	18.0	1	20.00	22.10	1	29.2	6.8
SMF20A-AU	SMF20CA-AU	LVH	20CH	20.0	1	22.20	24.50	1	32.4	6.2
SMF22A-AU	SMF22CA-AU	LXH	22CH	22.0	1	24.40	26.90	1	35.5	5.6
SMF24A-AU	SMF24CA-AU	LZH	24CH	24.0	1	26.70	29.50	1	38.9	5.1
SMF26A-AU	SMF26CA-AU	MEH	26CH	26.0	1	28.90	31.90	1	42.1	4.8
SMF28A-AU	SMF28CA-AU	MGH	28CH	28.0	1	31.10	34.40	1	45.4	4.4
SMF30A-AU	SMF30CA-AU	MKH	30CH	30.0	1	33.30	36.80	1	48.4	4.1
SMF33A-AU	SMF33CA-AU	MMH	33CH	33.0	1	36.70	40.60	1	53.3	3.8
SMF36A-AU	SMF36CA-AU	MPH	36CH	36.0	1	40.00	44.20	1	58.1	3.4
SMF40A-AU	SMF40CA-AU	MRH	40CH	40.0	1	44.40	49.10	1	64.5	3.1
SMF43A-AU	SMF43CA-AU	MTH	43CH	43.0	1	47.80	52.80	1	69.4	2.8
SMF45A-AU	SMF45CA-AU	MVH	45CH	45.0	1	50.00	55.30	1	72.7	2.7
SMF48A-AU	SMF48CA-AU	MXH	48CH	48.0	1	53.30	58.90	1	77.4	2.6
SMF51A-AU	SMF51CA-AU	MZH	51CH	51.0	1	56.70	62.70	1	82.4	2.4
SMF54A-AU	SMF54CA-AU	NEH	54CH	54.0	1	60.00	66.30	1	87.1	2.3

ELECTRICAL CHARACTERISTICS( $T_A=25^{\circ}\text{C}$ , continued)

Part Number		Marking		$V_R$	$I_R @ V_R$	$V_{BR} @ I_T$		$I_T$	$V_C @ I_{PP}$	$I_{PP}^{\text{①}}$
Uni-Polar	Bi-Polar	Uni	Bi	V	Max ( $\mu\text{A}$ )	Min (V)	Max (V)	mA	Max (V)	A
SMF58A-AU	SMF58CA-AU	NGH	58CH	58.0	1	64.40	71.20	1	93.6	2.1
SMF60A-AU	SMF60CA-AU	NKH	60CH	60.0	1	66.70	73.70	1	96.8	2.0
SMF64A-AU	SMF64CA-AU	NMH	64CH	64.0	1	71.10	78.60	1	103.0	1.9
SMF70A-AU	SMF70CA-AU	NPH	70CH	70.0	1	77.80	86.00	1	113.0	1.8
SMF75A-AU	SMF75CA-AU	NRH	75CH	75.0	1	83.30	92.10	1	121.0	1.7
SMF78A-AU	SMF78CA-AU	NVH	78CH	78.0	1	86.70	95.80	1	126.0	1.6
SMF85A-AU	SMF85CA-AU	NXH	85CH	85.0	1	94.40	104.0	1	137.0	1.5
SMF90A-AU	SMF90CA-AU	NZH	90CH	90.0	1	100.0	111.0	1	146.0	1.4
SMF100A-AU	SMF100CA-AU	PEH	100CH	100.0	1	111.0	123.0	1	162.0	1.2
SMF110A-AU	SMF110CA-AU	PGH	110CH	110.0	1	122.0	135.0	1	177.0	1.1
SMF120A-AU	SMF120CA-AU	PKH	120CH	120.0	1	133.0	147.0	1	193.0	1.0
SMF130A-AU	SMF130CA-AU	PMH	130CH	130.0	1	144.0	159.0	1	209.0	0.9
SMF150A-AU	SMF150CA-AU	PRH	150CH	150.0	1	167.0	185.0	1	243.0	0.8
SMF160A-AU	SMF160CA-AU	PVH	160CH	160.0	1	178.0	197.0	1	259.0	0.8
SMF170A-AU	SMF170CA-AU	PXH	170CH	170.0	1	189.0	209.0	1	275.0	0.7
SMF180A-AU	SMF180CA-AU	PZH	180CH	180.0	1	201.0	222.0	1	292.0	0.7
SMF200A-AU	SMF200CA-AU	QEH	200CH	200.0	1	224.0	247.0	1	324.0	0.6
SMF220A-AU	SMF220CA-AU	QRH	220CH	220.0	1	246.0	272.0	1	356.0	0.5

① Surge waveform: 10/1000 $\mu\text{s}$  $V_R$ : Stand-off voltage -- maximum voltage that can be applied $V_{BR}$ : Breakdown voltage $V_C$ : Clamping voltage -- peak voltage measured across the suppressor at a specified  $I_{PP}$  $I_R$ : Reverse leakage current

ORDERING INFORMATION



RATINGS AND V-I CHARACTERISTICS CURVES ( $T_A=25^\circ C$ , unless otherwise noted)

FIG.1:V- I curve characteristics (Uni-directional)




FIG.2:V- I curve characteristics (Bi-directional)




FIG.3: Pulse waveform






FIG.4: Pulse derating curve




**FIG.5: Peak pulse power dissipation vs. pulse width**




## SOLDERING PARAMETERS

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(min)}$ )	+150°C
	-Temperature Max( $T_{s(max)}$ )	+200°C
	-Time (Min to Max) ( $t_s$ )	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak)		3°C/sec. Max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquidus)	+217°C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_p$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp ( $T_p$ )		8 min. Max
Do not exceed		+260°C




PACKAGE MECHANICAL DATA



SOD-123FL

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.60	3.00	0.102	0.118
B	1.60	2.00	0.063	0.079
C	3.45	3.95	0.136	0.156
D	0.10	0.25	0.004	0.01
E	0.3	0.9	0.012	0.035
F	0.80	1.20	0.031	0.047
G	0.70	1.00	0.028	0.039
J	1.30		0.051	
K		1.70		0.067
L	1.30		0.051	

TAPE AND REEL SPECIFICATION-SOD-123FL



Ref.	Dimensions	
	Millimeters	Inches
A0	1.95 ± 0.3	0.077 ± 0.012
B0	3.95 ± 0.3	0.156 ± 0.012
C	178	7.0
D0	1.55 ± 0.1	0.061 ± 0.004
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.3 ± 0.3	0.524 ± 0.012
F	3.50 ± 0.2	0.138 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	4.00 ± 0.2	0.157 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	8.0 ± 0.2	0.315 ± 0.008
W1	11.5 ± 1.0	0.453 ± 0.039

PART No.	UNIT WEIGHT (g/PCS) TYP	REEL (PCS)	PER CARTON (PCS)	DESCRIPTION
SMFxxA/CA-AU	0.0144	3000	150,000	7 inch reel pack

JieJie products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable JieJie product documentation. Warranties granted by JieJie shall be deemed void for products used for any purpose not expressly set forth in applicable JieJie documentation. JieJie shall not be liable for any claims or damages arising out of products used in applications not expressly intended by JieJie as set forth in applicable JieJie documentation. The sale and use of JieJie products is subject to JieJie terms and conditions of sale, unless otherwise agreed by JieJie.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the first version which is made in 15-Dec.-2022. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ©2022 Jiangsu JieJie Microelectronics Co., Ltd. Printed All rights reserved.

单击下面可查看定价，库存，交付和生命周期等信息

[>>JW\(捷捷微\)](#)