




### FEATURES


- ◇ 300 Watts peak pulse power per line ( $t_P=8/20\mu s$ )
- ◇ Protects four I/O lines
- ◇ Low clamping voltage
- ◇ Low operating voltage
- ◇ Low capacitance
- ◇ RoHS compliant



SOT-143

### MAIN APPLICATIONS

- ◇ USB power and data line protection
- ◇ Digital video interface (DVI)
- ◇ Notebook computers
- ◇ Video graphics cards
- ◇ Monitors and flat panel displays
- ◇ 10/100 ethernet
- ◇ SIM ports
- ◇ ATM interfaces



PIN Configuration

### PROTECTION SOLUTION TO MEET

- ◇ IEC61000-4-2 (ESD)  $\pm 30kV$  (air),  $\pm 30kV$  (contact)
- ◇ IEC61000-4-4 (EFT) 40A (5/50ns)
- ◇ IEC61000-4-5 (Lightning) 20A (8/20 $\mu s$ )

### MECHANICAL CHARACTERISTICS

- ◇ JEDEC SOT-143 package
- ◇ Molding compound flammability rating: UL 94V-0
- ◇ Quantity per reel: 3,000pcs
- ◇ Lead finish: Lead free
- ◇ Marking code: R05

**ABSOLUTE MAXIMUM RATINGS** ( $T_A=25^{\circ}\text{C}$ , RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak pulse power dissipation on 8/20 $\mu\text{s}$ waveform	$P_{PP}$	300	W
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	$V_{ESD}$	+/-30 +/-30	kV
Lead soldering temperature	$T_L$	260 (10 sec.)	$^{\circ}\text{C}$
Operating junction temperature range	$T_J$	-55 to +125	$^{\circ}\text{C}$
Storage temperature range	$T_{STG}$	-55 to +150	$^{\circ}\text{C}$

**ELECTRICAL CHARACTERISTICS** ( $T_A=25^{\circ}\text{C}$ )

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse working voltage	$V_{RWM}$				5.0	V
Reverse breakdown voltage	$V_{BR}$	$I_T=1\text{mA}$	6.0			V
Reverse leakage current	$I_R$	$V_{RWM}=5\text{V}$			0.1	$\mu\text{A}$
Clamping voltage (I/O pin to ground)	$V_C$	$I_{PP}=5\text{A}$ , $t_P=8/20\mu\text{s}$		11	12.5	V
		$I_{PP}=20\text{A}$ , $t_P=8/20\mu\text{s}$		16	18	
Clamping voltage ( $V_{CC}$ to ground))	$V_C$	$I_{PP}=10\text{A}$ , $t_P=8/20\mu\text{s}$		10	12	V
		$I_{PP}=25\text{A}$ , $t_P=8/20\mu\text{s}$		13	20	
Junction capacitance	$C_J$	$V_{RWM}=0\text{V}$ , $f=1\text{MHz}$ Any I/O pin to ground		3	3.5	pF
		$V_{RWM}=0\text{V}$ , $f=1\text{MHz}$ Between I/O pins		1.5	2	

RATINGS AND V-I CHARACTERISTICS CURVES (T<sub>A</sub>=25°C, unless otherwise noted)

FIG.1: V- I curve characteristics (Uni-directional)




FIG.2: Pulse waveform (8/20µs)




FIG.3: Pulse derating curve






FIG.4: ESD clamping (30kV contact)




**SOLDERING PARAMETERS**

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ( $T_{s(min)}$ )	+150°C
	-Temperature Max( $T_{s(max)}$ )	+200°C
	-Time (Min to Max) ( $t_s$ )	60-180 secs.
Average ramp up rate (Liquidus Temp ( $T_L$ )to peak)		3°C/sec. Max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature( $T_L$ )(Liquidus)	+217°C
	-Temperature( $t_L$ )	60-150 secs.
Peak Temp ( $T_p$ )		+260(+0/-5)°C
Time within 5°C of actual Peak Temp ( $t_p$ )		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp ( $T_p$ )		8 min. Max
Do not exceed		+260°C




**PACKAGE MECHANICAL DATA**



Symbol	Millimeter			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.90	1.00	1.15	0.035	0.039	0.045
A1	0.00	0.065	0.10	0.000	0.003	0.004
A2	0.90	1.00	1.10	0.035	0.039	0.043
b	0.30	0.40	0.50	0.012	0.016	0.020
b1	0.75	0.81	0.90	0.030	0.032	0.035
c	0.05	0.10	0.15	0.002	0.004	0.006
D	2.70	2.90	3.10	0.106	0.114	0.122
d	0.20Typ.			0.008Typ.		
E	1.10	1.30	1.50	0.043	0.051	0.059
E1	2.20	2.40	2.60	0.087	0.094	0.102
e	0.95Typ.			0.037Typ.		
e1	1.80	1.90	2.00	0.071	0.075	0.079
L	0.55Typ.			0.022Typ.		
L1	0.30	0.40	0.50	0.012	0.016	0.020
θ	0°	-	8°	0°	-	8°

**TAPE AND REEL SPECIFICATION-SOT-143**



**Packaging description:**


SOT-143 parts are shipped in tape. The carrier tape is made from a dissipative(carbon filled) polycarbonate resin. The cover tape is a multilayer film(heat activated adhesive in nature)primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and made of polystyrene plastic(anti-static coated).

Symbol	Millimeters	Inches
	Typ.	Typ.
A	3.10	0.122
B	2.80	0.110
C	1.30	0.051
d	Φ1.50	Φ0.059
E	1.75	0.069
F	3.50	0.138
P0	4.00	0.157
P	4.00	0.157
P1	2.00	0.079
W	8.00	0.315
D	Φ178	7.008
D1	54.40	2.142
D2	13.00	0.512
G	R78.00	3.071
H	R25.60	1.008
I	R6.50	0.256
W1	9.50	0.374
W2	12.30	0.484

**ORDERING INFORMATION**

OUTLINE	PACKAGE TYPE	QUANTITY REEL	DESCRIPTION
TAPING	SOT-143	3,000	7 inch reel pack

**MARKING CODE**

Part Number	Marking Code
JEU05R	

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 4.2rd version which is made in 21-Dec.-2021. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright ©2021 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.