## KEMET Part Number: C0603T223K3RCLTU

(C0603T223K3RCL7867)



## SMD COTS X7R, Ceramic, 0.022 uF, 10%, 25 VDC, X7R, SMD, MLCC, COTS, Temperature Stable, Class II, 0603



| Dimensions |                  |  |
|------------|------------------|--|
| Chip Size  | 0603             |  |
| L          | 1.6mm +/-0.15mm  |  |
| W          | 0.8mm +/-0.15mm  |  |
| Т          | 0.8mm +/-0.07mm  |  |
| S          | 0.7mm MIN        |  |
| В          | 0.35mm +/-0.15mm |  |

| Packaging Specifications |                        |  |
|--------------------------|------------------------|--|
| Packaging:               | T&R, 180mm, Paper Tape |  |
| Packaging Quantity:      | 4000                   |  |

| General Information |   |      |
|---------------------|---|------|
| Series:             | SMD COTS X7R  |      |
| Style:              | SMD Chip  |      |
| Description:        | SMD, MLCC, COTS,<br>Temperature Stable, Class II  |      |
| Features:           | Temperature Stable, Class II  |      |
| RoHS:               | No  |      |
| Prop 65:            | WARNING: Cancer<br>and reproductive harm -<br>www.p65warnings.ca.gov.   |      |
| SCIP Number:        | 2d771165-5336-48a3-96fa-3663929f  | d828 |
| Termination:        | Lead (SnPb)   |      |
| Marking:            | No  |      |
| Failure Rate:       | Testing per MIL-PRF-55681 PDA<br>8%, DPA per EIA-469, Humidity<br>per MIL-STD-202, Method 103,<br>Condition A |      |
| AEC-Q200:           | No  |      |
| Component Weight:   | 4800 ug   |      |
| Shelf Life:         | 78 Weeks  |      |
| MSL:                | 1   |      |

| Specifications  |  |  |
|---|--|--|
| Capacitance:  | 0.022 uF   |  |
| Measurement Condition:  | 1 kHz 1.0Vrms                                      |  |
| Capacitance Tolerance:  | 10%  |  |
| Voltage DC:   | 25 VDC   |  |
| Dielectric Withstanding<br>Voltage:                                       | 62.5 VDC   |  |
| Temperature Range:  | -55/+125°C   |  |
| Temperature Coefficient:  | X7R  |  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC): | 15%, 1kHz 1.0Vrms                                  |  |
| Dissipation Factor:   | 3.5% 1 kHz 1.0Vrms                                 |  |
| Aging Rate:   | 3% Loss/Decade Hour: Referee<br>Time is 1000 Hours |  |
| Insulation Resistance:  | 45.4545 GOhms                                      |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)