

KEMET Part Number: PHE845VF6330KR06L2
(F845FS334K760Z, PHE845VF6330KF15R06L2)

KEMET

a YAGEO company

PHE845/F845, Film, Metallized Polypropylene, Safety, 0.33 uF, 10%, 760 VAC (X1), 1500 VDC, 105°C, Lead Spacing = 27.5mm



Dimensions

L	31.5mm MAX
H	29mm MAX
T	19mm MAX
S	27.5mm +/-0.4mm
LL	6mm -1mm
F	0.8mm NOM

Packaging Specifications

Packaging:	Pizza, Box
Packaging Quantity:	117

General Information

Series:	PHE845/F845
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X1
Qualifications:	ENEC, UL, cUL
AEC-Q200:	No
THB Performance:	Yes

Specifications

Capacitance:	0.33 uF
Capacitance Tolerance:	10%
Voltage AC:	760 VAC (X1)
Voltage DC:	1500 VDC
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Dissipation Factor:	0.1% 1kHz, 0.4% 10kHz
Insulation Resistance:	30 GOhms
Max dV/dt:	100 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)