


RSBMC2470AA00K

Aliases (SBMC2470AA00K)

RSB, Film, Metallized Polyester Stacked, Automotive Grade, 0.047 uF, 10%, 400 VDC, 85°C, Lead Spacing = 5mm



Click here for the 3D model.

Dimensions	
L	7.2mm +0.3mm
н	11mm +0.1mm
т	6mm +0.2mm
S	5mm +/-0.4mm
LL	4mm +1.5mm
F	0.5mm +/-0.05mm

Packaging Specifications		
Packaging	Bulk	
Packaging Quantity	2000	

General Information	
Series	RSB
Dielectric	Metallized Polyester Stacked
Style	Radial
Features	Automotive Grade, DC Multipurpose Applications
RoHS	Yes
Lead	Cut
Qualifications	AEC-Q200
AEC-Q200	Yes
Component Weight	0.95 g
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Specifications		
Capacitance	0.047 uF	
Capacitance Tolerance	10%	
Voltage AC	200 VAC	
Voltage DC	400 VDC	
Temperature Range	-55/+125°C	
Rated Temperature	85°C	
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz	
Insulation Resistance	30 GOhms	
Max dV/dt	600 V/us	
Inductance	7 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)