
KEMET Part Number: MMK37.5335K400R05L4TRAY

(F601RF335K400C, MMK37,5335K400R05L4TRAY)



MMK/F601, Film, Metallized Polyester, General Purpose, 3.3 uF, 10%, 400 VDC, 85°C, Lead Spacing = 37.5mm



General Information	
Series:	MMK/F601
Dielectric:	Metallized Polyester
Style:	Radial
Features:	DC Multipurpose Applicatiions
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Dimensions	
L	41mm MAX
Н	24mm MAX
Т	13mm MAX
S	37.5mm +/-0.5mm
LL	5mm NOM
F	1mm NOM

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	140	

Specifications	
Capacitance:	3.3 uF
Capacitance Tolerance:	10%
Voltage AC:	200 VAC
Voltage DC:	400 VDC, 310 VDC (100C)
Temperature Range:	-55/+100°C
Rated Temperature:	85°C
Dissipation Factor:	1% 1kHz
Insulation Resistance:	3.0303 GOhms
Max dV/dt:	5 V/us
Inductance:	6 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2022 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)