



Click [here](#) for the 3D model.

Dimensions

| | |
|---|----------|
| L | 91mm MIN |
| W | 51mm MIN |
| H | 45mm MIN |

Packaging Specifications

| | |
|--------------------|-------|
| Packaging | Bulk |
| Packaging Quantity | 1 |
| Component Weight | 350 g |

General Information

| | |
|----------------|-------------------------------------|
| Series | FLLE2-R |
| Style | Chassis Mount |
| Description | Single Phase, Chassis Mount Filters |
| Features | Single Phase |
| Phase | Single-phase |
| RoHS | Yes |
| Qualifications | IEC/EN 60939, UL, CSA |
| Terminal Type | Threaded Studs M4 |

Specifications

| | |
|----------------------------|---------------|
| Voltage AC | 300 VAC |
| Voltage DC | 300 VDC |
| Rated Frequency | 50-60 Hz |
| Rated Current | 20 A |
| Rated Temperature | 40°C |
| Temperature Range | -25/+100°C |
| Climate Category | 25/100/21 |
| Leakage Current | 0.37 mA (MAX) |
| Test Voltage DC (P/N to E) | 2250 VDC |
| Test Voltage DC (P to N) | 1300 VDC |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)