



Click [here](#) for the 3D model.

| Dimensions | |
|------------|----------------|
| D | 12mm MAX |
| T | 5mm MAX |
| S | 10mm MAX |
| LL | 5mm +/-1mm |
| F | 0.6mm +/-0.1mm |
| A | 4mm MAX |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 400 |

| General Information | |
|---------------------|----------------------------|
| Series | C700KJY SFTY X1-400 Y2-250 |
| Style | Radial Disc |
| RoHS | Yes |
| Termination | Tin |
| Failure Rate | N/A |
| Qualifications | UL, CSA, TUV |
| AEC-Q200 | No |

| Specifications | |
|---------------------------------|----------------------------|
| Capacitance | 4700 pF |
| Capacitance Tolerance | 20% |
| Voltage AC | 400 VAC (X1), 250 VAC (Y2) |
| Dielectric Withstanding Voltage | 2600 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | Y5V |
| Dissipation Factor | 5% 1 kHz 5.0Vrms |
| Insulation Resistance | 10 GOhms |
| Safety Class | X1/Y2 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)